Crownline Cabinets Provide A Wide Selection of Door Styles, Glazing and Sizes. These Durable Cabinets are Designed to Industry Standards for Fire Department Valves, Fire Hose Rack Units and Extinguishers.

Door & Trim: Clear anodized aluminum. 1-3/4" Trim on face and door. These flush cabinet doors are mounted in a 5/8" door stop, are attached by a continuous hinge and are equipped with zinc-plated handle and roller catch for all non-locking doors. Theft-deterrent SAF-T-LOK™ also available.

Trim Style and Depth: 1-3/4" face trim on frame and 1-1/4" trim on door. Recessed - 3/8" flat trim.

Semi-recessed - 1-1/4" Square Edge or 2-1/2" Rolled Edge. Rolled edge models are constructed of mechanically-joined extrusions (see photo).

Surface mounted - Square edge. See separate submittal for trimless.

Tub: CRS, white powder-coat finish standard. Surface-mounted tubs are of the same material as the door and trim

Knockouts: K.O's are provided on both sides of the cabinet. K.O.'s on left side will be located using "J" dimension, K.O.'s on right side using "K" dimension and may be offset from K.O.'s on "J" side of cabinet. Models 6027 & 6227 - Specify knockout

location. Provided on surface mounted cabinets by request except for rolled edge models. Custom location K.O.'s available. See page 2 for drawings of K.O. locations.

Special Features: Models 8025, 8026, 8027 & 8023 have a shelf 12" from the bottom of the cabinet and are designed to hold a fire extinguisher plus FD valve or other accessory. Those models can also be ordered without shelf to allow for lower mounting height of valve piping to meet NFPA14.


Fire-Rated Option Available: Yes - See separate submittal.



STEP 1: SELECT MODEL NUMBER, TRIM & QUANTITY (Refer to Chart on Page 2)


911	EP 2: SELECT DOOR STYLE	(Check one box below)								
	F Full Glazing		L22 Solid with SAF-T-LOK							
	G Full Glazing with SAF-T-LOK™		V Vertical Duo							
	D Horizontal Duo Panel		W Vertical Duo with SAF-T-LOK							
	E Horizontal Duo Panel with SAF-T-LOK		B10 Acrylic View Window with SAF-T-LOK							
	A Center Duo Panel with SAF-T-LOK		L24 Solid with Cylinder Lock & No Handle							
S21 Solid Door View Door Styles Online										
	ADA Cabinet Mounting Height: Standard Pull on G, E, W, L22, A and B Door Styles with Saf-T-Lok are 3 5/8" Higher than Door Center, so Allow for that When Mounting Cabinet. Standard Pull with No Lock or ADA Recessed Pull are Centered on Door.									
ST	STEP 3: <u>SELECT DOOR GLAZING</u> (Check one box below)									
	10 Clear Acrylic 16 Gray Acrylic									
	13 Clear Wire Glass with Safety Film 17 Clear Tempered Glass									

	15 Bronze Acrylic		18 Laminated Safety Glass	and Si 24 - Solid	
ST	EP 4: OPTIONAL FEATURES AT ADDIT	101		der key le (L22,24 r	
	Dark Bronze Anodized Door & Trim		PUCH Polished Chrome Handle		Blac
	(Pull will be painted to match)		FDVO Decal Fire Department Valve Octagonal 6 x 6"		Red
	Aluminum Tub - Clear Anodized		1403 Decal Fire Hose Black/Red Horiz. Letters 4 x 9		Whi
	Optional Tub Color: BlackRed		LDCHRFDV-R Diecut Fire Dept. Valve Horiz.10-1/4 x 4-3/8		Blad
	Futura "Fire" Handle Mill Red White		LDCVRFDV Diecut Fire Dept Valve Vert. 3/4" x 211/2"		Red
	PRH Recessed Pull Handle		LDCVRFDV-R Diecut Fire Dept Valve Vert. Rever. 3/4" x 211/	⁄2"	Whi
	SA Strobe Alarm (surface mount models)		LDCHRFDV Diecut Fire Department Valve Ascend. 1" x 17"		Etch
	CA Commander Alarm		LDCVRFSCV-R Diecut Fire Sprinkler Cont. Valve Vert 3/4"	' x 18"	(Ch
	BA Brigadier Alarm		Fire Hose Racks - See separate submittal		No :



G - Full glass with pull panel with pull handle and Saf-T-Lok E - Horizontal duo panel with pull and Saf (Not Shown) -T-Lok. (Not Shown)

V - Vertical duo panel W - Vertical duo panel with pull and Shown)



S21 - Solid with pull L22 - Solid with pull nd Saf-T-Lok Solid with cylinkey lock/no pull

B10 - Acrylic view window with pull, and Saf-T-Lok

A - Center duo panel with pull and Saf-T-Lok

Black Vertical FE Letters LDCVBFE
Red Vertical FE Letters LDCVRFE
White Vertical FE Letters LDCVWFE
Black Horizontal FE Letters LDCHBFE
Red Horizontal FF Letters I DCHRFF

White Horizontal FE Letters LDCHWFE Etched Glass/Engraved Metal Lettering

(Check Box & Attach Separate Submittal)


No Shelf for 8000 Series

It is the responsibility of the customer to communicate specifications and product performance requirements that are needed for their application. This document is intended to convey potential product configurations and offerings. It is not to be used to imply or represent a specification or rating, of finished products shipped. Detailed, specific submittals can be created upor request. It is the responsibility of the customer to specify product accordingly to comply with local laws, codes, and ordinances.




JL INDUSTRIES	Distributor:	Quantity:			
	Contractor:	Approved By:			
	Model #:	Architect:			
©2023 Activar Construction Products Group, Inc.	Project:	Date:			
		•			

SUBMITTAL: CROWNLINE VALVE & HOSE CABINETS - ALUMINUM



 Cabinets that meet ADA projection requirement



PAGE 2 OF 2

ADA Cabinet Mounting Height: Standard Pull on G, E, W, A,L22 and B Door Styles with Saf-T-Lok are 3 5/8" Higher than Door Center, so Allow for that When Mounting Cabinet. Standard Pull with No Lock or ADA Recessed Pull are Centered on Door.

	TRIM & DOOR TUB I.D. W x H x D FRAME O.D.			KNOCKOUT LOCATIONS			RECOMMENDED HOSE RACK,							
	TERIAL & SERIES		in Inches	С				LL OPE					FD VALVES & EXTINGUISHERS	
QTY #	TRIM STYLE				E Fustinan	F	Width			J G K s Indicated in Blue &				
6025	FLAT TRIM 3/8" •	Capiner 24	30	e Rack	x =xung ı 27 3/8	33 3/8	25	31	5 7/8	2 1/2	≆0 III 4	2 1/2	HOSE RACK:	
6026		24	30	6	27 3/8	33 3/8	25	31	4 7/8	2 1/2	4	2 1/2	1- 1/2" x 1-1/2" Hose Rack Unit with 50	
6027		24	30	6	27 3/8	33 3/8	25	31	4 1/4			Ordering	or 75' Hose (HRA:050B, 050CH, 075B,	
6023		27 3/16	33 3/16	6 1/2	27 3/8	33 3/8	-	_	, .	Upon			075CH) & Cosmic 2½ or	
6225		24	34 3/4	6	27 3/8	38 1/8	25	35 3/4	5 7/8	2 1/2	4	2 1/2	Galaxy 2½- 5 lb Extinguisher HOSE RACK:	
6226		24	34 3/4	6	27 3/8	38 1/8	25	35 3/4	4 7/8	2 1/2	4	2 1/2	1- 1/2" x 1-1/2" Hose Rack Unit - 100'	
6227		24	34 3/4	6	27 3/8	38 1/8	25	35 3/4	4 1/4			Ordering	Hose (HRA 100B, HRA100CH)	
6223		27 3/16	37 15/16	6 1/2	27 3/8	38 1/8	_	_	, .		n Red	•	& Cosmic 2½ or	
6125		24	30	8	27 3/8	33 3/8	25	31	7 7/8	4	4	2 1/2	Galaxy 2½- 5 lb Extinguisher	
6126		24	30	8	27 3/8	33 3/8	25	31	6 7/8	4	4	2 1/2	HOSE RACK: 2-1/2" x 1-1/2" Hose Rack Unit	
6127		24	30	8	27 3/8	33 3/8	25	31	6 1/4	4	4	2 1/2	50 or 75' Hose	
6123		27 3/16	33 3/16	8 1/2	27 3/8	33 3/8	-	-	-		n Red		(HRA050B-2.5, HRA075B-2.5)	
6425		24	34 3/4	8	27 3/8	38 1/8	25	35 3/4	7 7/8	4	4	2 1/2		
6426		24	34 3/4	8	27 3/8	38 1/8	25	35 3/4	6 7/8	4	4	2 1/2	HOSE RACK:	
6427		24	34 3/4	8	27 3/8	38 1/8	25	35 3/4	6 1/4	4	4	2 1/2	2-1/2" x 1-1/2" Hose	
6423	SURFACE MOUNTED	27 3/16	37 15/16	8 1/2	27 3/8	38 1/8	_	_	_	Upo	n Red		Rack Unit 100' Hose (HRA100B-2.5)	
6625	FLAT TRIM 3/8" •	24	38 3/4	8	27 3/8	42 1/8	25	39 3/4	7 7/8	4	4	2 1/2		
6626	1-1/4" SQUARE EDGE•	24	38 3/4	8	27 3/8	42 1/8	25	39 3/4	6 7/8	4	4	2 1/2	HOSE RACK : 2-1/2" x 1-1/2" Hose	
6627		24	38 3/4	8	27 3/8	42 1/8	25	39 3/4	6 1/4	4	4	2 1/2	Rack Unit 125' Hose (HRA125B-2.5)	
6623	SURFACE MOUNTED	27 3/16	41 15/16	8 1/2	27 3/8	42 1/8	-	-	-	Upo	n Red	quest	,	
6325		30	30	8	33 3/8	33 3/8	31	31	7 7/8	4	4	2 1/2	HOSE RACK & FD VALVE	
6326		30	30	8	33 3/8	33 3/8	31	31	6 7/8	4	4	2 1/2	OR EXTINGUISHER: 1-1/2" OR 2-1/2" Valve 50' or 75' Hose	
6327		30	30	8	33 3/8	33 3/8	31	31	6 1/4	4	4	2 1/2	Rack Unit Plus FD Valve Cosmic or	
6323	SURFACE MOUNTED	33 3/16	33 3/16	8 1/2	33 3/8	33 3/8	-	-	-	Upo	n Red	quest	Galaxy Extinguisher	
6525	FLAT TRIM 3/8" •	32 3/4	34 3/4	8	36 1/8	38 1/8	33 3/4	35 3/4	7 7/8	4	4	2 1/2	HOSE RACK & FD VALVE	
6526		32 3/4	34 3/4	8	36 1/8	38 1/8	33 3/4	35 3/4	6 7/8	4	4	2 1/2	OR EXTINGUISHER:	
6527	2-1/2" ROLLED EDGE•	32 3/4	34 3/4	8	36 1/8	38 1/8	33 3/4	35 3/4	6 1/4	4	4	2 1/2	1-1/2" OR 2-1/2" Valve, 100' Hose Rack Unit Plus FD Valve or Cosmic or Galaxy	
6523	SURFACE MOUNTED	35 15/16	37 15/16	8 1/2	36 1/8	38 1/8	_	-	-	Upo	n Red	quest	Extinguisher	
722	FLAT TRIM 3/8" •	32 3/4	38 3/4	8	36 1/8	42 1/8	33 3/4	39 3/4	7 7/8	4	4	2 1/2	HOSE RACK & FD VALVE	
7226	1-1/4" SQUARE EDGE•	32 3/4	38 3/4	8	36 1/8	42 1/8	33 3/4	39 3/4	6 7/8	4	4	2 1/2	OR EXTINGUISHER:	
7227	2-1/2" ROLLED EDGE•	32 3/4	38 3/4	8	36 1/8	42 1/8	33 3/4	39 3/4	6 1/4	4	4	2 1/2	1-1/2" OR 2-1/2" Valve, 125' Hose Rack Unit Plus FD Valve or Cosmic or Galaxy	
7223	SURFACE MOUNTED	35 15/16	41 15/16	8 1/2	36 1/8	42 1/8	_	-	-	Upo	n Red	quest	Extinguisher	
					Cabin	ets for Fir	e Depart	ment Va	ves				<u> </u>	
8525	FLAT TRIM 3/8" •	18	18	8	21 3/8	21 3/8	19	19	7 7/8	4	9	2 1/2		
8526		18	18	8	21 3/8	21 3/8	19	19	6 7/8	4	9	2 1/2		
8527		18	18	8	21 3/8	21 3/8	19	19	6 1/4	4	9	2 1/2	FIRE DEPARTMENT VALVE:	
8523		21 3/16		8 1/2	21 3/8	21 3/8	-	-	-			quest	1-1/2" or 2-1/2"	
	FLAT TRIM 3/8" •	18	18	10	21 3/8	21 3/8	19	19	9 7/8	5	9	5	Fire Department Valve with Cap and Chain	
8426	3 1-1/4" SQUARE EDGE ● 2-1/2" ROLLED EDGE ●	18 18	18 18	10 10	21 3/8 21 3/8	21 3/8 21 3/8	19 19	19 19	8 7/8 8 1/4	5 5	9	5 5	Cap and Chain	
8423		21 3/16	21 3/16	10 1/2	21 3/8	21 3/8	-	-	0 1/4		n Red			
8725		26	26	8	29 3/8	29 3/8	27	27	7 7/8	4	13	2 1/2		
8726		26	26	8	29 3/8	29 3/8	27	27	6 7/8	4	13	2 1/2		
8727		26	26	8	29 3/8	29 3/8	27	27	6 1/4	4	13	2 1/2	DUAL SIDE BY SIDE FIRE DEPART-	
8723		29 3/16		8 1/2	29 3/8	29 3/8	-	-	_	Upo	n Red	quest	MENT VALVE & EXTINGUISHER OR 2 FIRE DEPARTMENT VALVES:	
8625	FLAT TRIM 3/8" ●	26	26	10	29 3/8	29 3/8	27	27	9 7/8	5	13	5	1-1/2" or 2-1/2" FD Valve w/Cap and Chain	
8626		26	26	10	29 3/8	29 3/8	27	27	8 7/8	5	13	5	Plus Extinguisher - Cosmic & Galaxy 2.5-10	
8627		26	26	10	29 3/8	29 3/8	27	27	8 1/4	5	13	5	•	
8623		29 3/16		10 1/2	29 3/8	29 3/8	- 47	-	- 0.7/0		n Red			
8025		16 16	40 40	9	19 3/8 19 3/8	43 3/8 43 3/8	17 17	41 41	8 7/8 7 7/8	4 1/4 4 1/4	6	4 1/4 4 1/4	DUAL EXTINGUISHER & FD VALVE	
8026	7 2-1/2" ROLLED EDGE	16	40	9	19 3/8	43 3/8	17	41	7 1/4	4 1/4	6	4 1/4	CABINET W/SHELF: Shelf is 12" from bottom. Cosmic or Galaxy	
	SURFACE MOUNTED		43 3/16	9 1/2	19 3/8	43 3/8	-	-	-		n Red		Extinguisher	
002	, JOSINI / IOE MODITIED	10 0/10	70 0/10	V 1/2	10 0/0	70 0/0			_	U O P O		14001	U	