



EQUIPMENT SERIES: DOUBLE LEAF HATCHES

Our double door steel or aluminum equipment hatches are ideal for equipment installation and servicing from the roof.

Product Details:

Curb: 14 gauge galvanized steel or 11 gauge aluminum 12" single wall curb with 4" wide flange includes holes for securing to roof deck.

Cover: 14 gauge galvanized steel or 11 gauge aluminum exterior and liner. Hinged on the "length" side. Oversize doors may be spliced.

Gasketing: Continuous, weatherproof bulb neoprene door seal.

Insulation: The cover has 1" fiberglass insulation, and the curb has 1" rigid fiber insulation.

Finish: 2 coats silver prime coat.

Hardware: Heavy-duty galvanized hinges, automatic hold-open, and operating arms with red vinyl handlegrip. Cover hardware has two point universal spring latches, with both exterior and interior handles and padlock hasps.

Spring: Standard lift springs are pressure intensifiers. Adjustable torsion springs are provided for oversized models.

Sizes: Roof opening size is order size. Clear opening is minus 8" on width and minus 4" on length.

Options: R 11.4 polyiso insulation, double wall curb, optional colors, custom sizes.

Roof Opening W x L (L = Hinge Side)	Steel	Aluminum	Domed Steel	Domed Aluminum
72" x 96"	EHG-1	EHA-1	DEHG-1	DEHA-1
60" x 120"	EHGA-2*	EHA-2	DEHGA-2*	DEHA-2
120" x 120"	EHGA-3*	EHA-3	DEHGA-3*	DEHA-3
144" x 144"	EHGA-4*	EHA-4	DEHGA-4*	DEHA-4
* Steel curb with aluminum covers				

EQUIPMENT SERIES: DOUBLE LEAF DOMED HATCHES

Add more daylight into your building with domed equipment hatches.

Product Details:

Curb: 14 gauge galvanized steel or 11 gauge aluminum 12" single wall curb with 4" wide flange includes holes for securing to roof deck.

Cover: 14 gauge galvanized steel or 11 gauge aluminum exterior and liner. Hinged on the "length" side. Cover includes a one piece dome (or multiples) of either white or clear acrylic, a dome frame of extruded aluminum #6063-T5 and self-contained sloping condensation and weepage gutter for drainage. Oversize doors may be spliced.

Gasketing: Continuous, weatherproof bulb neoprene door seal.

Insulation: The cover has 1" fiberglass insulation, and curb has 1" rigid fiber insulation.

Finish: 2 coats silver prime coat.

Hardware: Heavy-duty galvanized hinges, automatic hold-open and operating arms with red vinyl handlegrip. Cover hardware has 2 point universal spring latch, with both exterior and interior handles and padlock hasps.

Spring: Standard lift springs are pressure intensifiers. Adjustable torsion springs are provided for oversized models.

Sizes: Roof opening size is order size. Clear opening is minus 8" on width and minus 4" on length.

Options: R 11.4 polyiso insulation, dual domes, double wall curb, optional colors, custom sizes.

