FIRE EXTINGUISHERS - ORBIT PURPLE K DRY CHEMICAL - Portable Handheld

Purple K extinguisher is suitable flammable liquid hazards in public areas such as offices, classrooms, churches, garages, service bays, boats, vehicles, fuel storage and transfer areas. It is not recommended for use on sensitive electronic equipment





CLASS B FIRES Flammable Liquids



CLASS C FIRES

Energized

Electrical

Button Hook for FPK10VB

SPECIFICATIONS:

The Orbit Fire Extinguisher is as much as 40 percent slimmer than traditional 10-lb. models, allowing for more efficient and elegant building design. It is the only 10-lb. fire extinguisher that is always compliant with ADA protruding object regulations and local building codes.

Purple K

Contain specially fluidized and siliconized potassium bicarbonate dry chemical which is particularly effective on Class B flammable liquids and pressurized gases. It is electrically non-conductive. Purple K is the preferred fire fighting agent of oil, gas, chemical and utilities industries

Conforms to Test Standards: CAN/ULC-S504 — ANSI/UL299 & CAN/ULC S508 — ANSI/UL711

Operation: Squeeze the lever, which opens the valve, allowing the chemical to be forced out. Upright squeeze grip operation. Approved to $-40^{\circ}F(-40^{\circ}C) - 120^{\circ}F(49^{\circ}C)$

Construction: Non-Magnetic corrosion-resistant tempered aluminum vessel with aluminum valve and siphon tube. Also features visual pressure gauge, stainless steel pull pin, handles, bracket and button hook. Durable powder coat finish. Tested to 3 Tesla.

Valve Material: Aluminum

All units meet the current requirements established by the National Fire Protection Association (NFPA) for NFPA10 "Standard for Portable Fire Extinguishers", and any other applicable NFPA standards. Tested and listed by UL to meet construction and performance standards for this type of extinguisher, and can by used where required by local codes such as OSHA.

Q	ety.	Model	Туре	Nominal Capacity	Shipping Weight	Cylinder Dia.	Overall Height	Overall Width	Shipping Vol. Approx.	UL Rating 🕕	Mounting	USCG Approved
	FP	K10VB	Purple K	10 lbs.	22 lbs.	3.5″	23″	9″	1.35 cu.ft.	80B:C	Surface	

Note: NFPA regulations also require extinguishers to be inspected when initially placed in service and all local fire code and tagging requirements must be adhered to. All fire extinguisher sizes are nominal. Contact Customer Service for more information about ordering tagged extinguishers in your area.

	& 800-554-6077	Distributor:		Project:	
JL INDUSTRIES	Sales@activarcpg.com	Contractor:		Approved By:	
	www.activarcpg.com	Date:		Architect:	
9702 Newton Ave S. Bloomington, MN 55431 N	Scale: N/A	Pages: 1 of 1	Item #:		
© 2022 Activar Construction Products Group, Inc. THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ACTIVAR CONSTRUCTION PRODUCTS GROUP, INC. IS PROHIBITED.					