## FIRE EXTINGUISHERS - ORBIT MULTI-PURPOSE DRY CHEMICAL - Portable Handheld

ABC dry chemical is a multipurpose extinguishing agent that is suitable for use in offices, classrooms, churches, parking garages and retail. Not recommended for use on sensitive electronic equipment.







Liauids

and Gases

**CLASS C FIRES** 

**CLASS A FIRES** CLASS B FIRES Common Flammable Combustibles

Energized Electrical Equipment



Button Hook for FE10VB & FPK10VB

## SPECIFICATIONS:

The Orbit Fire Extinguisher is as much as 40 percent slimmer than traditional 10-lb. models, allowing for more efficient and elegant building design. It is the only 10-lb. fire extinguisher that is always compliant with ADA protruding object regulations and local building codes.

## **ABC Dry Chemical**

These units contain specially fluidized and siliconized mono ammonium phosphate powder, which smothers and breaks the chain reaction on Class B fires, fuses and insulates Class A fires and is a non-conductor of electricity. Non-toxic.

**Conforms to Test Standards:** CAN/ULC-S504 — ANSI/UL299 & CAN/ULC S508 — ANSI/UL711

**Operation:** Squeeze the lever, which opens the valve, allowing the chemical to be forced out. Upright squeeze grip operation. Approved to -40°F (-40°C) - 120° F (49°C)

**Construction:** Non-Magnetic corrosion-resistant tempered aluminum vessel with aluminum valve and siphon tube. Also features visual pressure gauge, stainless steel pull pin, handles, bracket and button hook. Durable powder coat finish. Tested to 3 Tesla.

Valve Material: Aluminum

All units meet the current requirements established by the National Fire Protection Association (NFPA) for NFPA10 "Standard for Portable Fire Extinguishers", and any other applicable NFPA standards. Tested and listed by UL to meet construction and performance standards for this type of extinguisher, and can by used where required by local codes such as OSHA.

Qty.	Model	Туре	Nominal Capacity	Shipping Weight	Cylinder Dia.	Overall Height	Overall Width	Shipping Vol. Approx.	UL Rating 🕕	Mounting	USCG Approved
	FE10V	ABC Dry	10 lbs.	24 lbs.	3″	22″	11″	1.35 cu.ft.	4A:80B:C	Surface or <u>3.25" Depth Cabinet</u>	
	FE10VB	Chemical	10 lbs.	22 lbs.	3.5″	23″	9″	1.35 cu.ft.	4A:80B:C	Surface	

Note: NFPA regulations also require extinguishers to be inspected when initially placed in service and all local fire code and tagging requirements must be adhered to. All fire extinguisher sizes are nominal. Contact Customer Service for more information about ordering tagged extinguishers in your area.

	<b>&amp;</b> 800-554-6077	Distributor:		Project:			
	🔀 sales@activarcpg.com	Contractor:		Approved By:			
	www.activarcpg.com	Date:		Architect:			
9702 Newton Ave S. Bloomington, MN 55431   Many Locations Across North America		Scale: N/A	Page 1 of 1	Item #:			
© 2022 Activar Construction Products Group, Inc. The information contained in this drawing is the sole property of activar construction products group, inc.							

ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ACTIVAR CONSTRUCTION PRODUCTS GROUP, INC. IS PROHIBITED.