

ASTM			Product	Use				Reinforcement			Application		Roll Coverage	Roll Weight
				Base	Ply	Cap	Flashing	Fiber Glass	Polyester	Composite				
D 6222	Type I	Grade S	APPEX® 4S		X	X	X		X			X	95.8 ft² (8.9 m²)	100 lb (45.4 kg)
			APPeX® 4S Embossed		X	X	X		X			X		89 lb (39.9 kg)
		Grade G	APPEX® 4.5M			X	X		X			X		112 lb (50.8 kg)
			APPeX® 4.5M CR G			X	X		X			X		108 lb (49 kg)
			APPEX® 4.5M FR			X	X		X			X		112 lb (50.8 kg)
			APPeX® 4.5M FR CR G			X	X		X			X		108 lb (49 kg)
			DIBITEN			X	X		X			X		89 lb (39.9 kg)
			DIBITEN Poly/4.5 CR G			X	X		X			X		108 lb (49 kg)
D 6223	Type I	Grade S	BICOR S	X	X					X	X	X	95.8 ft² (8.9 m²)	98 lb (44.5 kg)
		Grade G	BICOR M FR			X	X			X	X	X		111 lb (50.3 kg)
	Type II	Grade S	TRICOR™ S	X	X					X	X	X		94 lb (42.6 kg)
		Grade G	TRICOR™ M FR			X	X			X	X	X	99.5 ft² (9.2 m²)	117 lb (53 kg)
			TRICOR™ M FR CR G			X	X			X	X	X		117 lb (53 kg)
		D 6509			JM APP™ Base Sheet	X	X			X			X	X
JM APP™ Base 2.0 SQ	X				X			X				X	198.91 ft² (18.6 m²)	101 lb (45.8 kg)
JM APP™ Base Plus	X				X			X			X	X	145.08 ft² (13.5 m²)	123 lb (55.8 kg)
			ValuWeld® G Cold			X	X		X		X		95.8 ft² (8.9 m²)	114 lb (51.71 kg)
			ValuWeld® S Cold		X	X	X		X		X			98 lb (44.45 kg)