

Product	Description	Systems		Deck	Color	Size	Packaging
		Single Ply	Bituminous				
Insulation							
Fasteners							
UltraFast® Fastener	#12 case-hardened steel, polymer-coated fastener.	X	X	Metal (18-24 ga.) Wood	Blue	1 ⁵ / ₈ " to 8" (4.13 cm to 20.32 cm) (1) #3 Phillips bit in each pail (1) ¼" (6.35 mm) hex head bit per 3 pails	1,000/pail
Plates							
UltraFast® Plate (Metal)	Recessed round or square flat-bottomed plate. Compatible with UltraFast® and All Purpose Fasteners.	X	X	Metal (18-22 ga.) Wood	Grey	3" (76 mm) round or square	1,000/pail
UltraFast® Plate (Locking Plastic)	High strength polypropylene plates with a special locking feature. Compatible with UltraFast® and All Purpose Fasteners.	X	X	Metal (18-22 ga.) Wood	Blue	3" (76 mm) round	1,000/pail
Fastener and Plate Systems							
Lite-Deck Fasteners and Plates	Insulation Fasteners and plates.	X	X	Cementitious Wood Fiber Gypsum	Black (fasteners) Grey (plates)	Fastener lengths: 2.6" to 12" (6.7 cm to 30.5 cm) Plates: 3" (7.6 cm) round	Quantities vary by fastener length. Plates 500/box
UltraFast® AccuTrac™ Fastener and Plate System	Insulation fastening system.	X	X	Metal (18-24 ga.) Wood	Blue (fasteners) Grey (plates)	Fastener lengths: 1 ⁵ / ₈ " to 6" (4.13 cm to 15.24 cm) Plate: 3" (76 mm) square	Fasteners: 1,000/pail Plates: 1,000/pail
UltraFast® Pre-Assembled Fasteners and Plates	Polymer-coated fastener with Galvalume®-Metal or Locking Plastic Plates.	X	X	Metal (18-24 ga.) Wood	Blue (fasteners) Grey (metal plates) Blue (plastic plates)	Fasteners length: 1.6" to 8" (4.13 cm to 20.32 cm) (A bit is provided in each box) Plates: 3" (7.6 cm) Round Metal or Plastic	1,000/box

Product	Description	Systems		Deck	Color	Size	Packaging
		Single Ply	Bituminous				
Membrane							
Fasteners							
Extra High Load Fasteners	#21 fasteners with a corrosion-resistant coating.	X		Metal (18-24 ga.) Wood	Black	2" to 3" (5.1 cm to 7.6 cm) 4" to 6" (10.2 cm to 15.2 cm) 7" to 8" (17.8 cm to 20.32 cm)	2" to 3" - 1,000/pail 4" to 6" - 500/pail 7" to 8" - 250/pail
High Load Fasteners	#15 case-hardened steel roof membrane fastener and Galvalume®-coated steel seam plates.	X	X	Metal (18-24 ga.) Wood	Blue	1¼" to 24" (3.2 cm to 61 cm)	Quantities vary by fastener length.
High Load LH Fastener	#15 case-hardened steel roof membrane fastener with Galvalume®-coated steel seam plates.	X	X	Metal (18-24 ga.) Wood	Grey	1¼"-12" (3.2cm to 30.5cm)	Quantities vary by fastener length.
JM Purlin Fastener	Steel-coated roof membrane fastener with a 1/4" hex head and 3/4" drill point.	X		Metal Purlins (12-18 ga.)	Grey	3¾" (9.53 cm) 4¾" (12.07 cm) 5¾" (14.61 cm) 7" (17.78 cm) 8" (20.32 cm)	500/pail
Plates							
APB Plates	Galvalume®-coated steel round plate with barbs.	X		Metal (18-24 ga.) Wood Structural Concrete	Grey	2" (5.1 cm) round	1,000/pail
Anchor Disc	Anchor Discs are 2" (5.1 cm) diameter, round, Galvalume®-coated steel discs. Please contact your JM sales representative for information regarding this product.		X			2" (51 mm) round	1,000/box
Extra High Load Plates	#3 Phillips head and a drill point.	X			Grey	3" (7.6 cm) round	500/pail
ENRGY® Anchor	Photovoltaic solution replacing ballast in traditional rail-mounted systems.	X	X	Dependent on system	Grey	Membrane Dimensions: 11.75" x 11.75" (30 cm x 30cm) Plate Dimensions: 5.5" (14 cm) round	25/box
High Load Plates	#15 case-hardened steel roof membrane fastener and Galvalume®-coated steel seam plates.	X	X		Grey	2 ¾" (60 mm) round	1,000/pail
High Load Plus Plates	High Load Plus Plates are heavy duty Galvalume®-coated steel seam plates with barbs.	X	X		Grey	2¾" (7 cm) round	500/pail

Product	Description	Systems		Deck	Color	Size	Packaging
		Single Ply	Bituminous				
JM 90 Seam Plate	JM 90 Seam Plate are heavy duty Galvalume®-coated steel seam plates with eye hooks.	X	X		Grey	3" (7.62 cm)	2½"-8" - 500/pail 9"-10" - 250/pail
UltraFast® Plus Plate	Galvalume®-coated steel 3" nominal square plate used with UltraFast #12 or #14 fasteners.	X		Metal (18-22 ga.) Wood	Grey	3" (7.62 cm) nominal Square	1,000/pail
Fastener and Plate Systems							
High Load AccuSeam™ System	Premier one-step, automated, single-ply membrane seam-fastening system.	X		Metal (18-24 ga.) Wood	Black (fasteners) Grey (plates)	Fastener Sizes: 1¼" to 24" (3.2 cm to 61 cm) 2 ⅜" Plates	Quantities vary by fastener length.
Lightweight Concrete Base Sheet Pre-Assembled Fastener and Plate	Twin-legged, expanding fastener with Galvalume®-coated steel plate.		X	Lightweight Insulated Concrete Gypsum	Black	Fastener lengths: 1.2" (31 mm) and 1.7" (43 mm) Plate: 2.7" (69 mm) round	1.2" - 1,000/box 1.7" - 500/box
JM Termination Systems	Single ply membrane fastening systems include termination bars, anchor discs and masonry nail-in anchors.	X	X	Metal (18-24 ga.) Wood	Various	Termination Bar: 1.35' x 10' (34 mm x 3.05 m) strips Anchor Disc: 2" (51 mm) diameter Fastener: 1¼" (32 mm) Nail-In Anchor: 1¼" (32 mm) diameter	Termination Bar: 500/tube Anchor Disc: 1,000/box Fastener: 1,000/pail Nail-In Anchor: 1,000/box
Membrane Battens	1" wide, prepunched, polymer batten strips with prepunched, counter-sunk, Galvalume®-coated steel anchor bars.	X		Metal (18-24 ga.) Wood Structural Concrete	White (Battens) Grey (Anchor Bars)	Polymer Batten Strip: 1" (2.54 cm) wide .05" (1.27 mm) thick Anchor Bars: 1" (2.54 cm) wide 10' (3.05 m) length	Polymer Batten Strip: 250' (76.2 m)/carton Anchor Bars: 500'/carton
Zinc Nail-In Anchor	Zinc-plated steel pin attaches termination bar to concrete or masonry walls.	X		Structural Concrete Masonry Wall	Grey	¼" (6 mm) dia., 1¼" (32 mm) length	1,000/box
Multi-Purpose							
Fasteners							
All-Purpose Fasteners	#14 case-hardened steel insulation and membrane fastener with a #3 Phillips head.	X	X	Metal (18-24 ga.) Wood Structural Concrete	Grey	1¼" to 4" (3.2 cm to 10.2 cm) 5" to 11" (12.7 cm to 27.9 cm) 12" to 24" (30.5 cm to 61.0 cm)	1¼" to 4" - 1,000/pail 5" to 11" - 500/pail 12" to 24" - 250/box
JM Retrodriller Fastener	Roof Membrane and Insulation Fastener.	X		Metal Purlins (18-24 ga.)	Grey	4" to 10" (10.2 cm to 25.4 cm)	500/pail

Product	Description	Systems		Deck	Color	Size	Packaging
		Single Ply	Bituminous				
Structural Concrete Deck Fasteners	Diamond point, nonthreaded carbon steel insulation and membrane fastener.	X	X	Structural Concrete	Black	2½" to 10" (6.4 mm to 25.4 mm) lengths	2½"-8" - 500/pail 9"-10" - 250/pail
Plates							
JM isoweld®	Insulation and Membrane Fastening Plate.	X		Metal (18-24 ga.) Metal Purlins (18-24 ga.) Wood Structural Concrete	TPO: Yellow PVC: Purple	3" (7.6 cm) round	500/pail
JM PVC Rhinoplate®	Coated Galvalume® insulation and PVC membrane fastening plate with recessed center and raised flat-bonding surface.	X		Metal (18-24 ga.) Wood Structural Concrete	Black	3" (7.6 cm) round	500/pail
JM TPO Rhinoplate®	Coated Galvalume®, TPO fastening plate with a recessed center and raised flat-bonding surface.	X		Metal (18-24 ga.) Metal Purlins (18-24 ga.) Wood Structural Concrete	Amber	3" (7.6 cm) round	500/pail
Fastener and Plate Systems							
Polymer Auger Fastener with Plates	Solid glass-reinforced nylon membrane and insulation fasteners.	X	X	Cementitious Wood Fiber Gypsum	Black (fasteners) Grey (plates)	Fastener lengths: 2½" (6.4 cm) to 7½" (19.1 cm) Plate: 2" (51 mm) round and 3" (76 mm) square	Fastener: 500/pail Plate: 1,000/pail
UltraLok™ Locking Impact Fastener and Plate	Galvanized-steel tube and Galvalume®-coated steel disc clamped to a wire-locking staple.	X	X	Cementitious Wood Fiber Lightweight Insulated Concrete Gypsum	Black (fasteners) Grey (plates)	Fastener lengths: 1.4" to 1.7" (3.6 cm to 4.32 cm) Plate: 2.7" (6.9 cm)	500/carton