

Thermal Resistance To obtain insulation resistance of:	Minimum Thickness (inches) Installed insulation shall not be less than:	Density of Insulation (lb/cu³) Installed insulation shall not be less than:	Maximum Coverage (ft²/bag) Contents of the bag shall not cover more than:	Minimum Weight (lb/ft²) Weight should not be less than:
14	3.5	1.2	85.7	0.350
15	3.5	1.4	73.5	0.408
16	3.5	2.0	51.0	0.583
22	5.5	1.1	59.5	0.504
23	5.5	1.2	54.5	0.550
24	5.5	1.5	44.0	0.690
25	5.5	2.0	33.0	0.920
29	7.25	1.1	45.1	0.665
30	7.25	1.3	38.2	0.785
31	7.25	1.5	33.0	0.910
32	7.25	2.0	25.0	1.210
38	9.25	1.3	29.9	1.002
39	9.25	1.4	27.8	1.079
40	9.25	1.5	26.0	1.160
41	9.25	2.0	19.0	1.540
47	11.25	1.3	25.6	1.172
48	11.25	1.5	21.3	1.406
49	11.25	1.7	18.8	1.594
55	13.25	1.3	20.9	1.435
57	13.25	1.5	18.1	1.656
58	13.25	1.7	16.0	1.877