

Thermal Resistance To obtain insulation resistance of:	Minimum Thickness (inches) Installed insulation shall not be less than:	Density of Insulation (lb/cu³) Installed insulation shall not be less than:	Maximum Coverage (ft²/bag) Contents of the bag shall not cover more than:	Minimum Weight (lb/ft²) Weight should not be less than:
33	9.25	0.8	49	0.617
35	9.25	0.9	43	0.694
36	9.25	1.0	39	0.771
34	9.5	0.8	47	0.633
36	9.5	0.9	42	0.713
37	9.5	1.0	38	0.792
40	11.25	0.8	40	0.750
42	11.25	0.9	36	0.844
44	11.25	1.0	32	0.938
43	11.875	0.8	38	0.792
44	11.875	0.9	34	0.891
46	11.875	1.0	30	0.990
43	12	0.8	37.5	0.800
45	12	0.9	33.3	0.900
47	12	1.0	30.0	1.000
50	14	0.8	32.1	0.933
52	14	0.9	28.6	1.050
54	14	1.0	25.7	1.167
57	16	0.8	28.1	1.067
60	16	0.9	25.0	1.200
62	16	1.0	22.5	1.333
64	18	0.8	25.0	1.200
67	18	0.9	22.2	1.350
70	18	1.0	20.0	1.500
72	20	0.8	22.5	1.333
75	20	0.9	20.0	1.500
78	20	1.0	18.0	1.667
79	22	0.8	20.5	1.467
82	22	0.9	18.2	1.650
85	22	1.0	16.4	1.833
86	24	0.8	18.8	1.600
90	24	0.9	16.7	1.800
93	24	1.0	15.0	2.000
101	26	1.0	13.8	2.167
107	26	1.2	11.5	2.600
112	26	1.5	9.2	3.250
109	28	1.0	12.9	2.333
115	28	1.2	10.7	2.800
120	28	1.5	8.6	3.500
117	30	1.0	12.0	2.500
123	30	1.2	10.0	3.000
129	30	1.5	8.0	3.750
124	32	1.0	11.3	2.667
131	32	1.2	9.4	3.200
138	32	1.5	7.5	4.000
132	34	1.0	10.6	2.833
139	34	1.2	8.8	3.400
146	34	1.5	7.1	4.250
140	36	1.0	10.0	3.000
148	36	1.2	8.3	3.600
155	36	1.5	6.7	4.500