

APP and Self-Adhered Modified Bitumen Selector Guide

Product	Description	Use	Approx. Thickness	Roll Size	Coverage
BICOR M FR	Fiber glass/polyester composite. Granule surfaced, APP.	Excellent weatherability, high tensile and puncture resistance. FR additives for UL Class A.	0.178 mils (4.5 mm)	39 ³ / ₈ " x 34'5" (1 m x 10.5 m)	1 sq. 9.29 m ²
BICOR M	Fiber glass/polyester composite. Granule surfaced, APP.	Excellent weatherability, high tensile and puncture resistance.	0.178 mils (4.5 mm)	39 ³ / ₈ " x 34'5" (1 m x 10.5 m)	1 sq. 9.29 m ²
APPeX 4S	Polyester reinforced, 180 gm/m ² Smooth surfaced, APP.	Very good weatherability, high tensile and puncture resistance.	0.158 mils (4.0 mm)	39 ³ / ₈ " x 32'10" (1 m x 10 m)	1 sq. 9.29 m ²
APPeX 4.5M FR	Polyester reinforced, 180 gm/m ² Granule surfaced, APP.	Excellent weatherability, high tensile and puncture resistance. FR additives for UL Class A.	0.178 mils (4.5 mm)	39 ³ / ₈ " x 32'10" (1 m x 10 m)	1 sq. 9.29 m ²
APPeX 4.5M	Polyester reinforced, 180 gm/m ² Granule surfaced, APP.	Excellent weatherability, high tensile and puncture resistance.	0.178 mils (4.5 mm)	39 ³ / ₈ " x 32'10" (1 m x 10 m)	1 sq. 9.29 m ²
JM APP Base	Glass mat reinforced, Smooth surfaced, APP.	Excellent tensile strength. Base ply in two or more ply. APP modified bitumen roofing system.	0.087 mils (2.2 mm)	39 ³ / ₈ " x 48'10" (1 m x 15 m)	1.5 sq. 13.9 m ²
Sure Grip	Glass mat reinforced. Granule surfaced, self adhered SBS.	Self-sealing, pliable and durable ice and water guard membrane.	70 mils (1.8 mm)	3' x 67' (0.92 m x 20.4 m)	2 sq. 18.58 m ²

**For Additional Technical or
Guarantee Information:**

Guarantee Services Unit
P.O. Box 625001
Littleton, CO 80162-5001
800-922-5922
FAX 303.978.2808