


NOTES:

1. DETAILS TO BE USED IN CONJUNCTION WITH GUIDE SPECIFICATIONS CONTAINING REQUIREMENTS FOR NAILERS, INSULATION, ETC.
2. PENETRATION MUST NOT EXCEED 150°F (66°C) IN TEMPERATURE. NO FLEXIBLE TUBES, LIGHTNING ROD CABLES, ETC.
3. ROOF PENETRATION MUST BE CLEANED OF ALL CONTAMINANTS (I.E., ASPHALT) IN AREA WHERE JM POLYURETHANE POURABLE SEALANT IS INSTALLED.
4. MAXIMUM PENETRATION POCKET SIZE - 18" x 18" (450 mm x 450 mm), OTHERWISE BASE MUST BE FASTENED TO NAILER, ANCHORED TO DECK.
5. BRACING STRIP MUST BE INSTALLED AT PENETRATION POCKET CORNERS.
6. FOR MULTIPLE PIPES, ETC. 1" (25 mm) MINIMUM BETWEEN ALL PIPES, ETC., AS WELL AS THE WALLS OF THE PENETRATION POCKET.

DRAWING NO. PF-54	PVC-COATED METAL PENETRATION POCKET			 Johns Manville
	SCALE N.T.S.	ISSUE DATE 3-06	CAD PV54MEF	