

**JM Spray Polyurethane Foam (SPF) – Component A (USA and Canada)**

Version 2.4

Revision Date 07/30/2019

Print Date 07/30/2019

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Trade name : JM CORBOND® (A) ISO

## Manufacturer or supplier's details

Company : Johns Manville  
Address : P.O. Box 5108  
Denver, CO USA 80127  
Telephone : +1-303-978-2000  
Emergency telephone : +1-800-424-9300 (CHEMTREC)  
numberCompany : Johns Manville Canada Inc.  
Address : 5301 42 Avenue  
Innisfail, AB Canada T4G 1A2  
Telephone : +1-303-978-2000  
Emergency telephone : +1-800-424-9300 (CHEMTREC)  
number

## Recommended use of the chemical and restrictions on use

Restrictions on use : For professional users only.

Prepared by : productsafety@jm.com

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with 29 CFR 1910.1200 (OSHA HCS 2012) and the Hazardous Products Regulations (WHMIS 2015)**Acute toxicity (Inhalation) : Category 4  
Skin irritation : Category 2  
Eye irritation : Category 2A  
Respiratory sensitisation : Category 1  
Skin sensitisation : Category 1  
Specific target organ toxicity : Category 3 (Respiratory system)  
- single exposure  
Specific target organ toxicity : Category 1 (Respiratory system)  
- repeated exposure  
(Inhalation)**GHS label elements**

**JM Spray Polyurethane Foam (SPF) – Component A (USA and Canada)**

Version 2.4

Revision Date 07/30/2019

Print Date 07/30/2019

Hazard pictograms :



Signal word : Danger

Hazard statements : H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335 May cause respiratory irritation.  
H372 Causes damage to organs (Respiratory system) through prolonged or repeated exposure if inhaled.

Precautionary statements :

**Prevention:**

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/ eye protection/ face protection.  
P285 In case of inadequate ventilation wear respiratory protection.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.  
P337 + P313 If eye irritation persists: Get medical advice/attention.  
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.  
P362 Take off contaminated clothing and wash before reuse.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.

**Disposal:**

P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

## JM Spray Polyurethane Foam (SPF) – Component A (USA and Canada)

Version 2.4

Revision Date 07/30/2019

Print Date 07/30/2019

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**
**Hazardous components**

Chemical name	CAS-No.	Concentration (%)
polymethylenepolyphenylene isocyanate	9016-87-9	>= 50 - <= 70
4,4'-methylenediphenyl diisocyanate	101-68-8	>= 30 - <= 50

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Remove to fresh air immediately. Get medical attention immediately.  
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Get medical attention if irritation develops and persists.
- In case of eye contact : In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Keep eye wide open while rinsing.  
Protect unharmed eye.  
Seek medical advice.
- If swallowed : Do NOT induce vomiting.  
Gently wipe or rinse the inside of the mouth with water.  
Never give anything by mouth to an unconscious person.  
If swallowed, call a poison control centre or doctor immediately.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Harmful if inhaled.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause respiratory irritation.  
Causes damage to organs through prolonged or repeated exposure if inhaled.

**JM Spray Polyurethane Foam (SPF) – Component A (USA and Canada)**

Version 2.4

Revision Date 07/30/2019

Print Date 07/30/2019

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Water mist  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical  
Foam
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : The product reacts with water and generates heat.
- Hazardous combustion products : carbon oxides  
nitrogen oxides  
isocyanates  
hydrogen cyanide
- Specific extinguishing methods : Use a water spray to cool fully closed containers.
- Further information : Standard procedure for chemical fires.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Immediately evacuate personnel to safe areas.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Recovered material should be stored in a vented container.  
The vent must prevent the ingress of water as further reaction with spilled materials can take place which could lead to overpressurization of the container.  
Large spills should be collected mechanically (remove by pumping) for disposal.

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Provide sufficient air exchange and/or exhaust in work rooms.

## JM Spray Polyurethane Foam (SPF) – Component A (USA and Canada)

Version 2.4

Revision Date 07/30/2019

Print Date 07/30/2019

Do not breathe vapours/dust.  
 Avoid formation of aerosol.  
 Avoid exposure - obtain special instructions before use.  
 Avoid contact with skin and eyes.  
 Smoking, eating and drinking should be prohibited in the application area.  
 Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
 For personal protection see section 8.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
 Observe label precautions.  
 Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : Stable at normal ambient temperature and pressure.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
4,4'-methylenediphenyl diisocyanate	101-68-8	TWA	0.005 ppm	ACGIH
		TWA	0.005 ppm 0.05 mg/m <sup>3</sup>	NIOSH REL
		C	0.02 ppm 0.2 mg/m <sup>3</sup>	NIOSH REL
		C	0.02 ppm 0.2 mg/m <sup>3</sup>	OSHA

Johns Manville is a member of the Center for the Polyurethanes Industry (CPI) of the American Chemistry Council. For more information about safe work practices, see CPI's *Health and Safety Product Stewardship Workbook for High-Pressure Application of Spray Polyurethane Foam (SPF)* and other resources (some available in Spanish and French) at the following website hyperlinks: <https://www.spraypolyurethane.org/resources/> and <https://www.spraypolyurethane.org/additional-resources/>.

#### Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled

## JM Spray Polyurethane Foam (SPF) – Component A (USA and Canada)

Version 2.4

Revision Date 07/30/2019

Print Date 07/30/2019

release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection		
Material	:	Nitrile rubber
Material	:	butyl-rubber
Material	:	Neoprene
Material	:	PVC
Remarks	:	Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
Eye protection	:	Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place. Remove and wash contaminated clothing before re-use.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday. Written instructions for handling must be available at the work place.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	viscous liquid
Color	:	dark brown
Odor	:	musty
Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	> 204 °C Decomposition
Flash point	:	> 230 °C

## JM Spray Polyurethane Foam (SPF) – Component A (USA and Canada)

Version 2.4

Revision Date 07/30/2019

Print Date 07/30/2019

Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: 13.9 hPa (40 °C)
Relative vapour density	: No data available
Relative density	: ca. 1.235 (25 °C) (Water = 1.0)
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: > 300 °C
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Mixture reacts slowly with water resulting in evolution of carbon dioxide. Polymerisation is a highly exothermic reaction and may generate sufficient heat to cause thermal decomposition and/or rupture containers.
Conditions to avoid	: Do not expose to temperatures above: 177 °C Exposure to moisture If contained in exposed to high heat (> 350 °F), it can be pressurized and possibly rupture. Methylene diisocyanate reacts slowly with water to form carbon dioxide gas. This gas can cause sealed container to expand and possibly rupture.

**JM Spray Polyurethane Foam (SPF) – Component A (USA and Canada)**

Version 2.4

Revision Date 07/30/2019

Print Date 07/30/2019

Incompatible materials	:	Water Strong bases Acids Alcohols Metals
Hazardous decomposition products	:	carbon oxides nitrogen oxides Isocyanates Hydrogen cyanide (hydrocyanic acid)

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity****Components:****polymethylenepolyphenylene isocyanate:**

Acute oral toxicity : LD50 (Rat): &gt; 2,000 mg/kg

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 (Rabbit, male and female): > 9,400 mg/kg  
Method: OECD Test Guideline 402**Acute toxicity****4,4'-methylenediphenyl diisocyanate:**

Acute oral toxicity : LD50 (Rat, male and female): &gt; 2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 2.24 mg/l  
Exposure time: 1 h  
Test atmosphere: dust/mist  
Assessment: The component/mixture is moderately toxic after short term inhalation.Acute dermal toxicity : LD50 (Rabbit, male and female): > 9,400 mg/kg  
Method: OECD Test Guideline 402**Skin corrosion/irritation****Components:****polymethylenepolyphenylene isocyanate:**

Species: Rabbit

Result: Skin irritation

**Skin corrosion/irritation****4,4'-methylenediphenyl diisocyanate:**

Species: Rabbit

Method: Draize Test

Result: Mild skin irritant

Species: Human



**JM Spray Polyurethane Foam (SPF) – Component A (USA and Canada)**

Version 2.4

Revision Date 07/30/2019

Print Date 07/30/2019

Result: irritating

**Serious eye damage/eye irritation****Components:****polymethylenepolyphenylene isocyanate:**

Species: Rabbit

Result: Eye irritation

**Serious eye damage/eye irritation****4,4'-methylenediphenyl diisocyanate:**

Species: Rabbit

Result: Moderate eye irritation

Method: Draize Test

Species: Human

Result: irritating

Respiratory sensitisation: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Respiratory or skin sensitisation****Components:****polymethylenepolyphenylene isocyanate:**

Exposure routes: Dermal

Species: Mouse

Assessment: May cause sensitisation by skin contact.

Method: OECD Test Guideline 429

Result: positive

Exposure routes: Inhalation

Species: Guinea pig

Assessment: May cause sensitisation by inhalation.

Result: positive

**Respiratory or skin sensitisation****4,4'-methylenediphenyl diisocyanate:**

Exposure routes: Dermal

Species: Mouse

Assessment: May cause sensitisation by skin contact.

Method: OECD Test Guideline 429

Result: positive

Exposure routes: Inhalation

Species: Guinea pig

Assessment: May cause sensitisation by inhalation.

Result: positive

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**ACGIH**

No component of this product present at levels greater than or

**JM Spray Polyurethane Foam (SPF) – Component A (USA and Canada)**

Version 2.4

Revision Date 07/30/2019

Print Date 07/30/2019

equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**STOT - single exposure****Components:****polymethylenepolyphenylene isocyanate:**

Exposure routes: Inhalation

Target Organs: Respiratory Tract

Assessment: May cause respiratory irritation.

**STOT - single exposure****4,4'-methylenediphenyl diisocyanate:**

Exposure routes: Inhalation

Target Organs: Respiratory Tract

Assessment: May cause respiratory irritation.

**STOT - repeated exposure****Components:****polymethylenepolyphenylene isocyanate:**

Exposure routes: Inhalation

Target Organs: Respiratory system

Assessment: Causes damage to organs through prolonged or repeated exposure.

**STOT - repeated exposure****4,4'-methylenediphenyl diisocyanate:**

Exposure routes: Inhalation

Target Organs: Respiratory system

Assessment: May cause damage to organs through prolonged or repeated exposure.

**Aspiration toxicity**

Not classified based on available information.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**JM Spray Polyurethane Foam (SPF) – Component A (USA and Canada)**

Version 2.4

Revision Date 07/30/2019

Print Date 07/30/2019

**Bioaccumulative potential****Components:****4,4'-methylenediphenyl diisocyanate:**Partition coefficient: n- : log Pow: 4.51 (20 °C)  
octanol/water pH: 7**Mobility in soil**

No data available

**Other adverse effects****Product:**Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82  
Protection of Stratospheric Ozone - CAA Section 602 Class I  
Substances  
Remarks: This product neither contains, nor was  
manufactured with a Class I or Class II ODS as defined by the  
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +  
B).

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**Disposal of residual product : Dispose of contents/container to an approved facility in  
accordance with local, regional, national and international  
regulations.  
Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with  
chemical or used container.  
Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

---

**SECTION 14. TRANSPORT INFORMATION****International transport regulations**

## Land transport

USDOT: Not classified as a dangerous good under transport regulations

TDG: Not classified as a dangerous good under transport regulations

## Sea transport

IMDG: Not classified as a dangerous good under transport regulations

## Air transport

IATA/ICAO: Not classified as a dangerous good under transport regulations

## JM Spray Polyurethane Foam (SPF) – Component A (USA and Canada)

Version 2.4

Revision Date 07/30/2019

Print Date 07/30/2019

### SECTION 15. REGULATORY INFORMATION

#### TSCA list

TSCA - 5(a) Significant New Use Rule List of Chemicals : No substances are subject to a Significant New Use Rule.

U.S. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpart D) : No substances are subject to TSCA 12(b) export notification requirements.

#### EPCRA - Emergency Planning and Community Right-to-Know Act

##### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
4,4'-methylenediphenyl diisocyanate	101-68-8	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

##### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Acute toxicity (any route of exposure)  
 Skin corrosion or irritation  
 Serious eye damage or eye irritation  
 Respiratory or skin sensitisation  
 Specific target organ toxicity (single or repeated exposure)

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

polymethylenepolyphenylene isocyanate	9016-87-9	50 - 70 %
4,4'-methylenediphenyl diisocyanate	101-68-8	30 - 50 %

##### Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

4,4'-methylenediphenyl diisocyanate	101-68-8	50 - 70 %
-------------------------------------	----------	-----------

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

4,4'-methylenediphenyl diisocyanate	101-68-8	50 - 70 %
-------------------------------------	----------	-----------

**JM Spray Polyurethane Foam (SPF) – Component A (USA and Canada)**

Version 2.4

Revision Date 07/30/2019

Print Date 07/30/2019

**California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)**

This product does not require a warning under the California Safe Drinking Water and Toxic Enforcement Act (Proposition 65).

**The components of this product are reported in the following inventories:**

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

---

**SECTION 16. OTHER INFORMATION****Further information**

Revision Date : 07/30/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.