

Features and Components

Use: Designed for use as a protective layer between pavers or ballast and EPDM membrane, as well as a separating sheet in some recover systems.

Material: Nominal 7.0 oz/yd² (237.34 g/m²) needle-punched UV-resistant polypropylene fabric.

Color: Black



Component

A
Accessory

Single Ply

Type

PT
Protection

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS				
	HA	CA	CA	HW	HA	CA	HW	SA	MF
<i>Do not use in Multi-Ply systems</i>									

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
<i>Compatible with the selected Single Ply systems above</i>							

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened FA = Fully Adhered BA = Ballasted

Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Installation/Application



Ballasted

- The JM EPDM Protective Stone Mat is typically installed between the overlying ballast or pavers and the JM EPDM roofing membrane.
- Refer to JM EPDM applicator guides or detail drawings for instructions.

Packaging and Dimensions

Roll Size	15' wide x 300' long (4.57 m x 91.44 m)
Material Weight	7.0 oz/yd ² (237.34 g/m ²) (nom)
Coverage per Roll	4,500 ft ² (418.06 m ²) (gross)
Weight per Roll	180 lb (81.65 kg)

Storage

Storage Conditions	Store indoors, out of direct sunlight, and keep clean and dry prior to application.
--------------------	---