

JM TPO Membrane Selector Guide

Description	Product	ASTM	Thickness	Color			Sizes	Area per Roll	Weight	Specifications		Guarantees
				White	Grey	Tan				Mechanically Fastened	Fully Adhered	
Thermoplastic, polyester reinforced membrane manufactured using an ultraviolet-resistant TPO (thermoplastic polyolefin) formulation.	JM TPO	D 6878	45 mil	X	*	*	5' x 100' (1.52 m x 30.48 m)	500 ft ² (46.45 m ²)	130 lb (58.97 kg)	ST4RM-S ST4RM-S/I ST4RM-W	ST4RA-S ST4RA-S/I ST4RA-C ST4RA-C/I	5 or 10 yr NDL
				X	*	*	8' x 100' (2.44 m x 30.48 m)	800 ft ² (74.32 m ²)	208 lb (94.35 kg)			
				X	*	*	10' x 100' (3.04 m x 30.48 m)	1,000 ft ² (92.90 m ²)	258 lb (117.03 kg)			
			60 mil	X	X	X	5' x 100' (1.52 m x 30.48 m)	500 ft ² (46.45 m ²)	162 lb (73.48 kg)	ST6RM-S ST6RM-S/I ST6RM-W	ST6RA-S ST6RA-S/I ST6RA-C ST6RA-C/I	5, 10, 15, or 20 yr NDL
				X	*	*	8' x 100' (2.44 m x 30.48 m)	800 ft ² (74.32 m ²)	256 lb (116.19 kg)			
				X	X	X	10' x 100' (3.04 m x 30.48 m)	1,000 ft ² (92.90 m ²)	322 lb (146.06 kg)			
			80 mil	X	*	*	5' x 75' (1.52 m x 22.86 m)	375 ft ² (34.84 m ²)	216 lb (97.98 kg)			5, 10, 15, or 20 yr NDL
				X	*	*	8' x 75' (2.44 m x 22.86 m)	600 ft ² (55.74 m ²)	347 lb (157.40 kg)			
				X	*	*	10' x 75' (3.04 m x 22.86 m)	750 ft ² (69.68 m ²)	434 lb (196.86 kg)			
Thermoplastic polyolefin (TPO) membrane with a reinforced polyester fabric and integral polyester fleece backing.	JM TPO FB 100™	D 6878	45 mil	X	*	*	10' x 100' (3.04 m x 30.48 m)	1,000 ft ² (92.90 m ²)	270 lb (122.47 kg)			5 or 10 yr NDL
	JM TPO FB 115™		60 mil	X	*	*	10' x 100' (3.04 m x 30.48 m)	1,000 ft ² (92.90 m ²)	325 lb (147.42 kg)			5, 10, 15, or 20 yr NDL

*Grey and tan are special order.