


- NOTES:
1. DETAILS TO BE USED IN CONJUNCTION WITH GUIDE SPECIFICATIONS CONTAINING REQUIREMENTS FOR NAILERS, INSULATION, ETC.
 2. JM TPO EDGE SEALANT IS REQUIRED ON ALL CUT OR NON-ENCAPSULATED EDGES OF REINFORCED MEMBRANE. THIS INCLUDES FACTORY CUT MEMBRANE.
 3. PENETRATION MUST NOT EXCEED 150°F IN TEMPERATURE. NO FLEXIBLE TUBES, LIGHTNING ROD CABLES, ETC.
 4. ROOF PENETRATION MUST BE CLEANED OF ALL CONTAMINANTS (I.E., ASPHALT) IN AREA WHERE JM TPO POLYURETHANE POURABLE SEALANT IS INSTALLED.
 5. FOR MULTIPLE PIPES, ETC. 1" (25 mm) MINIMUM BETWEEN ALL PIPES, ETC. AS WELL AS THE WALLS OF THE PENETRATION POCKET.

DRAWING NO. TF-54	TPO-COATED METAL PENETRATION POCKET			 Johns Manville
	SCALE N.T.S.	ISSUE DATE 3-06	CAD TPO-6.04	