



NOTES:

1. DETAILS TO BE USED IN CONJUNCTION WITH GUIDE SPECIFICATIONS CONTAINING REQUIREMENTS FOR NAILERS, INSULATION, ETC.
2. IN NEW CONSTRUCTION ACCEPTABLE SUBSTRATES INCLUDE EXTERIOR GRADE PLYWOOD, POURED OR PRECAST CONCRETE, CEMENT BLOCK OR MASONRY WALLS. CONTACT JM TECHNICAL SERVICES FOR OTHER SUBSTRATES.
3. ON REROOFING PROJECTS AN APPROVED ASPHALT BARRIER MUST BE INSTALLED OVER THE EXISTING FLASHINGS TO FULLY DIVORCE THE JM TPO FLASHING MEMBRANE FROM ANY INCOMPATIBLE MATERIALS.
4. DO NOT APPLY JM TPO POLYURETHANE CAULK OVER ASPHALT OR OTHER MATERIALS THAT WILL PREVENT PROPER ADHESION.
5. WHEN REROOFING, COUNTER FLASHING CAN BE REBENT AND FASTENED THROUGH FACE WITH ACCEPTABLE FASTENER.

DRAWING NO. TC-43	TPO COUNTERFLASHING (MEMBRANE)			
	SCALE N.T.S.	ISSUE DATE 3-06	CAD TPO-5.04	