



NOTES:

1. DETAILS TO BE USED IN CONJUNCTION WITH GUIDE SPECIFICATIONS CONTAINING REQUIREMENTS FOR NAILERS, INSULATION, ETC.
2. JM TPO EDGE SEALANT IS USED TO SEAL THE MEMBRANE EDGES WHERE REINFORCING FABRIC IS CUT AND EXPOSED. EDGE SEALANT IS REQUIRED ON ALL END LAPS, T-JOINTS, AND FIELD-CUT EDGES.
3. ACCORDING TO PROJECT CONDITIONS, THE SPECIFIER AND/OR APPLICATOR MUST DETERMINE THE REQUIRED VERTICAL FLASHING HEIGHT BASED ON REGIONAL CLIMATIC CONDITIONS.
4. JM TPO-COATED METAL FLASHING MUST EXTEND UNDER A MINIMUM OF TWO COURSES OF SHINGLES AND 12" (300 mm) ABOVE MEMBRANE.
5. INSULATION MUST BE COMPATIBLE WITH JM TPO BONDING ADHESIVE.

DRAWING NO. <b>TT-82</b>	<b>TRANSITION TO SHINGLE ROOF</b>			
	SCALE N.T.S.	ISSUE DATE 3-06	CAD TPO-7.04	