









ASTM	Product	Application				Roll Size	Roll Coverage	Colors*						
		Hot Air Weld 	Fully Adhered 	Mechanically Fastened 	Hot Asphalt 			White	Grey	Grey ES	Charcoal	Sandstone	Sandstone ES	
<b>PVC with Dow Elvaloy KEE Polymer</b> JM PVC with the optimal amount of Dow™ Elvaloy® KEE is a heat weldable polyvinyl chloride thermoplastic membrane that provides superior resistance against oil, fuels, and other hard chemicals.														
D 4434, Type III	50 MIL		X	X		3.25' x 100' (1 m x 30.48 m)	325 ft² (30.19 m²)	X						
			X	X		5' x 100' (1.52 m x 30.48 m)	500 ft² (46.45 m²)							
			X	X		6.5' x 100' (1.98 m x 30.48 m)	650 ft² (60.38 m²)							
			X	X		10' x 100' (3.05 m x 30.48 m)	1000 ft² (92.9 m²)							
	60 MIL	X	X	X		3.25' x 100' (1 m x 30.48 m)	325 ft² (30.19 m²)	X	X	X	X	X	X	
		X	X	X		5' x 100' (1.52 m x 30.48 m)	500 ft² (46.45 m²)							
		X	X	X		6.5' x 100' (1.98 m x 30.48 m)	650 ft² (60.38 m²)							
		X	X	X		10' x 100' (3.05 m x 30.48 m)	1000 ft² (92.9 m²)							
		X	X	X		12' x 100' (3.66 m x 30.48 m)	1200 ft² (111.5 m²)							
	80 MIL	X	X	X		3.25' x 75' (1 m x 22.86 m)	243.75 ft² (22.65 m²)	X	X	X	X	X	X	
		X	X	X		5' x 75' (1.52 m x 22.86 m)	375 ft² (34.84 m²)							
		X	X	X		6.5' x 75' (1.98 m x 22.86 m)	487.5 ft² (45.29 m²)							
		X	X	X		10' x 75' (3.05 m x 22.86 m)	750 ft² (69.68 m²)							
		X	X	X		12' x 75' (3.66 m x 22.86 m)	900 ft² (83.61 m²)							
	<b>PVC mil/MIN with Dow Elvaloy KEE Polymer</b> JM PVC with KEE MIN is a heat weldable thermoplastic membrane with a minimum thickness of either 60 or 72 mils.													
D 4434, Type III	60 MIL MIN	X	X	X		3.25' x 100' (1 m x 30.48 m)	325 ft² (30.19 m²)	X	X				X	
		X	X	X		6.5' x 100' (1.98 m x 30.48 m)	650 ft² (60.38 m²)							
		X	X	X		10' x 100' (3.05 m x 30.48 m)	1000 ft² (92.9 m²)							
	72 MIL MIN	X	X	X		6.5' x 75' (1.98 m x 22.86 m)	487.5 ft² (45.29 m²)	X						

\*All colors not available as standard stocked items in all size configurations. Please call for minimums and lead times.

ASTM	Product	Application				Roll Size	Roll Coverage	Colors*					
		Hot Air Weld 	Fully Adhered 	Mechanically Fastened 	Hot Asphalt 			White	Grey	Grey ES	Charcoal	Sandstone	Sandstone ES
<b>PVC FB with Dow Elvaloy KEE Polymer</b> JM PVC with KEE FB is a heat weldable thermoplastic membrane that utilizes a Spunbond 3.8 oz. fleece creating an extremely durable, strong yet light and flexible protection layer.													
D 4434, Type III	60 MIL	X	X	X	X	6.33' x 90' (1.93 m x 27.43 m)	569.7 ft <sup>2</sup> (52.93 m <sup>2</sup> )	X	X	X	X	X	X
		X	X	X	X	12' x 90' (3.66 m x 27.43 m)	1080 ft <sup>2</sup> (100.34 m <sup>2</sup> )						
	80 MIL	X	X	X	X	6.33' x 75' (1.93 m x 22.86 m)	474.75 ft <sup>2</sup> (44.11 m <sup>2</sup> )	X	X	X	X	X	X
		X	X	X	X	12' x 75' (3.66 m x 22.86 m)	900 ft <sup>2</sup> (83.61 m <sup>2</sup> )						
<b>PVC SD Plus</b> JM PVC SD Plus is a heat weldable thermoplastic polyvinyl chloride membrane.													
D 4434, Type III	50 MIL	X	X	X		5' x 100' (1.52 m x 30.48 m)	500 ft <sup>2</sup> (46.33 m <sup>2</sup> )	X					
		X	X	X		10' x 100' (3.05 m x 30.48 m)	1000 ft <sup>2</sup> (92.96 m <sup>2</sup> )						
	60 MIL	X	X	X		5' x 100' (1.52 m x 30.48 m)	500 ft <sup>2</sup> (46.33 m <sup>2</sup> )	X	X				
		X	X	X		10' x 100' (3.05 m x 30.48 m)	1000 ft <sup>2</sup> (92.96 m <sup>2</sup> )						
		X	X	X		12' x 100' (3.66 m x 30.48 m)	1200 ft <sup>2</sup> (111.5 m <sup>2</sup> )						
	60 MIL MIN	X	X	X		10' x 100' (3.05 m x 30.48 m)	1000 ft <sup>2</sup> (92.96 m <sup>2</sup> )	X					
	80 MIL	X	X	X		5' x 75' (1.52 m x 22.9 m)	375 ft <sup>2</sup> (34.84 m <sup>2</sup> )	X	X				
		X	X	X		10' x 75' (3.05 m x 22.9 m)	750 ft <sup>2</sup> (69.67 m <sup>2</sup> )						
		X	X	X		12' x 75' (3.66 m x 22.86 m)	900 ft <sup>2</sup> (83.61 m <sup>2</sup> )						
	<b>PVC SD Plus FB</b> JM PVC SD Plus is a heat weldable thermoplastic membrane that utilizes a Spunbond 3.8 oz. fleece creating an extremely durable, strong yet light and flexible protection layer.												
D 4434, Type III	60 MIL	X	X	X	X	6.33' x 90' (1.93 m x 27.43 m)	569.7 ft <sup>2</sup> (52.93 m <sup>2</sup> )	X	X				
		X	X	X	X	12' x 90' (3.66 m x 27.43 m)	1080 ft <sup>2</sup> (100.34 m <sup>2</sup> )						
	80 MIL	X	X	X	X	6.33' x 75' (1.93 m x 22.86 m)	474.75 ft <sup>2</sup> (44.11 m <sup>2</sup> )	X	X				
		X	X	X	X	12' x 75' (3.66 m x 22.86 m)	900 ft <sup>2</sup> (83.61 m <sup>2</sup> )						

\*All colors not available as standard stocked items in all size configurations. Please call for minimums and lead times.