


**NOTES:**

1. IF VERTICAL LEG OF PENETRATION POCKET IS LESS THAN 3" (80 mm), JM EPDM FLASHING MUST EXTEND UP AND OVER TOP EDGE AND DOWN INSIDE OF POCKET A MINIMUM OF 1" (25 mm).
2. JM EPDM POURABLE SEALER MUST FILL POCKET TO TOP.
3. FLASH CORNERS OF ROOF PENETRATION POCKET PER DETAIL EM-1.
4. THIS DETAIL ALSO SUITABLE FOR MULTIPLE PENETRATIONS THROUGH A SINGLE OPENING, PROVIDED MINIMUM 1" (25 mm) CLEARANCES ARE MAINTAINED.
5. ALL METAL SURFACES MUST BE CLEANED AND PRIMED WITH JM EPDM TAPE PRIMER/WASH. JM EPDM TAPE PRIMER/WASH MUST BE COMPLETELY DRY AND TACK FREE BEFORE APPLYING JM EPDM LAP CEMENT.

DRAWING NO.  <b>EP-5</b>	<b>ROOF PENETRATION POCKET FLASHING WITH NAILER</b>			 <b>Johns Manville</b>
	SCALE  N.T.S.	ISSUE DATE  3-06	CAD  SP05PEN	