

UL External Fire Resistance (UL 790)

Asphalt Adhered SBS Modified Bitumen

**** Check Individual Construction Listing to Insure Accuracy****

Deck	Max. Slope (Inch/Ft)	Insulation	Base	Ply	Cap	Rating	Comments
C(15/32)	½	E,FF,F,FG (Optional)	(1+)GP,GPP, PP,GB,DB,V, DP	N/A	DKF,DGF, DG3,DL1, DL2	A	
C(15/32)	½	E,F,FG* (Optional)	(1+)GB,GB+, PP,V	(1+)GB, GB+,PP, V, DB,GP, GPP	DKF,DGF, DL1,DL2,	A	*Min 3/4"F, 15/16"FG, 2"E
NC	½	E,FF,F,FG (Optional)	(1+)GB,GB+, PP,V,DB,GP, GPP		DKF,DGF, DL1,DL2	A	
C(15/32)	1	E,FF,F,FG (Optional)	(1+)GB,DB, DP,PP,GP, GPP	N/A	DK,DP,DG, DG3,DL1, DL2	A	Gravel Surface
NC	3	E,FF,F,FG (Optional)	(1+)GB,DB, DP,PP,GPP, GP,V	N/A	DK,DP,DG, DL1, DL2	A	Gravel Surface

Deck: C-Combustible; ()=Min Thickness; NC-Non Combustible

Slope: UL=Unlimited

Insulation: E=ENRGY 3; F=Fesco; FF=Fesco Foam; RF=Retro-Fit; FG=FGRI

Base Sheet: PP=PermaPly 28; GB=GlasBase; GB+=GlasBase Plus; V=Ventulation; DB=DynaBase; DP=DynaPly

Ply Sheet: GP=GlasPly IV; GPP=GlasPly Premier

Cap Sheet: DK=DynaKap; DKF=DynaKap FR; DG=DynaGlas; DGF=DynaGlas FR; DG3=DynaGlas30 FR; DL1=DynaLastic 180 FR; DL2=DynaLastic 250 FR; DMF=DynaMax FR; DC=DynaClad

Coatings: TA=TopGard A; TB=TopGard B; FA=Fibrated Aluminum Roof Coating

Notes:

1. Approvals for combustible decks automatically apply to non-combustible decks.
2. Insulation is any thickness one or more layers unless otherwise stated.