

Standard PVC Membranes Advantages: Heat weldable seaming, superior tear, tensile and puncture resistance.

Product	Description	Use	Approx. Thickness	ASTM	Sizes	Sq. Ft.	Weight
SR-50	White Thermoplastic (PVC Membrane)	For use in all mechanically attached and fully adhered systems.	0.050" nominal	D 4434 Type III	75" x 80'	500	170 lbs.
					47" x 80'	313	107 lbs.
SR-60	White Thermoplastic (PVC Membrane)	For use in all mechanically attached and fully adhered systems.	0.060" nominal	D 4434 Type III	75" x 100'	625	238 lbs.
					47" x 100'	392	149 lbs.
SR-80	White Thermoplastic (PVC Membrane)	For use in all mechanically attached and fully adhered systems and premium guarantee programs.	0.080" nominal	D 4434 Type III	75" x 50'	313	166 lbs.
					47" x 50'	196	104 lbs.

V2 Thermoplastic Membranes Advantages: A rubberized thermoplastic alloy combining the recognized weathering characteristics of rubber to create one durable, cost effective membrane system.

Product	Description	Use	Approx. Thickness	ASTM	Sizes	Sq. Ft.	Weight
V2-50	Top: Black / Bottom: Gray Thermoplastic (PVC Membrane)	For use in all mechanically attached and fully adhered systems.	0.050" nominal	D 4434 Type III	75" x 80'	500	170 lbs.
					47" x 80'	313	107 lbs.
V2-60	Top: Black / Bottom: Gray Thermoplastic (PVC Membrane)	For use in all mechanically attached and fully adhered systems.	0.060" nominal	D 4434 Type III	75" x 100'	625	238 lbs.
					47" x 100'	392	149 lbs.

Specialty Thermoplastic Membranes and Systems

Product	Description	Use	Approx. Thickness	ASTM	Sizes	Sq. Ft.	Weight
Plus-50	White/ Fleece Back	For use in mechanically attached and fully adhered systems.	0.100" nominal	D 4434 Type III	75" x 55'	344	197 lbs.
Plus-60	White/ Fleece Back	For use in mechanically attached and fully adhered systems.	0.110" nominal	D 4434 Type III	75" x 55'	344	216 lbs.

FAS

Product	Description	Use	Approx. Thickness	ASTM	Sizes	Sq. Ft.	Weight
FAS	White Fiber Glass Reinforced PVC	Premium Thermoplastic Systems for fully adhered systems.	50 -0.050" minimum	D 4434 Type II	75" x 80'	500	170 lbs.
			60 -0.060" minimum	D 4434 Type II	75" x 100'	625	238 lbs.
			80 -0.080" nominal	D 4434 Type II	75" x 50'	313	166 lbs.



Johns Manville

*Ultra***Gard**® PVC Selector Guide

Thermoplastic Systems also provide a full line of Adhesives, Flashings, Accessories and Fasteners.

Product	Description	Size/Packaging
7" PVC Disc Caps	.60" Patches, White/Black	600/Box
6" Detail Strip; reinforced	White	6" x 150' 0.080 mils
Detail Membrane; non-reinforced	White	35" x 75' 0.080 mils
Type R Tie-In Membrane	Grease Resistant/BUR Tie-in	24" x 82'
Walk Way Pads	Gray	36" x 60'
Prefabricated Corners	White/Black/Gray/Sandstone	20/box
Universal Pipe Boots	White/Gray/Black/Sandstone	1" - 6"
PVC One Way Vent w/metal insert	Gray	4" base opening, 8.5" high
Vinyl Coated Metal	White/Gray/Black	4' x 10'
UltraGard Termination Bar	Aluminum	1.35" x 10'
3" Coated Metal Strips	N/A	3' x 10' 25 strips/bdl.
Caulk	White/Gray/Black	24 tubes/box
Thermoplastic Membrane Adhesive		
Solvent	For adhering vertical surfaces and field membrane	5 gallon pail
Latex	For adhering field membrane	5 gallon pail

Product	Description	Size/Packaging
Welding Solution		1 gallon cans; 6 per box
Membrane Cleaner		1 gallon cans; 6 per box
Seam Sealant	Clear	12, 16 oz. Bottles
Penetration Pockets	6" x 8"; White (Colors on Request)	5/boxes
Pourable Sealer	Black	1 gallon can: 1 pint
UltraGard DN Flameguard	Reinforced foil/craft slip sheet used to divorce membrane from contaminated or harmful surfaces	71" x 700'
UltraGard Polyester Mat. 9 oz.	Divorcement slip sheet, providing cushioning layer in various applications	12' x 100'
Aluminum Tape	For use in divorcing exhaust pipes from pipe boots and +G35 at coated metal joints	2" x 180'

For Technical Information

For Guarantee Information

Guarantee Services
Department
P.O. Box 625001
Littleton, CO 80162-5001
303 978 2191
FAX 303 978 2808

Regional Sales Offices

Eastern

437 North Grove Street
Berlin, NJ 08009-9700
856 768 7078
FAX 856 768 7034

For Technical Services Information
1 800 345 9603

Midwestern

2151 W. Channahon Road
Rockdale, IL 60436-8559
815 744 1545
FAX 815 741 6131

For Technical Services Information
1 800 231 1064

Southwestern

1612 Summit Avenue
Suite 204
Fort Worth, TX 76102
817 339 1500
FAX 817 339 1540

For Technical Services Information
1 800 654 0071

Canadian Customer Service

Write to:
27 Pearl Street
Portland, ME 04101
877 766 3295
(877 Roof by JM)
FAX 1 800 343 1331



717 17th Street, Denver, CO 80202, 800 654 3103, FAX 303 978 2318