

## **Suggested Short Form Spec**

## **Stainless Steel Chemical and Ozone Resistant, High Temperature Waterstop**

Waterstop indicated in drawings and specifications for contraction (control), expansion and construction joints to be Earth Shield® Stainless Steel (S/S) **Part No. JP558** as manufactured by **JP Specialties, Inc.** - 551 Birch Street, Lake Elsinore, CA 92530 - Phone 888-836-5778; International 951-674-6869; Fax 951-674-1315; Web <a href="www.earthshield.com">www.earthshield.com</a>; E-mail <a href="mailto:davidp@earthshield.com">davidp@earthshield.com</a>

- 1. Stainless steel waterstop shall conform to ASTM A 240 (type 316L), be 20 guage thick, and manufactured specifically as a waterstop, with outer flanges and center "V", as opposed to flat steel.
- 2. No equals or substitutions allowed.

JP Specialties, Inc. / Earth Shield® 551 Birch Street • Lake Elsinore, CA 92530 www.jpspecialties.com phone 800-821-3859 • international 951-674-6869 • fax 951-674-1315		
6" Stainless Steel Waterstop		
PART NUMBER	DRAWN BY	DATE
JP558	DRP	01/00
CAD FILE NAME	APPROVALS	SIZE
JP558		A
1		