

ROOFING

107 Velvet Roof Coating



Read Safety Data Sheet before using this product.

DESCRIPTION: 107 Velvet Roof Coating is a non-fibered specially formulated black coating for use on all types of smooth surface asphalt roofs. It is prepared from selected asphalts and is carefully mixed with refined solvents to form a heavy paint consistency. 107 Velvet Roof Coating will withstand the rigors of hot summer temperatures and provide excellent protection against the ravages of weather and corrosion.

USES: 107 Velvet Roof Coating is for application on all types of smooth surface, low slope asphalt roofs.

SURFACE PREPARATIONS: All surfaces should be swept clean of all dust, dirt or loose particles. Repair all blisters, breaks and cracks with 19 Ultra Rubberized Flashing Cement and 34 Asphalt Saturated Cotton Fabric or 31 Fiberglass Membrane.

APPLICATION: 107 Velvet Roof Coating is easily applied by wide fiber roof brush or airless spray equipment. Recommended application temperature is 40°F to 120°F. If applying at temperatures lower than 40°F, the substrate must be free of moisture and/or ice crystals.

COVERAGE RATE: Apply at the rate of 1 to 2 gallon per 100 sq. ft. (16-32 wet mils) depending upon the condition and porosity of the roof surface.

CAUTION: Do not use near open flame. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, do not induce vomiting. Call a physician immediately. Keep out of reach of children. Store in a heated room and keep container covered when not in use. Do not thin. Dispose of in an environmentally safe manner. Cover air intakes during application and while drying. Exterior use only.

Cold-process systems and coatings, either emulsion or solvent-based, should only be installed on decks with positive drainage. Per NRCA (National Roofing Contractors Association), "The criteria for judging proper slope for drainage is that there be no evidence of standing water on a deck 48 hours after it stops raining."

PACKAGING: Available in 5-gallon pails and 55-gallon drums.

If further information is needed, contact KARNAK Technical services at 800-526-4236.

PHYSICAL PROPERTIES & SPECIFICATIONS

Weight per Gallon:	7.85 lbs.
Solids by Weight:	72% Nominal
Solids by Volume:	66% Nominal
Color:	Black
Application Temp.:	40°F to 120°F
Dry Time:	8 to 24 hours
Service Temp (Cured Film):	15°F to 180°F
VOC Content:	270 g/L MAX