

## ROOFING

### 112 Non-Fibered Foundation & Roof Coating



\*Read Safety Data Sheet before using this product.\*

**DESCRIPTION:** 112 Non-Fibered Foundation & Roof Coating is a non-fibered asphalt coating used for preventing moisture penetration through foundation walls and for protecting a variety of roof surfaces. The finished coating forms a smooth, tough, flexible film that serves to help retard the entrance of moisture into or through foundation walls. On the roof it helps to protect and extend the life of smooth surface built-up asphalt (BUR), APP and SBS modified bitumen membranes, metal roof surfaces and roll roofing.

**USES:** 112 Non-Fibered Foundation & Roof Coating may be applied on exterior below grade CMU block and masonry walls where no hydrostatic pressure is present. Use also on smooth surface BUR, smooth or granule APP or SBS modified bitumen membrane roofs as well as on metal roof surfaces and roll roofing. May also be used to protect wood and metal below grade.

#### FEATURES, BENEFITS & ADVANTAGES:

- Penetrates and seals exterior below grade walls.
- Protects asphalt roofs from the hot sun and winter weather.
- Forms a smooth, tough, elastic film.
- Protects metal and wood below grade.
- May be used as a bituminous roof primer.

**SURFACE PREPARATIONS:** All surfaces should be dry, clean and free from oil or grease, dust, dirt, loose paint or other foreign matter.

**APPLICATION:** Apply with either a brush, roller or heavy-duty airless spray equipment in a smooth continuous coat over the entire surface. Coating should be continuous and free of pinholes or holidays. If not, apply a second application at right angles to the original coat. Allow at least 24 hours drying time between coats. Do not apply to wet surfaces. Recommended application temperature is 40°F to 120°F. If applying at temperatures lower than 40°F, the substrate must be free of moisture and/or ice crystals.

#### COVERAGE RATE:

Foundations: Apply at the rate of 1 to 1.5 gallon per 100 sq. ft. (16-24 wet mils)  
Roofs: Apply at the rate of 1 to 2 gallon per 100 sq. ft. (16-32 wet mils)  
Coverage rates may vary depending on the condition and porosity of the surface.

**CAUTION:** Do not use near open flame. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, do not induce vomiting. Call a physician immediately. Keep out of reach of children. Store in a heated room and keep container covered when not in use. Do not thin. Dispose of in an environmentally safe manner. Cover air intakes during application and while drying. Exterior use only.

**PACKAGING:** Available in 5-gallon pails, 1-gallon cans and 55-gallon drums.

If further information is needed, contact KARNAK Technical services at 800-526-4236.

#### PHYSICAL PROPERTIES & SPECIFICATIONS

Weight per Gallon:	7.85 lbs.
Solids by Weight:	72% Nominal
Solids by Volume:	66% Nominal
Color:	Black
Application Temp.:	40°F to 120°F
Dry Time:	8 to 24 hours
Service Temp (Cured Film):	-40°F to 180°F
VOC Content:	270 g/L MAX

