

# 19 Ultra Rubberized Flashing Cement (wet/dry)

**DESCRIPTION:**

Karnak #19 Ultra Flashing Cement is the next generation asbestos-free elastomeric flashing cement. Scientifically compounded with a selection of rubber reinforced asphalt, mineral fibers, and refined solvents. Karnak #19 Ultra is manufactured to a heavy pliable consistency for ease of application by trowel. #19 Ultra provides a durable elastomeric coating of greater strength, excellent adhesion and high resistance to water and weathering.

Karnak #19 Ultra is composed of special chemical ingredients which give it a unique water displacement quality (Wet/Dry). Karnak #19 Ultra dries to a tough, flexible, waterproof and corrosion proof rubber coating which gives maximum protection and excellent performance over wide ranges of temperature and weather conditions. Karnak #19 Ultra is available in 3 consistencies: Summer, Semi and Winter.

**FEATURES, BENEFITS AND ADVANTAGES:**

- Rubberized - elastomeric
- Wet or dry application
- Improved low-temperature flexibility
- Improved water and weather resistance
- Will not shrink or crack
- Smooth, easy to apply rubber-like trowel consistency
- Excellent adhesion
- Excellent resistance to flow (sag) at high roof temperatures
- Ready to apply - no mixing required
- Greater strength
- Cures faster than regular flashing cements
- VOC compliant
- ASTM compliant
- Sticks under water the first time.
- Can be used with fiberglass membrane under water.

**USES:**

Karnak #19 Ultra Flashing Cement is a general purpose asbestos-free flashing cement for repairing leaks in shingles, concrete, metal or asphalt roofs, SBS and APP modified bitumen membranes flashings on walls, chimneys, flues, skylight flashings, downspouts and cornices.

Karnak #19 Ultra is excellent for sealing cracks in concrete and brick, as a joint

**KARNAK**

330 CENTRAL AVENUE, CLARK, NJ 07066  
732-388-0300 • 800-526-4236 • FAX: 732-388-9422  
WEB: <http://www.karnakcorp.com>



# 19 Ultra Rubberized Flashing Cement (wet/dry)

filler for precast roof slabs, for repair, patch and flashing detail on SBS and APP modified membranes, and for general purpose use in maintenance of exposed buildings and structures.

## **SURFACE PREPARATION:**

All surfaces should be clean, dry and free from oil, grease, dust, dirt, loose paint or other foreign matter. Excess water should be removed, if possible, before application of #19 Ultra.

## **APPLICATION:**

Spread Karnak #19 Ultra Flashing Cement to an average thickness of 1/8" (approximately 8 gallons per square) and press tightly into joints, seams or cracks.

## **TO REPAIR CRACKS, BREAKS AND BLISTERS:**

1. Spread Karnak #19 Ultra Flashing Cement over the damaged area at an average thickness of 1/8".
2. Embed Karnak Cotton, Glass or Polyester Membrane reinforcement in the #19 Ultra Flashing Cement.
3. Apply an additional coat of Karnak #19 Ultra Flashing Cement over the entire patch at an average thickness of 1/8".

## **SPECIFICATIONS:**

ASTM D-4586 Type I Class I & Class II

ASTM D-3409

Fed Spec SS-C-153 Type I (Asbestos-Free)

## **PHYSICAL PROPERTIES:**

1. Consistency: A smooth rubber-like trowel consistency which will readily spread on and adhere to vertical and horizontal surfaces without sagging.
2. Character of Dried Film: Excellent adhesion to masonry, steel, cured concrete, shingles, asphalt roofing, skylight flashings and a variety of other surfaces.
3. Film Performance Characteristics: The dried film retains its elasticity and ductility so that the material will resist extreme variations in temperature and weather.
4. Sag Resistance: Excellent resistance to flow at high roof temperatures on vertical surfaces.
5. Homogenized: Thoroughly mixed and consistent throughout.
6. Consistency: 19 Ultra is always smooth and of a trowel consistency.

# KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066  
732-388-0300 • 800-526-4236 • FAX: 732-388-9422  
WEB: <http://www.karnakcorp.com>



# 19 Ultra Rubberized Flashing Cement (wet/dry)

**CAUTION:**

Combustible Mixture: do not use near open flame. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, **do not induce vomiting**. Call a physical immediately.

Keep out of reach of children. Keep container covered when not in use. **Do not thin**. Consult MSDS for further safety precautions. Dispose of in an environmentally safe manner. Cover air intakes during application and while drying.

**CARE OF TOOLS:**

Tools and other equipment should be thoroughly cleaned with mineral spirits, taking necessary precautions when handling combustible materials. To clean hands use #709 Karnak Karna-Klean or a waterless hand cleaner.

**PACKAGING:**

Available in 1 gallon cans, 3 gallon buckets, 5 gallon pails and 10.1 oz. cartridges.

**If further information is needed, contact Karnak Technical Services at 1-800-526-4236.**

Please see page 222 for additional mold and safety information.

**KARNAK**

330 CENTRAL AVENUE, CLARK, NJ 07066  
732-388-0300 • 800-526-4236 • FAX: 732-388-9422  
WEB: <http://www.karnakcorp.com>

