

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012)

## SAFETY DATA SHEET

# 671 Karna-Seal Silicone Roof Sealant

### SECTION 1: Identification

#### 1.1. Product identifier

Trade name

671 Karna-Seal Roof Sealant

Product no.

671

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Adhesive

Restricted to professional users.

Uses advised against

None known.

#### 1.3. Details of the supplier of the safety data sheet

Company and address

**KARNAK Corporation**

330 Central Avenue

Clark, New Jersey

USA

1.732.388.0300

karnakcorp.com

E-mail

info@karnakcorp.com

SDS date

8/24/2023

SDS Version

1.0

Date of previous version

8/24/2023 (1.0)

#### 1.4. Emergency telephone number

Contact the poison control at 1-800-222-1222 (24/7) or use the webPOISONCONTROL® ([triage.webpoisoncontrol.org](http://triage.webpoisoncontrol.org)) to get specific guidance for your case

See also section 4 "First aid measures".

### SECTION 2: Hazard(s) identification

#### OSHA/HCS status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

#### 2.1. Classification of the substance or mixture

Skin Irrit. 2; H315, Causes skin irritation.

Eye Irrit. 2; H319, Causes serious eye irritation.

#### 2.2. Label elements

Hazard pictogram(s)



Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012)

**Signal word**

Warning

**Hazard statement(s)**

Causes skin irritation. (H315)  
Causes serious eye irritation. (H319)

**Precautionary statement(s)**

**General**

-

**Prevention**

Wash hands thoroughly after handling. (P264)  
Wear eye protection/protective gloves/protective clothing. (P280)

**Response**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)  
If eye irritation persists: Get medical advice/attention. (P337+P313)

**Storage**

-

**Disposal**

-

**Additional labelling**

Not applicable.

**2.3. Other hazards**

**Additional warnings**

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

**SECTION 3: Composition/Information on Ingredients**

**3.1. Substances**

Not applicable. This product is a mixture.

**3.2. Mixtures**

Product/substance	Identifiers	% w/w	Classification	Note
Butan-2-one O,O',O"- (methylsilylidyne)trioxime	CAS No.: 22984-54-9	3-5%	Acute Tox. 4, H312 Skin Sens. 1, H317 Eye Irrit. 2, H319	
3-aminopropyltriethoxysilane	CAS No.: 919-30-2	1-3%	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Skin Sens. 1, H317	

Where the concentration of an ingredient is expressed as a range the exact concentration has been withheld as a trade secret.

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

**Other information**

-

**SECTION 4: First-aid measures**

**4.1. Description of first aid measures**

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012)

#### General information

If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 911 and give immediate treatment (first aid).

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

#### Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

#### Eye contact

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

#### Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

#### Burns

Not applicable.

#### 4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

#### Information to medics

Bring this safety data sheet or the label from this product.

### SECTION 5: Fire-fighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Nitrogen oxides (NO<sub>x</sub>)

Carbon oxides (CO / CO<sub>2</sub>)

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the Poison Help Line on 1-800-222-1222 (24/7) in order to obtain further advice.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012)

#### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.  
Keep unauthorized persons away from the spill

#### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.  
Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

#### 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.  
See section 8 "Exposure controls/personal protection" for protective measures.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area.  
See section 8 "Exposure controls/personal protection" for information on personal protection.

#### 7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

##### Recommended storage material

Always store in containers of the same material as the original container.

##### Liquid class

Combustible Liquid / Class IIIA (NFPA 30)

##### Storage temperature

No specific requirements

##### Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

#### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

No substances are listed with a permissible exposure limit (ref: 29 CFR 1910.1000 TABLE Z-1)

#### 8.2. Exposure controls

Control is unnecessary if the product is used as intended.

##### General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

##### Exposure scenarios

There are no exposure scenarios implemented for this product.

##### Exposure limits

Occupational exposure limits have not been defined for the substances in this product.

##### Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of vapours.

##### Hygiene measures

Take off contaminated clothing and wash it before reuse.

##### Measures to avoid environmental exposure

No specific requirements.

#### Individual protection measures, such as personal protective equipment

##### Generally

No specific requirements

##### Respiratory Equipment

No specific requirements

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012)

**Skin protection**

No specific requirements.

**Hand protection**

No specific requirements.

**Eye protection**

No specific requirements.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**Physical state**

Paste=

**Color**

White

**Odor**

Mild

**Odor threshold (ppm)**

Testing not relevant or not possible due to the nature of the product.

**pH**

Testing not relevant or not possible due to the nature of the product.

**Density (g/cm<sup>3</sup>)**

1.03

**Relative density**

1.03

**Kinematic viscosity**

Testing not relevant or not possible due to the nature of the product.

#### Phase changes

**Melting point (°F)**

Testing not relevant or not possible due to the nature of the product.

**Boiling point (°F)**

Testing not relevant or not possible due to the nature of the product.

**Vapour pressure**

Testing not relevant or not possible due to the nature of the product.

**Vapour density**

Testing not relevant or not possible due to the nature of the product.

**Decomposition temperature (°F)**

Testing not relevant or not possible due to the nature of the product.

#### Data on fire and explosion hazards

**Flash point (°F)**

185

**Flash point (°C)**

85

Flash Point Method: ASTM D-93.

**Flammability (°F)**

The material is ignitable.

**Auto-ignition temperature (°F)**

Testing not relevant or not possible due to the nature of the product.

**Explosion limits (% v/v)**

Testing not relevant or not possible due to the nature of the product.

#### Solubility

**Solubility in water**

Insoluble

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012)

**n-octanol/water coefficient**

Testing not relevant or not possible due to the nature of the product.

**Solubility in fat (g/L)**

Testing not relevant or not possible due to the nature of the product.

**9.2. Other information**

**VOC (g/L)**

48

**Other physical and chemical parameters**

No data available.

**Oxidizing properties**

Testing not relevant or not possible due to the nature of the product.

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No data available.

**10.2. Chemical stability**

The product is stable under the conditions, noted in section 7 "Handling and storage".

**10.3. Possibility of hazardous reactions**

None known.

**10.4. Conditions to avoid**

None known.

**10.5. Incompatible materials**

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

**10.6. Hazardous decomposition products**

The product is not degraded when used as specified in section 1.

**SECTION 11: Toxicological information**

**11.1. Information on toxicological effects**

**Acute toxicity**

Product/substance	Silicon dioxide
Test method:	OECD 401
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	>2000 mg/kg

Product/substance	Butan-2-one O,O',O''-(methylsilyldiyl)trioxime
Species:	Rabbit
Route of exposure:	Oral
Test:	NOEC
Result:	10 mg/kg

Product/substance	Butan-2-one O,O',O''-(methylsilyldiyl)trioxime
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	2463 mg/kg

Product/substance	3-aminopropyltriethoxysilane
Species:	Rat
Route of exposure:	Oral
Test:	LD50

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012)

Result: 1490 mg/kg

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/irritation**

Causes serious eye irritation.

**Respiratory sensitisation**

Based on available data, the classification criteria are not met.

**Skin sensitisation**

May cause an allergic skin reaction.

**Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

**Carcinogenicity**

Based on available data, the classification criteria are not met.

**Reproductive toxicity**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Long term effects**

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

**Other information**

Silicon dioxide has been classified by IARC as a group 3 carcinogen.

## SECTION 12: Ecological information

**12.1. Toxicity**

No data available.

**12.2. Persistence and degradability**

No data available.

**12.3. Bioaccumulative potential**

No data available.

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

**12.6. Other adverse effects**

None known.

## SECTION 13: Disposal considerations

**RCRA Hazardous waste ("P" and "U" list) (40 CFR 261)**

None of the components are listed


**Specific labelling**

**Contaminated packing**

Packaging containing residues of the product must be disposed of similarly to the product.

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012)

**SECTION 14: Transport information**

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
DOT	UN1993	FLAMMABLE LIQUID, N.O.S. (Butan-2-one O,O',O''-(methylsilylidyne)trioxime)	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

\* Packing group

\*\* Environmental hazards

**Additional information**

ADR / See Table A, Section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

This product is within scope of the regulations of transport of dangerous goods.

**14.6. Special precautions for user**

Not applicable.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

No data available.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**15.2. U.S. Federal regulations**

**TSCA**

Silicon dioxide is listed in the non-confidential portion

Butan-2-one O,O',O''-(methylsilylidyne)trioxime is listed in the non-confidential portion

**Clean Air Act**

None of the components are listed

**EPCRA Section 302**

None of the components are listed

**EPCRA Section 304**

None of the components are listed

**EPCRA section 313**

None of the components are listed

**CERCLA**

None of the components are listed

**State regulations**

**California / Prop. 65**

None of the components are listed

**Massachusetts / Right To Know Act**

Silicon dioxide is listed

**New Jersey / Right To Know Act**

None of the components are listed

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012)

**New York / Right To Know Act**

None of the components are listed

**Pennsylvania / Right To Know Act**

Silicon dioxide is listed

—

**15.4. Restrictions for application**

Restricted to professional users.

**15.5. Demands for specific education**

No specific requirements.

**15.6. Additional information**

Not applicable.

**15.7. Chemical safety assessment**

No

**15.8. Sources**

OSHA Hazard Communication Standard (29 CFR 1910.1200)

## SECTION 16: Other information

**Full text of H-phrases as mentioned in section 3**

H302, Harmful if swallowed.

H312, Harmful in contact with skin.

H314, Causes severe skin burns and eye damage.

H317, May cause an allergic skin reaction.

H319, Causes serious eye irritation.

**The full text of identified uses as mentioned in section 1**

None known.

**Abbreviations and acronyms**

ACGIH = American Conference of Governmental Industrial Hygienists

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CERCLA = Comprehensive Environmental Response Compensation and Liability Act

DOT = Department of Transportation

EINECS = European Inventory of Existing Commercial chemical Substances

EPCRA = Emergency Planning and Community Right-To-Know Act

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

HCIS = Hazardous Chemical Information System

HNOC = Hazards Not Otherwise Classified

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

NFPA = National Fire Protection Association

NIOSH = National Institute for Occupational Safety and Health

OECD = Organisation for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

PBT = Persistent, Bioaccumulative and Toxic

RCRA = Resource Conservation and Recovery Act

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SARA = Superfund Amendments and Reauthorization Act

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2012)

SCL = A specific concentration limit.

STEL = Short-term exposure limits

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TSCA = The Toxic Substances Control Act

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

#### Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by HCS (29 CFR 1910.1200).

#### ▼ The safety data sheet is validated by

Farooq Ahmed

#### Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: US-en