

Complete Karnak U.L. Approved Systems Listing

Alphabetical Company Listing: P-R

Company	Deck Type	Membrane Manufact.	System	INC.	Surfacing Coating	U.L. Class
Performance Rfg. Systems, Inc.	NC	Permax	Insulation: WF, GF, Perlite, 1/2" Max. Base Sheet: Type G-1, G-2, 15 or 30 sheet Membrane: Permax A-Economy, A-Special, A-Xtra, {(A-Special A-Xtra) Mineral}	1/2"	#97 or #97AF (1-1/2 gal/sq)	A
	NC	Permax	Insulation: WF, GF, Perlite, ISO, Compos Base Sheet: Type G-2 Membrane: Permax A-Economy, A-Special, A-Xtra, {(A-Special A-Xtra) Mineral}, Permax B-Economy, B-Special, B-Xtra, B-Xtra 250	1"	#97 or #97AF (1-1/2 gal/sq)	A
	C-15/32	Permax	Base Sheet: 2plies Type G-2 or 1ply G-2 Membrane: Permax A-Economy, A-Special, A-Xtra, {(A-Special A-Xtra) Mineral}, Permax B-Economy, B-Special, B-Xtra, B-Xtra 250	1/4"	#97 or #97AF (2 gal/sq)	A
	C-15/32	Permax	Insulation: ISO, ISO/Composit Base Sheet: 2plies Type G-2 or 1ply G-2 Membrane: Permax A-Economy, A-Special, A-Xtra, {(A-Special A-Xtra) Mineral}, Permax B-Economy, B-Special, B-Xtra, B-Xtra 250	1/2"	#97 or #97AF (2 gal/sq)	A
	NC	Derbigum	Base Sheet: (Optional)1/moreType G-1, G-2 Insulation: (Optional) GF, Per., ISO, Comp Ply Sheet: 2 or more Type G-1 or G-2 Membrane: Derbigum	1/4"	#97 or #97AF (1-1/2 gal/sq)	A
	C-15/32	Derbigum	Base Sheet: (Optional)1/moreType G-1, G-2 Insulation: (Optional) GF, Per., ISO, Comp Ply Sheet: 2 or more Type G-1 or G-2 Membrane: Derbigum	1/4"	#97 or #97AF (1-1/2 gal/sq)	A
	C-15/32	Permax	Insulation: GF 1-1/2" Base Sheet: 1ply Type G-2 Membrane: Permax A-Economy, A-Special, A-Xtra, {(A-Special A-Xtra) Mineral},	1/4"	#97 or #97AF (1 to 2 gal/sq)	B
	C-15/32	Derbigum	Insulation: GYP 1/2", GF 1-1/2" min. Base Sheet: 1+ ply Type G-1 or G-2 Membrane: Derbigum	1/2"	#97 (1-1/2 gal/sq)	B
	C-15/32	Derbigum	Base Sheet: (Optional)1/moreType G-1, G-2 Insulation: (Optional) GF, Per., ISO, Comp Ply Sheet: 1 or more Type G-1 or G-2 Membrane: Derbigum	1/4"	#97 (1-1/2 gal/sq)	B
Polara Rfg.Sys. Durham, N.C.	NC	Polara	Insulation: GF, Per., ISO, ISO/Comp Base Sheet: Type G-2 Membrane: Polara MB Cap Sheet	1"	#97 or #97AF (1-1/2 gal/sq)	A
	C-15/32	Polara	Base Sheet: 2 plies G-1 or 1 ply G-2 Membrane: Polara MB Cap Sheet	1/4"	#97 or #97AF (2 gal/sq)	A
	C-15/32	Polara	Insulation: ISO, ISO/Comp Base Sheet: 2 plies G-1 or 1 ply G-2	1/2"	#97 or #97AF (2 gal/sq)	A

			Membrane: Polara MB Cap Sheet			
Proteccion Ant- icorrosiva De Cuautitlan S A DE C V EDO DE Mexico Mexico	NC	Coverply	Insulation: (Optional) WF, GF, Perlite Base Sheet: Type G-2 Membrane: Coverply APP 3mm Smooth, 4mm Smooth, 4.5mm Mineral	2"	#97 or #97AF (1 to 2 gal/sq)	A
	NC	Coverply	Insulation: (Optional) WF, GF, Perlite ISO, ISO/Perlite Composite Base Sheet: Type G-2 Membrane: Coverply APP 3mm Smooth, 4mm Smooth, 4.5mm Mineral, SBS 3mm Smooth, 4mm Smooth	1"	#97 or #97AF (1-1/2 gal/sq)	A
	C-15/32	Coverply	Barrier Board: Water Resist. 1/2" GYP Insulation: (Optional) WF, GF, Perlite ISO, ISO/Perlite Composite Base Sheet: Type G-2 Membrane: Coverply APP 3mm Smooth, 4mm Smooth, 4.5mm Mineral, SBS 3mm Smooth, 4mm Smooth	1"	#97 or #97AF (1-1/2 gal/sq)	A
	NC	Coverply	Base Sheet: (Optional) Type G-2 Membrane: Coverply APP 3mm Smooth, 4mm Smooth, 4.5mm Mineral, SBS 3mm Smooth, 4mm Smooth	1"	#97 or #97AF (1-1/2 gal/sq)	A
	C-15/32	Coverply	Base Sheet: 2 Plies Type G-2 Membrane: Coverply APP 3mm Smooth, 4mm Smooth, 4.5mm Mineral, SBS 3mm Smooth, 4mm Smooth	1/4"	#97 or #97AF (2 gal/sq)	A
	C-15/32	Coverply	Insulation: ISO, ISO/Perlite Comp. 2" min Base Sheet: Type G-2 Membrane: Coverply APP 3mm Smooth, 4mm Smooth, 4.5mm Mineral, SBS 3mm Smooth, 4mm Smooth	1/2"	#97 or #97AF (2 gal/sq)	A
	C-15/32	Coverply	Insulation: GF 1-1/2" Base Sheet: Type G-2 Membrane: Coverply APP 3mm Smooth, 4mm Smooth, 4.5mm Mineral, SBS 3mm Smooth, 4mm Smooth	1/4"	#97 or #97AF (2 gal/sq)	
	C-15/32	Coverply	Base Sheet: 1 or more plies Type G-2 Membrane: Coverply APP 3mm Smooth, 4mm Smooth, 4.5mm Mineral, SBS 3mm Smooth, 4mm Smooth	1/2"	#97 or #97AF (1-1/2-2gal/sq)	B
	C-15/32	Coverply	Insulation: AC Foam II 1.2" min Base Sheet: 1 or more plies Type G-2 Membrane: Coverply APP 3mm Smooth, 4mm Smooth, 4.5mm Mineral, SBS 3mm Smooth, 4mm Smooth	1/2"	#97 or #97AF (1-1/2-2gal/sq)	B
	C-15/32	Coverply	Insulation: ISO 1.2" Insulation: WF, GF, Perlite 1/2" min Membrane: Coverply APP 3mm Smooth, 4mm Smooth, 4.5mm Mineral, SBS 3mm Smooth, 4mm Smooth	1"	#97 or #97AF (1-1/2-2gal/sq)	B
	C-15/32	Coverply	Insulation: ISO 1.2" Base Sheet: Type G-2 Membrane: Coverply APP 3mm Smooth, 4mm Smooth, 4.5mm Mineral, SBS 3mm Smooth, 4mm Smooth	1/2"	#97 or #97AF (1-1/2 gal/sq)	B
	C-15/32 M R	Coverply	Existing Roof System: Class A,B,C Insulation: (Optional)ISO,Comp,GF,WF,PER Insulation: "Nord Board" (Gravel may be removed) Membrane: Coverply APP 3mm Smooth, 4mm Smooth, 4.5mm Mineral, SBS 3mm	1/2"	#97 or #97AF (1-1/2 gal/sq)	B

			Smooth, 4mm Smooth			
	C-15/32 M R	Coverply	Existing Roof System: Class A, B Smooth BUR Insulation: (Optional) ISO, Comp, GF, WF, PER Base Sheet: 1 or more plies Type G-2 Membrane: Coverply APP 3mm Smooth, 4mm Smooth, 4.5mm Mineral, SBS 3mm Smooth, 4mm Smooth	1/2"	#97 or #97AF (1-1/2 gal/sq)	A

KARNAK 800-526-4236

330 Central Avenue, Clark, NJ 07066
(732) 388-0300 fax: (732) 388-9422

For more information, email Karnak at info@KarnakCorp.com
Copyright ©1997, Karnak Corporation. All rights reserved.
