



PRODUCT GUIDE

Roofing, Waterproofing & Dampproofing



info@karnakcorp.com

karnakcorp.com

Table of Contents

Roofing Repair Mastics & Cements	2-3
Asphalt Roof Coatings	4
Acrylic Base Coats	5
Reflective Roof Coatings - Aluminum	6
Reflective Roof Coatings - White	7
Adhesives	8
Primers	9
Dampproofing	10
Waterproofing	11
Resaturants	11
Reinforcing Fabrics & Tapes	12
Miscellaneous	13
Caulks	14

Roofing Repair Mastics & Cements

Product

Approvals



18 Perfectseal Roof Cement

- General purpose roof repair cement
- Heavy trowel consistency
- Excellent resistance to flow on vertical surfaces
- 5-gallon

Use on asphalt roofs, concrete and metal roofs, shingles, general purpose use on exterior of buildings and structures

ASTM & Specifications	UL	FM	CRRC	Miami Dade
D-4586 Type I Class I SS-C-153 Type 1(AF)	•			•



19 Flashing Cement

- Smooth trowel consistency
- Excellent general purpose repair cement
- Adheres to vertical & horizontal surfaces
- 10.1 oz. caulk tubes, 1-gallon, 3-gallon, 5-gallon

Use on asphalt roofs, concrete and, metal roofs, shingles, general purpose use on exterior of buildings and structures

ASTM & Specifications	UL	FM	CRRC	Miami Dade
D-4586 Type I Class I SS-C-153 Type 1(AF)	•			•



19 Ultra Rubberized Wet/Dry Flashing Cement

- Rubberized elastomeric flashing cement
- Stops leaks on wet or dry surfaces, emergency repair
- Smooth trowel consistency
- 10.1 oz. caulk tubes, 1-gallon, 3-gallon, 5-gallon

Use on asphalt roofs, concrete and, metal roofs, shingles, general purpose use on exterior of buildings and structures.

ASTM & Specifications	UL	FM	CRRC	Miami Dade
D-4586 Type I Class I & Class II D-3409 SS-C-153 Type 1(AF)	•		•	•

Roofing Repair Mastics & Cements

Product

Approvals



155 Amphibikote Wet/Dry

- Emergency roof repair cement
- Bonds to wet or dry surfaces
- Smooth trowel consistency
- 10.1 oz. caulk tubes, 1-gallon, 5-gallon

Use on asphalt roofs, concrete and, metal roofs, shingles, general purpose use on exterior of buildings and structures.

ASTM & Specifications	UL	FM	CRRC	Miami Dade
D-4586 Type I Class I & Class II D-3409 SS-C-153 Type I(AF)	•			•



229 AR-Elastomeric/Trowel Grade

- Highly rubberized waterproof sealant
- Maintenance & repair of asphalt, concrete, metal, foam roofs
- Use to seal pitch pans, gravel stops, gutters, problem areas
- Superior protection in ponding areas
- 30 oz. caulk tubes, 1-gallon, 3-gallon, 5-gallon

Use on asphalt BUR, APP & SBS membrane roofs, concrete, metal, spray urethane foam roofs, masonry, stone and wood

ASTM & Specifications	UL	FM	CRRC	Miami Dade
D-4586 Type I Class I	•	•		•



502MS Karna-Flex

- Thermoplastic rubber SEBS sealant - White, Black, Gray
- Ideal for patch & repair even in ponding areas
- Flexible, durable, weather-resistant and UV stable
- 30 oz. caulk tubes, 1-gallon, 3-gallon

Use on metal, TPO, PVC, Hypalon, EPDM, Concrete, spray foam and asphalt (black only) roof surfaces

ASTM & Specifications	UL	FM	CRRC	Miami Dade
			•	•



505MS Karna-Flex WB

- Elastomeric acrylic sealant
- Use to patch & repair
- Flexible, durable, weather-resistant & UV stable
- 3.5-gallon, 5-gallon

Use on metal, TPO, PVC, Hypalon, EPDM, Concrete, spray foam and asphalt roof surfaces

ASTM & Specifications	UL	FM	CRRC	Miami Dade
			•	•



671 Karna-Seal Silicone Roof Sealant

- Single-component, moisture cure silicone sealant - White and Black
- Resists permanent ponding water
- Bonds to several different roof substrates
- For horizontal and vertical use, will not sag
- 10.1 oz. caulk tubes, 1-gallon, 2.5-gallon

Use on modified bitumen membranes, metal, TPO, PVC, EPDM, Spray Polyurethane Foam and concrete

ASTM & Specifications	NSF	UL	FM	CRRC	Miami Dade
D-6694					•



920 Fibered Emulsion Mastic

- Asphalt emulsion repair mastic, trowel grade
- Ideal for repairs on exterior duct work
- Durable protective sealant for asphalt, concrete, metal & wood
- 5-gallon

Use on concrete, metal, asphalt, wood

ASTM & Specifications	UL	FM	CRRC	Miami Dade
D-1187 Type I, D-1227 Type II Class I, SS-R-1787 (AF) MIL-R-3472A	•			•

Asphalt Roof Coatings

Product

Approvals



71 Fibered Asphalt Roof Coating

- Protects asphalt roofs from hot sun & winter weather
- Fills in hairline cracks & bare spots on asphalt roofs
- Coverage: 4 gallons per 100 sq. ft.
- 1-gallon, 5-gallon, 55-gallon

Use on smooth BUR, APP and SBS modified membranes, metal roofs and roll roofing

ASTM & Specifications	UL	FM	CRRC	Miami Dade
D-4479 Type I SS-A-694D	•			•



100 Non-Fibered Emulsion Roof Coating

- Adds additional asphalt protection to cover worn roof areas
- Prepares roof for reflective coating applications
- Coverage: 2-3 gallons per 100 sq. ft.
- 5-gallon, 55-gallon, 275-gallon

Use on asphalt BUR, APP & SBS modified bitumen membranes, metal and wood

ASTM & Specifications	UL	FM	CRRC	Miami Dade
D-1187 Type II, D-1227 Type II Class I, SS-R-1787 (AF) MIL-R-3472A	•			•



112 Non-Fibered Asphalt Roof Coating

- Non-fibered asphalt roof coating
- Adds a layer of asphalt protection to weathered roofs
- Coverage: 1-2 gallons per 100 sq. ft.
- 1-gallon, 5-gallon, 55-gallon

Use on smooth surface BUR, APP and SBS modified bitumen membrane roofs

ASTM & Specifications	UL	FM	CRRC	Miami Dade
				•



220 Fibered Emulsion Coating

- Seals cracked and alligatored asphalt surfaces - dries to durable finish
- Excellent base primer for reflective coatings
- Coverage: 4 gallons per 100 sq. ft.
- 5-gallon, 55-gallon, 275-gallon

Use on asphalt BUR, APP & SBS modified bitumen membranes, metal and wood

ASTM & Specifications	UL	FM	CRRC	Miami Dade
D-1187 Type I & Type II, D-1227 Type II Class I, SS-R-1781 (AF) MIL-R-3472A	•	•		•



229 AR-Elastomeric/Brush Grade

- Highly rubberized waterproof sealant - superior protection in ponding areas
- Seals weathered asphalt roofs
- Coverage: 2-4 gallons per 100 sq. ft.
- 30 oz. caulk tubes, 1-gallon, 3-gallon, 5-gallon

Use on asphalt BUR, APP & SBS membrane roofs, concrete, metal and spray urethane foam roofs

ASTM & Specifications	UL	FM	CRRC	Miami Dade
D-4479 Type I		•		•

Acrylic Base Coats

Product

Approvals



404 Corrosion Proof Base Coat

Use over properly prepared metal roofs

- Self-priming acrylic base coat with light gray indicator color, provides superior adhesion to metal
- Stops the formation of rust and corrosion
- Coverage: 1.5 gallons per 100 sq. ft.
- 5-gallon, 55-gallon, 275-gallon

ASTM & Specifications

UL FM CRRC Miami Dade



405 Bond-N-Shield Base Coat

Use over properly prepared, low-slope asphalt roofs

- Self-priming acrylic base coat with light blue indicator color, provides superior adhesion to asphalt surfaces
- Prevents asphalt bleed-thru and improves blister resistance in ponding areas
- Coverage: 1.5 gallons per 100 sq. ft.
- 5-gallon, 55-gallon, 275-gallon

ASTM & Specifications

UL FM CRRC Miami Dade



406 Tru-Grip Base Coat

Use over properly prepared TPO, PVC, Hypalon, EPDM, Smooth BUR and Mod Bit membrane roofs

- Self-priming acrylic base coat with marine green indicator color, provides superior adhesion to substrate
- Blocks plasticizer migration for coating durability, improves blister resistance in ponding areas
- Coverage: 1.5 gallons per 100 sq. ft.
- 5-gallon, 55-gallon, 275-gallon

ASTM & Specifications

UL FM CRRC Miami Dade
•

Reflective Roof Coatings - Aluminum

Product

Approvals



27 Perfectseal Fibered Aluminum Roof Coating

Use on smooth BUR, APP & SBS modified bitumen membranes, metal roofs

- Good reflectivity for protecting the underlying roof surface
- Fibered for longer service life
- Coverage: 1-1.5 gallons per 100 sq. ft.
- 5-gallon

ASTM & Specifications
D-2824 Type III

UL **FM** **CRRC** **Miami Dade**
•



28 Perfectseal Non-Fibered Aluminum Roof Coating

Use on smooth BUR, APP & SBS modified bitumen membranes, metal roofs

- Good reflectivity for protecting the underlying roof surface
- Good for use as a re-coat over existing aluminum coated roof
- Coverage: 0.5-1 gallon per 100 sq. ft.
- 5-gallon

ASTM & Specifications
D-2824 Type I

UL **FM** **CRRC** **Miami Dade**
•



97 Fibered Aluminum Roof Coating

Use on smooth BUR, APP & SBS modified bitumen membranes, metal roofs

- Fibered aluminum for heavy duty service
- Extends the life of asphalt and modified bitumen membranes
- Coverage: 1-1.5 gallon per 100 sq. ft.
- 1-gallon, 5-gallon

ASTM & Specifications
D-2824 Type III, D-3805
TT-C-498C(AF)
D-962 Type II

UL **FM** **CRRC** **Miami Dade**
• • • •



98 Fibered Aluminum Roof Coating

Use on smooth BUR, APP & SBS modified bitumen membranes, metal roof

- Highest leafing aluminum concentration for superior reflectivity and service life
- Extends the life of asphalt and modified bitumen membranes
- Coverage: 1-1.5 gallons per 100 sq. ft.
- 5-gallon

ASTM & Specifications
D-2824 Type III, D-3805
TT-C-498C(AF)
D-962 Type II

UL **FM** **CRRC** **Miami Dade**
• • • •



169 Non-Fibered Aluminum Roof Coating

Use on smooth BUR, APP & SBS modified bitumen membranes, metal roofs

- Non-fibered aluminum for smooth asphalt roof surfaces
- Extends the life of asphalt and modified bitumen membranes
- Coverage: 0.5-1 gallon per 100 sq. ft.
- 1-gallon, 5-gallon

ASTM & Specifications
D-2824 Type I, D-3805
TT-C-498C(AF)
D-962 Type II

UL **FM** **CRRC** **Miami Dade**
• • • •



298 Alumin-R Rubberized Aluminum Roof Coating

Use on smooth BUR, APP & SBS modified bitumen membranes, metal roofs

- Elastomeric, rubberized for longer service life
- Greater resistance to ponding water
- Coverage: 1.5-2 gallons per 100 sq. ft.
- 3-gallon, 5-gallon

ASTM & Specifications
D-2824 Type III
D-962 Type II
D-3805

UL **FM** **CRRC** **Miami Dade**
• • • •

Reflective Roof Coatings - White (Other colors available)

Product

Approvals



501 Elasto-Brite

- Premium, 100% acrylic polymer, elastomeric coating
- Superior reflectivity and elongation for the protection of the underlying roof surface
- Coverage: Apply over 400 series base coat at 1.5 gallons per 100 sq. ft.
- 5-gallon, 55-gallon, 275-gallon

Use over any of our 400 series base coats or over prepared smooth BUR, APP & SBS modified bitumen membranes and concrete, metal and spray polyurethane foam roofs

ASTM & Specifications	NSF	UL	FM	CRRC	Miami Dade
D-6083	•	•	•	•	•



502 RC-W Elasto-Kote (502 Base & 502 Finish)

- Highly elastic, SEBS thermoplastic rubber roof coating
- Low permeability provides excellent water blister resistance
- Coverage: Apply 502 Base first at the rate of 1.5 gallons per 100 sq. ft. then 502 Finish at 1.5 gallons per 100 sq. ft.
- 5-gallon, 55-gallon

Use on metal roofs, spray polyurethane foam roofs, EPDM, TPO, PVC roofs, concrete, stucco and wood structural surfaces.

ASTM & Specifications	NSF	UL	FM	CRRC	Miami Dade
D-6083 (Except Solvent-Based)	•	•	•	•	•



505HS Mohave Coat

- Premium, high-solids, 100% acrylic polymer, elastomeric coating
- Superior reflectivity and elongation for the protection of the underlying roof surface
- Coverage: Apply over 400 series base coat at 1.5 gallons per 100 sq. ft.
- 5-gallon, 55-gallon, 275-gallon

Use over any of our 400 series base coats or over prepared smooth BUR, APP & SBS modified bitumen membranes and concrete, metal and spray polyurethane foam roofs

ASTM & Specifications	UL	FM	CRRC	Miami Dade
D-6083			•	



529 Renu-White

- Reflective, co-polymer acrylic roof coating
- Excellent choice for re-coating existing acrylic coated roofs
- Coverage: Apply over 400 series base coat at 1.5 gallons per 100 sq. ft.
- 5-gallon, 55-gallon, 275-gallon

Use over any of our 400 series base coats or over prepared smooth BUR, APP & SBS modified bitumen membranes and metal roofs as well as above grade concrete, concrete block, brick, stucco and wood.

ASTM & Specifications	UL	FM	CRRC	Miami Dade
			•	



670HS Karna-Sil Ultra

- White, single-component, high solids, moisture cure silicone roof coating
- Excellent weather and water resistance - cured film resists degrading, chalking under harsh UV exposure
- Coverage: one coat applied over 180 Karna-Sil Epoxy Primer or specified 400 series base coat at the rate of 1.5 gallons per 100 sq. ft. (23 dry mils) up to 3 gallons per 100 sq. ft. (46 dry mils)
- 5-gallon, 50-gallon

Use directly on spray polyurethane foam roofing or over 180 Karna-Sil Epoxy Primer or applicable 400 series base coat over metal, asphalt, TPO, PVC, Hypalon and EPDM roofs

ASTM & Specifications	NSF	UL	FM	CRRC	Miami Dade
D-6694	•	•	•	•	•

Adhesives

Product

Approvals



16 Double Coverage Cement

- Cold-applied adhesive for asphalt cap sheets and roll roofing
- Use as a blind nailing/lap cement
- Coverage: 2-3 gallons per 100 sq. ft.
- 1-gallon, 5-gallon, 55-gallon

Use to adhere cap sheet roll roofing membranes

ASTM & Specifications
D-3019 Type III

UL	FM	CRRC	Miami Dade
•			•



66 Trowel Modified Bitumen Adhesive

- SBS cold-applied modified bitumen adhesive, eliminates the need for torches and kettles
- Tough, flexible, adhesive and cohesive bond
- Coverage: 1-2 gallons per 100 sq. ft.
- 5-gallon

Use to adhere SBS modified bitumen membranes, base and ply sheets as well as to adhere conventional BUR ply sheets or fully granulated cap sheets

ASTM & Specifications
D-3019 Type III

UL	FM	CRRC	Miami Dade
			•



81 Modified Bitumen Adhesive

- Specification-grade SBS cold-applied modified bitumen adhesive, eliminates need for torches and kettles
- Superior flexibility for strong adhesive and cohesive bonding
- Coverage: 1-2 gallons per 100 sq. ft.
- 5-gallon

Use to adhere SBS modified bitumen membranes, base and ply sheets as well as to adhere conventional BUR ply sheets or fully granulated cap sheets

ASTM & Specifications
D-3019 Type III

UL	FM	CRRC	Miami Dade
•	•		•

Primers

Product

Approvals



89 Sta-Tack Primer

Use as a primer for self-adhering membranes for roofing or waterproofing

- Water-based & quick drying
- Excellent coverage—1 gallon covers 500 sq. ft.
- Improves adhesion of membrane and performance
- 1-gallon, 5-gallon

ASTM & Specifications

UL FM CRRC Miami Dade
•



100 Non-Fibered Emulsion Primer

Use as a general-purpose primer on concrete, gypsum, masonry, brick, metal and asphalt surfaces over which waterproofing, dampproofing, roof coatings, membranes or other asphaltic products are to be applied

- Ideal for priming substrates prior to installing torch-applied modified membranes
- Water-based asphalt, safe to use, will not flash or burn in the liquid state
- Coverage: 1-2 gallons per 100 sq. ft.
- 5-gallon, 55-gallon, 275-gallon

ASTM & Specifications

D-1187 Type II, D-1227 Type III
Class I, SS-R-1781(AF)
MIL-R-3472A

UL FM CRRC Miami Dade
•



102 Asphalt Primer

Use on masonry, brick, concrete block, metal, gypsum and asphalt

- General purpose asphalt primer
- Provides a thick, firm base to promote better adhesion of asphalt adhesives and coatings
- Coverage: 0.5-1 gallon per 100 sq. ft.
- 5-gallon, 55-gallon

ASTM & Specifications

UL FM CRRC Miami Dade



108 Asphalt Primer (D-41)

Use on concrete, CMU block, gypsum, masonry, brick, metal and asphalt

- General purpose primer for roofing, dampproofing & waterproofing
- Revitalizes old asphalt roofing felts and surfaces prior to sealing and coating, quick drying
- Coverage: 0.5-1 gallon per 100 sq. ft.
- 14-oz. spray cans, 5-gallon, 55-gallon

ASTM & Specifications

D-41
SS-A-701
AASHTO M-116

UL FM CRRC Miami Dade
•



507 SPC Primer/Wash

Use to prepare EPDM roofing membranes for sealing and coating

- Cleans and prepares EPDM surfaces, a must for long-lasting coating applications
- Water-based, efficient cleaner - apply for 20 minutes then wash off
- Coverage: 0.20 gallon per 100 sq. ft. (500 sq. ft. per gallon)
- 1-gallon, 5-gallon

ASTM & Specifications

UL FM CRRC Miami Dade



702 K-Prep

Use on weathered Kynar coated metal roof panels

- Improves adhesion of coatings
- Improves blister resistance
- Coverage: 0.5 gallon per 100 sq. ft.
- 5-gallon, 55-gallon

ASTM & Specifications

UL FM CRRC Miami Dade

Dampproofing

Product

Approvals



83 Fibered Dampproofing

- Fibered, cutback asphalt dampproofing
- Cold-applied coating that forms a durable, flexible membrane
- Coverage: 4 gallons per 100 sq. ft.
- 5-gallon, 55-gallon

Use on masonry and concrete exterior surfaces below grade as well as general protective coating for wood, steel, brick

ASTM & Specifications
D-4479 Type I
SS-A-694D(AF)

UL	FM	CRRC	Miami Dade
•			•



86 Fibered Trowel Mastic

- Fibered, cutback asphalt dampproofing
- Ideal for making repairs to retaining walls, bridge abutments and steel panels before applying dampproof coating
- Coverage: 5-6 gallons per 100 sq. ft.
- 5-gallon

Use on masonry and concrete exterior surfaces below grade as well as or general repair on wood, steel, brick prior to applying dampproof coatings

ASTM & Specifications
D-4586 Type I
SS-A-153 Type 1(AF)

UL	FM	CRRC	Miami Dade
•			•



100 Non-Fibered Emulsion Dampproofing

- General purpose cavity wall dampproof coating
- Protects against dampness
- Coverage: 2-3 gallons per 100 sq. ft.
- 5-gallon, 55-gallon, 275-gallon

Use on concrete, masonry, metal and wood above or below grade as well as an adhesive for polystyrene insulation in cavity wall or on foundation wall

ASTM & Specifications
D-1187 Type II, D-1227 Type III
Class I, SS-R-1781(AF)
MIL-R-3472A

UL	FM	CRRC	Miami Dade
•			•



220 Fibered Emulsion Dampproofing

- Acts as vapor retarder in cavity wall construction
- Protects concrete, metal and wood above- or below- grade
- Coverage: 4-6 gallons per 100 sq. ft.
- 5-gallon, 55-gallon, 275-gallon

Use on concrete, masonry, metal and wood above or below grade as well as an adhesive for polystyrene insulation in cavity wall or on foundation wall

ASTM & Specifications
D-1187 Type I & II, D-1227
Type II Class I, SS-R-1781(AF)
MIL-R-3472A

UL	FM	CRRC	Miami Dade
•	•		•



920 Fibered Emulsion Mastic

- Trowel-applied version of 220
- Vapor retarder for above- or below-grade construction
- Coverage: 4-6 gallons per 100 sq. ft.
- 5-gallon, 55-gallon

Use on concrete, masonry, metal and wood above or below grade as well as an adhesive for polystyrene insulation in cavity wall or on foundation wall

ASTM & Specifications
D-1187 Type I, D-1227
Type II Class I, SS-R-1781(AF)
MIL-R-3472A

UL	FM	CRRC	Miami Dade
•			•

Waterproofing

Product

Approvals



88R Rubberized Waterproofing

- Spray-applied, rubberized below-grade waterproofing for masonry surfaces.
- Excellent upgrade to waterproofing for foundation walls
- Coverage: 4 gallons per 100 sq. ft.
- 5-gallon, 55-gallon

Use on masonry and concrete exterior surfaces below grade and interior cavity wall surfaces above grade as well as for general protective coating for wood, spray foam, steel brick and stone.

ASTM & Specifications
D-4479 Type I

UL FM CRRC Miami Dade



229 AR-Elastomeric

- Commercial-grade waterproofing protection
- Highly elastomeric, polymer modified asphalt that forms a seamless membrane
- Brush, trowel or spray grades
- 30 oz. caulk tubes, 1-gallon, 3-gallon, 5-gallon, 55-gallon

Use on masonry and concrete exterior surfaces below grade or above grade as well as for general protective coating for wood, spray foam, steel brick and stone

ASTM & Specifications
D-4479 Type I
D-4586 Type I

UL FM CRRC Miami Dade
• •

Resaturants

Product

Approvals



198 Asphalt Roof Resaturant

- Rejuvenates old gravel asphalt roofs
- Protects roof from the UV rays of the sun and keeps gravel in place
- Coverage: 7-8 gallons per 100 sq. ft. followed by new, clean gravel
- 5-gallon, 55-gallon

Use on asphalt BUR gravel roofs

ASTM & Specifications

UL FM CRRC Miami Dade
•

Reinforcing Fabrics & Tapes

Product

Approvals



31 Fiberglass Membrane

- Woven entirely of fiberglass yarn and resin coated for use with asphalt, coal tar coatings and acrylic sealants
- Ideal for use with cold applied cements and coatings
- Designed to reinforce roofing and waterproofing repairs and applications as well as air barrier sealants
- Widths of 4", 6", 9", 12", 18", 36" x 150' rolls

Use to reinforce mastics, sealants and coatings

ASTM & Specifications
D-1668 Type III
HH-C466B

UL FM CRRC Miami Dade



34 Asphalt Cotton Fabric

- Asphalt coated for increased bond of cements & coatings
- Lightweight, unrolls easily
- Open mesh allows cements & coatings to form a strong mechanical bond
- Widths of 4", 6", 9", 12", 18", 36" x 150' rolls

Use to reinforce asphalt flashing cements, mastics and coatings

ASTM & Specifications

UL FM CRRC Miami Dade



3036 Poly-Mat

- Firm finish, stitch-bonded polyester
- High tensile strength for increased toughness
- Lightweight and easy to handle, won't rot or decay
- Widths of 4", 6", 12", 40" x 180' rolls

Use to reinforce coatings and sealants over smooth surfaces

ASTM & Specifications

UL FM CRRC Miami Dade



5540 Resat-Mat

- Soft finish, stitch-bonded polyester
- Conforms to shape of roof, lightweight & easy to handle
- Excellent tensile strength & high breaking elongation
- Widths of 4", 6" x 300' and 40" x 324' rolls

Use to reinforce coatings and sealants over smooth or irregular surfaces

ASTM & Specifications

UL FM CRRC Miami Dade



560 Karna-Bond

- Self-adhering repair tapes with highly adhesive micro-sealant rubber
- Seals and waterproofs
- Available in White, Black, Fleece
- Widths of 4", 6", 12" x 50' rolls length depending on model

Use to seal seams & flashings and for making repairs on EPDM, Hypalon, PVC, TPO, Metal and over a number of other building materials

ASTM & Specifications

UL FM CRRC Miami Dade

Miscellaneous

Product

Approvals



45 Sky Kote

Use to seal fiberglass & polycarbonate skylight panels and glass transit windows

- Clear, acrylic coating for sealing hairline cracks to stop water infiltration
- Dries clear to allow light through
- Coverage: 1-2 gallons per 100 sq. ft.
- 1-gallon, 5-gallon

ASTM & Specifications

UL FM CRRC Miami Dade



105 Tac-Kote

Use to prepare surfaces for subsequent asphalt-based paving application

- Primer/adhesive for under asphalt-based roadways
- Binds and seals dusty surfaces for subsequent toppings
- Coverage: 1-1.5 gallons per 100 sq. ft.
- 5-gallon, 55-gallon

ASTM & Specifications

UL FM CRRC Miami Dade



230 2% Neo Asphalt (Trowel Grade)

Use to adhere paving blocks and pressed asphalt bricks to concrete or macadam (blacktop) surfaces

- Cold-applied, rubberized asphalt adhesive eliminates shifting and buckling of pavers
- Installs over new/existing concrete/macadam
- Coverage: 1.5-2 gallons per 100 sq. ft.
- 5-gallon

ASTM & Specifications

UL FM CRRC Miami Dade



237 2% Neo Asphalt (Brush Grade)

Use to adhere paving blocks and pressed asphalt bricks to concrete or macadam (blacktop) surfaces

- Cold-applied, rubberized asphalt adhesive eliminates shifting and buckling of pavers
- Installs over new/existing concrete/macadam
- Coverage: 1.5-2 gallons per 100 sq. ft.
- 5-gallon

ASTM & Specifications

UL FM CRRC Miami Dade



709 Karna-Klean

Use as a paint, asphalt & tar remover for cleaning

- Concentrated citric-based solvent with pleasant orange scent
- Removes paint, tar and asphalt
- Environmentally friendly non-toxic & petroleum free
- 1-liter size spray bottles

ASTM & Specifications

UL FM CRRC Miami Dade



799 Wash-N-Prep Roof Cleaner

Use to clean roof surfaces

- Concentrated, pro-grade strength cleaner for preparing roof surfaces for repair and coating
- Use on asphalt, metal, concrete, spray foam, TPO and PVC roofs as well as for general cleaning
- For general cleaning 1 qt. cleans 1,600 sq. ft.
- 1-quart bottles

ASTM & Specifications

UL FM CRRC Miami Dade

Caulks

Product

Approvals



19	Flashing Cement Caulk	Use for general repair of leaks in shingles, concrete, metal and asphalt roofs, flashings on walls, chimneys, flues, skylight flashings, downspouts and cornices								
<ul style="list-style-type: none"> Asphalt repair cement with smooth consistency for easy use Use for repairs on dry surfaces and as a shingle tab adhesive Coverage: 25 lineal feet per tube per 1/4" by 1/4" bead 10.1 oz. caulk tubes 	ASTM & Specifications D-4586 Type I Class I SS-C-153 Type I(AF)	<table border="0"> <tr> <td style="text-align: center;">UL</td> <td style="text-align: center;">FM</td> <td style="text-align: center;">CRRC</td> <td style="text-align: center;">Miami Dade</td> </tr> <tr> <td style="text-align: center;">•</td> <td></td> <td></td> <td style="text-align: center;">•</td> </tr> </table>	UL	FM	CRRC	Miami Dade	•			•
UL	FM	CRRC	Miami Dade							
•			•							



19	Ultra Flashing Cement Caulk	Use for general repair of leaks in shingles, concrete, metal and asphalt roofs, flashings on walls, chimneys, flues, skylight flashings, downspouts and cornices								
<ul style="list-style-type: none"> Elastomeric, rubberized asphalt repair cement with smooth consistency for easy use Use for repairs on wet or dry surfaces and as a shingle tab adhesive Coverage: 25 lineal feet per tube per 1/4" by 1/4" bead 10.1 oz. caulk tubes 	ASTM & Specifications D-4586 Type I Class I & Class II D-3409 SS-C-153 Type I(AF)	<table border="0"> <tr> <td style="text-align: center;">UL</td> <td style="text-align: center;">FM</td> <td style="text-align: center;">CRRC</td> <td style="text-align: center;">Miami Dade</td> </tr> <tr> <td style="text-align: center;">•</td> <td></td> <td></td> <td style="text-align: center;">•</td> </tr> </table>	UL	FM	CRRC	Miami Dade	•			•
UL	FM	CRRC	Miami Dade							
•			•							



160.1	Amphibicaulk	Use for general repair of leaks in shingles, concrete, metal and asphalt roofs, flashings on walls, chimneys, flues, skylight flashings, downspouts and cornices								
<ul style="list-style-type: none"> Asphalt repair cement for use on wet or dry surfaces, emergency repair use Use for repairs and as a shingle tab adhesive Coverage: 25 lineal feet per tube per 1/4" by 1/4" bead 10.1 oz. caulk tubes 	ASTM & Specifications D-4586 Type I Class I & Class II D-3409 SS-C-153 Type I(AF)	<table border="0"> <tr> <td style="text-align: center;">UL</td> <td style="text-align: center;">FM</td> <td style="text-align: center;">CRRC</td> <td style="text-align: center;">Miami Dade</td> </tr> <tr> <td></td> <td></td> <td></td> <td style="text-align: center;">•</td> </tr> </table>	UL	FM	CRRC	Miami Dade				•
UL	FM	CRRC	Miami Dade							
			•							



502MS	Karna-Flex Caulk	Use on metal, TPO, PVC, Hypalon, EPDM, concrete and spray foam roof surfaces								
<ul style="list-style-type: none"> White, SEBS thermoplastic rubber sealant Seal metal screws and gutters and problem areas even in ponding areas Coverage: 75 lineal feet per tube per 1/4" by 1/4" bead 30 oz. caulk tubes 	ASTM & Specifications	<table border="0"> <tr> <td style="text-align: center;">UL</td> <td style="text-align: center;">FM</td> <td style="text-align: center;">CRRC</td> <td style="text-align: center;">Miami Dade</td> </tr> <tr> <td></td> <td style="text-align: center;">•</td> <td></td> <td style="text-align: center;">•</td> </tr> </table>	UL	FM	CRRC	Miami Dade		•		•
UL	FM	CRRC	Miami Dade							
	•		•							



229	AR-Elastocaulk	Use on asphalt BUR, APP & SBS membrane roofs, concrete, metal, spray urethane foam roofs, masonry, stone and wood								
<ul style="list-style-type: none"> Black, SBS rubberized asphaltic sealant Seal metal screws, gutters, pitch pans, gravel stops and problem areas even in ponding areas Coverage: 75 lineal feet per tube per 1/4" by 1/4" bead 30 oz. caulk tubes 	ASTM & Specifications D-4586 Type I Class I D-4479 Type I	<table border="0"> <tr> <td style="text-align: center;">UL</td> <td style="text-align: center;">FM</td> <td style="text-align: center;">CRRC</td> <td style="text-align: center;">Miami Dade</td> </tr> <tr> <td style="text-align: center;">•</td> <td style="text-align: center;">•</td> <td></td> <td style="text-align: center;">•</td> </tr> </table>	UL	FM	CRRC	Miami Dade	•	•		•
UL	FM	CRRC	Miami Dade							
•	•		•							

Application Temperature Recommendations

PRODUCT TYPE	PRODUCT EXAMPLES	STORAGE TEMPERATURE (Store indoors in dry environment)	APPLICATION TEMPERATURES (Includes the substrate, product and ambient temperature*)	SERVICE/PERFORMANCE TEMPERATURES
Acrylics (Except 405 Bond-N-Shield and 529 Renu-White)	400 Series Base Coats 500 Series Finish Coats 505MS Karna-Flex WB	50°F to 90°F	40°F to 120°F	-15°F to 180°F
Acrylic - Exceptions	529 Renu-White 405 Bond-N-Shield	50°F to 90°F	40°F to 120°F	15°F to 180°F
Silicone	670HS Karna-Sil	50°F to 90°F	50°F to 120°F	-15°F to 185°F
SEBS & SBS	502 RC-W Elasto-Kote 502MS Karna-Flex 229AR Elastomeric	50°F to 90°F	40°F to 140°F	-40°F to 180°F
Aluminum	97 Fibered Aluminum 169 Non-Fibered AL 298 Alumin-R	50°F to 90°F	50°F to 120°F	15°F to 180°F (298 Alumin-R -40°F to 180°F)
Asphalt Cements, Coatings, Adhesives & Primers	19 Flashing Cement 19 Ultra Rub. Flashing Cement 71 Fib. Asphalt Coating 108 Asphalt Primer 66 Mod. Bit. Adhesive 83 Fibered Dampproofing 86 Fibered Trowel Mastic	50°F to 90°F	40°F to 120°F	15°F to 180°F
Asphalt Emulsions	100 Non-Fibered / 100 Primer 220 Fibered 920 Fibered Emulsion Mastic	50°F to 90°F	40°F to 120°F	15°F to 180°F
Epoxy Primer	180	50°F to 90°F	40°F to 120°F	-15°F to 180°F
Water-Based Polymer Modified Primer	89 Sta-Tak	50°F to 90°F	30°F to 120°F	15°F to 180°F

NOTE: Application at temperatures lower than 40° F will become difficult due to the increase in viscosity that occurs when the product's temperature is lowered. Application of products at or below freezing temperatures could result in adhesive failure, unless special precautions are taken to ensure that the surface is free of moisture or ice crystals.

* Apply all products at ambient air temperatures 5°F or higher above the dew point unless applicable for use over wet surfaces.

INDEX

Roofing Repair Mastics & Cements.	2-3	Dampproofing	10
Asphalt Roof Coatings	4	Waterproofing	11
Acrylic Base Coats	5	Resaturants	11
Reflective Roof Coatings - Aluminum	6	Reinforcing Fabrics & Tapes.	12
Reflective Roof Coatings - White.	7	Miscellaneous.	13
Adhesives	8	Caulks.	14
Primers	9		

Spray Tip Information & Recommendations

Product	Tip Size Range	Working Pressure	Hose ID Tested*	Recommended Overspray During Application
16	.049-.053	4000	1/2"	
27	.039-.043	1500	1/2"	20%
28	.023-.027	1500	1/2"	
71	.049-.053	4000	1/2"	
83 Spray	.049-.053	4000	1/2"	
97	.039-.043	1500	1/2"	20%
98	.039-.043	1500	1/2"	20%
108	.029-.033	2500	1/2"	
112	.031-.035	2500	1/2"	
169	.023-.027	1500	1/2"	
198	.049-.053	4000	1/2"	
220	.045-.049	1800	1/2"	
229 Spray	.039-.043	4000	1/2"	30%
298	.043-.047	1700	1/2"	10%
404	.023-.027	1800	1/2"	30%
405	.023-.027	1800	1/2"	30%
406	.023-.027	1800	1/2"	30%
501	.035-.045	1800	1/2"	30%
502 ES	.029-.033	3300	1/2"	
502	.029-.033	2300	1/2"	
529	.035-.045	1800	1/2"	30%
670HS	.030-.035	3500	3/4"	

*Hose length used for testing was 81'.

Products applied using a Graco GH 833 Airless Sprayer and 1/2" diameter hose, unless otherwise noted. Contact spray equipment manufacturer for more complete information.

Better to increase tip size first before increasing pressure to eliminate overspray.



THE SEAL OF QUALITY



330 Central Avenue
Clark, NJ 07066
(800) 526-4236
info@karnakcorp.com
karnakcorp.com

Manufacturing/Warehouse Locations:
Clark, NJ
Ft. Lauderdale, FL
Broadview, IL
Kingman, AZ

Distribution Warehouse Locations:
Renton, WA
Rancho Cucamonga, CA
Dallas, TX



At time of manufacture, all containers were filled at the designated quantity. However, due to the reduction in volume that occurs after cooling, settling and other environmental factors, the actual volume may be less. Please see front panel of each container for content information.