

## Product Data

# Driwall™ Membrane 60 mil

Self-Adhesive Waterproofing Membrane

### Description

Driwall™ Membrane 60 mil thick (1.5 mm) self-adhering flashing and waterproofing membrane.

It provides an self-adhered waterproofing membrane in above and below grade applications such as concrete foundation walls, plaza decks, balconies, tunnels and breezeways.

#### Storage:

Protect from weather. Store in enclosed area, which is not subject to high heat (120°F). Store rolls on end, and on original pallets.

Not intended for permanent exposure to the elements. Cover as soon as possible. Do not use in contact with PVC or vinyl products.

### Applications

- ✓ Concrete foundation walls
- ✓ Plaza decks
- ✓ Tunnels
- ✓ Parking decks
- ✓ Foundation waterproofing
- ✓ Balconies

### Features and Benefits

Impermeable to air, moisture vapor, and water

Excellent self adhesion to plywood, oriented strand board (OSB), concrete, metal, and like materials

Highly resistant to punctures and tears

**60 mil (1.5 MM) CORE**

## Properties

Description	Measurement
Flame Spread	Self-Extinguishing
Color	White
Thickness	60 mil 1.5 mm
Tensile Strength Membrane (ASTM D412)	390 psi
Tensile Strength Film (ASTM D882)	6,242 psi
Puncture Resistance (ASTM E154)	> 60 lbs.
Water Vapor Permeation (ASTM E96)	0.02
Moisture Absorption (ASTM D570-81)	0.2%
Low Temperature Flexibility (ASTM D1970)	Unaffected at -45°F
Hydrostatic Head (ASTM D5385)	Pass 231 ft.

## Packaging

Product Name	Product Part Number	Rolls per Box	Coverage per Box	Weight per Roll lb	Weight per Roll kg	Length per Roll ft	Length per Roll m	Roll Width in	Roll Size
Driwall™ Membrane	01-X-0147	4	200 sq. ft.	65	29.48	67	20.42	9	9 in. x 67 ft.
Driwall™ Membrane	01-X-0045	3	200 sq. ft.	65	29.48	67	20.42	12	12 in. x 67 ft.
Driwall™ Membrane	01-X-0046	1	200 sq. ft.	65	29.48	67	20.42	36	36 in. x 67 ft.

See installation instructions for methods and procedures.

LIMITED WARRANTY: Keene Building Products, Inc. warrants to the initial purchaser only that the goods sold hereunder will be free from defects in material and workmanship and, except as otherwise set forth herein, will conform to the specifications provided. If any failure to meet this warranty appears within one year from the date of shipment of the goods, on the condition that Keene Building Products, Inc. will correct any such failure by either replacing or repairing any defective goods, at Keene Building Products, Inc.'s option.

The preceding paragraph sets forth the exclusive remedy for all claims based on failure of or defect in the goods sold hereunder, whether such failure or defect arises before or during the warranty period and whether a claim, however instituted, is based on contract, indemnity, warranty, tort (including negligence), strict liability or otherwise. The forgoing warranty is exclusive and is in lieu of all other warranties whether written, oral, implied or statutory.



Info@KeeneBuilding.com 877 | 514 | 5336  
KeeneBuilding.com P 440 | 605 | 1020  
F 440 | 605 | 1120