

## Product Data

# Driwall™ Membrane Mastic

A Rubberized Asphalt-based Cement

### Description

Driwall™ Membrane Mastic is an asbestos free rubberized asphalt-based cement. Formulated to meet Federal specification SS-C-153C and ASTM D4586, Driwall Membrane Mastic can be used under wet or dry conditions, and may be used on horizontal or vertical surfaces. Engineered to have outstanding performance with all Keene Driwall Membrane products, Driwall Membrane Mastic will also work with most asphalt based waterproofing membranes.

### Packaging

5 gallon pail

### Features and Benefits

- Fiber reinforced (asbestos free)
- Vertical or horizontal surfaces
- Wet or dry conditions
- Usable over a wide range of substrates

### Application

- Suitable for any Driwall Membrane application
- Usable in both wet or dry conditions
- Acceptable for vertical or horizontal surfaces
- Appropriate for use over a wide variety of substrates

Ensure all surfaces are dry and free of any oil or grease. All surfaces must be clean and free of dust, dirt and any foreign material. Flashing – apply  $\frac{1}{8}$ " to  $\frac{1}{2}$ " thick around and over joints of flashing. Trowel down to a smooth, feathered edge. Small Holes (under 1") – trowel into, over and around hole about  $\frac{3}{8}$ " to  $\frac{1}{2}$ " thick, feather to edge. Large Holes – apply  $\frac{1}{4}$ " thick layer into and around the hole. Imbed a piece of membrane approximately 4" in diameter. Apply a layer of mastic over the patch feathering the edge. Wet conditions – work back and for the over surface to ensure maximum bond.

### General Guidelines

- KEEP FROM FREEZING
- KEEP AWAY FROM OPEN FLAME AND ANY IGNITION SOURCE
- Close container after each use
- Use appropriate protective clothing and eye protection
- Avoid prolonged exposure to skin, use in adequately ventilated area. Prolonged exposure may lead to dizziness or headache. NIOSH/MESA respirator.

\*Do not use with coal tar based products

\*May not be compatible with some one-ply roofing systems – check with manufacturer

\*VOC content does not exceed 300g/l – VOS under 2.5lbs/gal

LIMITED WARRANTY: Keene Building Products, Inc. warrants to the initial purchaser only that the goods sold hereunder will be free from defects in material and workmanship and, except as otherwise set forth herein, will conform to the specifications provided. If any failure to meet this warranty appears within one year from the date of shipment of the goods, on the condition that Keene Building Products, Inc. will correct any such failure by either replacing or repairing any defective goods, at Keene Building Products, Inc.'s option.

The preceding paragraph sets forth the exclusive remedy for all claims based on failure of or defect in the goods sold hereunder, whether such failure or defect arises before or during the warranty period and whether a claim, however instituted, is based on contract, indemnity, warranty, tort (including negligence), strict liability or otherwise. The forgoing warranty is exclusive and is in lieu of all other warranties whether written, oral, implied or statutory.