

GreenGuard®

Applications

LG XPS insulation board for continuous insulation behind siding




- Exterior continuous insulation (CI) helps block energy loss
- Creates level surface for new siding
- R-Value of 5.0 per inch of thickness
- Highly moisture resistant
- Maintains integrity
- Blowing agent blend of GWP of less than 50

XPS-LG insulation board for continuous insulation behind siding




Wood is not a good insulator

Energy loss and temperature transfer from outside to inside is greater through wood framing than through wall cavity insulation.



Extruded Polystyrene is a good insulator



Continuous Insulation (CI) with a layer of XPS, reduces energy loss and temperature transfer through both wood framing and wall cavity insulation.

Sealing Seams

Use Kingspan GreenGuard® Butyl Flashing for an effective seal at seams.

Product Data		
Property	Test Method	Result
Nominal Thickness (in)		1/2 3/4 1

Thermal Resistance, R-value1 (°F·ft²·hr/Btu per in thick)	ASTM C578 (@75°Mean Temperature)	2.8 3.8 5.0
--	-------------------------------------	-------------

Water Absorption, Max. (% by volume)	ASTM C272	0.3 0.3 0.3
---	-----------	-------------

1 R-values listed are in accordance with the testing requirements of ASTM C578 and are based on 1" aged product at 75oF mean temperature.

Size Availability				
Nominal Thickness (in)		1/2	3/4	1
2 x 8	Shiplap Edge	●	●	●
2 x 8	Square Edge			●
4 x 8	Shiplap Edge			●
4 x 8	Square Edge	●	●	●

Description

Kingspan GreenGuard® XPS-LG Insulation Board comprises closed-cell extruded polystyrene (XPS) with a minimum compressive strength of 25 psi. It has an R-value of 5.0 per inch of thickness. It is characterized by low water absorption and retention of R-value over time.

Compliance

Intertek CCRR-1021;
Intertek CCRR-1022 (.56", .75");
CA BEARHFTI Lic. No. TB1334;
Florida Product Approval;
CCMC 12722-L;
Miami-Dade County, FL;
UL Listings - R11183.

To ensure you are viewing the most recent and accurate product information, please visit this link <https://www.kingspan.com/us/en/products/rigid-insulation/insulation-board/>

For more information on specific building product recommendations and installation guidelines, contact your Kingspan Insulation LLC representative.

Kingspan Insulation LLC believes the information and recommendations herein to be accurate and reliable. However, since use conditions are not within its control, Kingspan Insulation LLC does not guarantee results from use of such products or other information herein and disclaims all liability from any resulting damage or loss. No warranty, express or implied, is given as to the merchantability, fitness for particular purpose, or otherwise with respect to the products referred to.

Kingspan Insulation LLC
2100 Riveredge Parkway | Suite 175
Atlanta | Georgia 30328

T: +1 (800) 241 4402 F: +1 (678) 589 7325
E: info@kingspaninsulation.us
www.kingspaninsulation.us
© Kingspan, the G Device and the Lion Device are Registered Trademarks of the Kingspan Group plc in the US, Canada and other countries. All rights reserved.® GreenGuard is a Registered Trademark of the Kingspan Group plc in the US. All rights reserved.

