

Revision date 07/04/2025
 Current revision 3.1
 Supersedes version of 30/05/2024



SAFETY DATA SHEET

Fiberglass with ECOSE® Technology

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

SECTION 1: Identification

Product identifier

Product name	Fiberglass with ECOSE® Technology
Product number	KI_DP_101
Other means of identification	None.
Trade name	EcoBatt® (Unfaced and Faced) Building Insulation, EcoBatt® QuietTherm® (Unfaced and Faced) Building Insulation, Acoustical/IB Board, Acoustical Smooth Board, Air Duct Board (Atmosphere™), KB Blanket, Black Acoustical Board, Black Diffuser Board, Condensation Control Blanket, Duct Liner (Atmosphere™), Duct Wrap Faced and Unfaced (Atmosphere™), Earthwool® 1000° Pipe Insulation*, ET Batt*, ET HD Blanket, ET Blanket*, ET Board*, ET Panel*, Equipment Liner M, Everbilt (Unfaced and Faced) Building Insulation, Fabrication Board*, Flexible Duct Material, Guardian (Unfaced and Faced) Building Insulation, Hullboard*, Earthwool Insulation Board (Faced and Unfaced)*, KF_110*, KFR/ET Range Insulation*, KN Series*, Manufactured Housing Duct Board, Manufactured Housing Insulation, Metal Building Insulation, Metal Building Cavity Insulation, Metal Building Filler Insulation, Earthwool Pipe & Tank Insulation*, Atmosphere Rigid Plenum Liner, Sill Sealer, Wall & Ceiling Liner M, Guardian by Knauf Insulation, Inner Safe™ Batt, EcoBatt® IRD, EcoRoll® Insulation, Basement Blanket Insulation, Performance + Duct Wrap (faced and unfaced), Performance + Duct Liner, Performance + Air Duct Board, Performance + Rigid Plenum Liner, Performance + Black Diffuser Board, Performance+ EcoBatt Insulation (Unfaced and Faced), Performance+ EcoRoll Insulation (Unfaced and Faced), Performance+ KwikFlex Pipe and Tank Insulation, Performance+ Earthwool 1000 Pipe Insulation, Performance+ Earthwool Pipe and Tank Insulation

Recommended use of the chemical and restrictions on use

Identified Uses Thermal and/or acoustic insulation for use in :
 technical applications, industrial applications and in building construction.

Uses advised against None known.

Details of the supplier of the safety data sheet

Supplier	Knauf Insulation Inc. One Knauf Drive Shelbyville IN 46176-1496 Tel: 800 825 4434
	www.knaufnorthamerica.com sds@knaufinsulation.com
Region	United States, Central & South America
Emergency telephone number	
Emergency phone number	24hrs: Chemtrec Tel: 800 424 9300

SECTION 2: Hazards identification

Classification of the substance or mixture

OSHA Regulatory Status	This product is regulated as a nuisance dust under OSHA criteria.
Physical hazards	Not classified
Health hazards	Not classified
Environmental hazards	Not classified

Label elements

Hazard statements	Not classified
Contains	None.
Hazard pictograms	None.
Signal word	None.
Precautionary statements	None.
Supplemental label information	None.

The following sentences and pictograms apply to this product:



<http://www.knaufinsulation.com/comfort-and-handling>

Other hazards

Physical hazards	None.
Health hazards	Mechanical irritation of the skin, eyes and upper respiratory system.
Environmental hazards	None.
Most important symptoms/effects	Contact with skin, eyes and upper respiratory system may cause mechanical irritation.

Biosoluble Fiberglass is classified as a nuisance dust by OSHA.

Persistent Bioaccumulative Toxic Not relevant

*** Heat-up precautions** For product with binder: When heated for the first time above 400°F, release of binder components and binder decomposition products can occur which, in high concentrations, may irritate eyes and the respiratory system.

see section(s) : 8 & 10

SECTION 3: Composition/information on ingredients

Mixtures

Biosoluble Fiberglass	(1)(2)	82 - 100%
CAS number	—	
Classification	Not classified	
Ingredient comments	<p>(1) 650-016-00-2 - Man made vitreous (silicate) fibres with random orientation with alkaline oxide and alkali earth oxide ($\text{Na}_2\text{O}+\text{K}_2\text{O}+\text{CaO}+\text{MgO}+\text{BaO}$) content greater than 18% by weight meeting the requirements of Note Q of regulation n° 1272/2008 and therefore not classified as carcinogenic.</p> <p>(2) All Knauf Insulation products covered by this SDS are independently certified by EUCEB to be manufactured using biosoluble glass formulations and thus exempt from labeling under NTP or California Prop 65 requirements.</p>	

Thermo set, inert polymer bonding agent derived from plant starches**0 - 18%**

CAS number

—

Classification**Not classified**

Full text of R-phrases: see section 16

Specific chemical identity and/or exact percent concentration is withheld as trade secret.

SECTION 4: First aid measures**Description of first aid measures****General information**

Show this Safety Data Sheet to the medical professional in attendance. If symptoms occur, follow first aid measures as appropriate.

Note to physician :

No specific measures.

Inhalation

Remove from exposure. Rinse the throat and clear dust from airways.

Ingestion

Wash out mouth and drink plenty of water if accidentally ingested.

Skin contact

If mechanical irritation occurs, remove contaminated clothing and wash skin gently with cold water and soap.

Eye contact

Rinse abundantly with water for at least 15 minutes.

Most important symptoms and effects, both acute and delayed**General information**

Mechanical irritation of the skin, eyes and upper respiratory system.

Biosoluble Fiberglass is classified as a nuisance dust by OSHA.

Indication of any immediate medical attention and special treatment needed**General information**

If any adverse reaction or discomfort continues from any of the above exposures, seek professional medical advice.

Specific treatments

No specific measures.

SECTION 5: Fire-fighting measures**Extinguishing media****Suitable extinguishing media**Water, foam, carbon dioxide (CO₂), and dry powder.**Unsuitable extinguishing media**

None.

Special hazards arising from the substance or mixture**General information**

Products do not pose a fire hazard in use; however, some packaging materials or facings may be combustible. Products of combustion from product and packaging – carbon dioxide, carbon monoxide and some trace gases such as ammonia, nitrogen oxides and volatile organic substances.

Advice for firefighters**General information**

In large fires in poorly ventilated areas involving packaging materials respiratory protection / breathing apparatus may be required.

SECTION 6: Accidental release measures**Personal precautions, protective equipment and emergency procedures****Personal precautions**

Minimise direct contact with skin in order to prevent mechanical itching. In dusty environments, use suitable respiratory protection such as 3M 8210, N95 or equivalent. Use glasses or goggles when working with fiber insulation above shoulder height or in dusty environments. Where possible, use natural ventilation during installation in order to minimise dust levels.

After contact with the product, rinse skin in cold water to reduce potential effects of mechanical itching. Dispose of surplus product in accordance with local regulations.

Use personal protection recommended in Section 8 of the SDS.

Environmental precautions

Environmental precautions Not relevant

Methods and material for containment and cleaning up

Methods for cleaning up Vacuum cleaner or dampen down with water spray prior to brushing up.

Reference to other sections For personal protection, see section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

Precautions for safe handling

Usage precautions Assure proper respiratory protection if potential dust exposure exceeds occupational exposure limits.

Conditions for safe storage, including any incompatibilities

Storage precautions To ensure optimum product performance; when packaging is removed or opened; products should be stored inside or covered to protect them from ingress of rain water or snow. Storage arrangements should ensure stability of stacked products and use on a first in first out basis (FIFO) is recommended.

Specific end use(s)

Specific end use(s) Thermal and/or acoustic insulation for use in :technical applications, industrial applications and in building construction.

SECTION 8: Exposure controls/personal protection

Control parameters

Occupational exposure limits Biosoluble Fiberglass

Long-term exposure limit (8-hour TWA): ACGIH, (Notes: (A3)) 1 f/cc Glass wool fibers
Long-term exposure limit (8-hour TWA): NIOSH 5 mg/m³ Mineral wool fiber, total particulate
Long-term exposure limit (8-hour TWA): OSHA 5 mg/m³ Particulates not otherwise regulated (PNOR), respirable fraction
Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ Particulates not otherwise regulated (PNOR), total dust

ACGIH = American Conference of Governmental Industrial Hygienists.

OSHA = Occupational Safety and Health Administration.

NIOSH = The National Institute for Occupational Safety and Health.

Exposure limit values have been established by many authorities. Check on limit values that apply in your local situation

Ingredient comments	(A3) - Fibers longer than 5 µm; diameter less than 3 µm; aspect ratio greater than 5:1 as determined by the membrane filter method at 400-450X magnification (4-mm objective) phase contrast illumination.
	Biosoluble Fiberglass – see section(s) : 3.
Exposure controls/personal protection	
Appropriate engineering controls	Maintain sufficient mechanical or natural ventilation to assure fiber concentrations remain below PEL/TLV. Use local exhaust if necessary. Power equipment should be equipped with properly designed dust collection devices.
Eye/face protection	Use glasses or goggles when working with fiberglass insulation above shoulder height or in dusty environments.
Other skin and body protection	Minimize direct contact with skin in order to prevent mechanical itching.
Hygiene measures	After contact with the product, rinse skin in cold water to reduce potential effects of mechanical itching.
Respiratory protection	In dusty environments, use suitable respiratory protection.
Environmental exposure controls	Not relevant
* Heat-up precautions	For product with binder: When heated for the first time above 400°F, release of binder components and binder decomposition products can occur which, in high concentrations, may irritate eyes and the respiratory system. The duration of release is dependant upon the thickness of the insulation, binder content and the temperature applied. Provide adequate ventilation. In confined spaces or where ventilation is not possible, occupants should wear appropriate self-contained breathing apparatus.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Solid. Rolls. Panel. Loose fibre.
Color	Brown
Odor	Not relevant
Odor threshold	No data available
pH	Not relevant
Melting point	Not relevant
Initial boiling point and range	Not relevant
Flash point	Not relevant
Evaporation rate	Not relevant
Flammability (solid, gas)	Not relevant
Upper/lower flammability or explosive limits	Not relevant
Vapor pressure	Not relevant
Vapour density	Not relevant

Relative density	7 - 96 kg/m ³
Solubility	Generally chemically inert and slightly soluble in water.
Auto-ignition temperature	Not relevant
Decomposition temperature	Not relevant
Viscosity	Not relevant
Explosive properties	Not relevant
Oxidizing properties	Not relevant

Other information

Devitrification temperature	Not relevant
Softening temperature	Not relevant
Nominal diameter of fibres	3 - 8 µm
Length weight geometric mean diameter less 2 standard errors	< 6 µm
Orientation of fibres	Random

SECTION 10: Stability and reactivity

Reactivity	None.
Chemical stability	Binder will decompose above 200°C (400°F).
Possibility of hazardous reactions	None under normal use
Conditions to avoid	None under normal use
Incompatible materials	Hydrofluoric acid will react with and dissolve glass.

Hazardous decomposition products

None under normal use

For product with binder: When heated for the first time above 400°F, release of binder components and binder decomposition products can occur which, in high concentrations, may irritate eyes and the respiratory system. The duration of release is dependant upon the thickness of the insulation, binder content and the temperature applied. Provide adequate ventilation. In confined spaces or where ventilation is not possible, occupants should wear appropriate self-contained breathing apparatus.

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity (oral) - LD50 oral	No data were identified for the product as a whole. Data are for constituents: Biosoluble Fiberglass - Not applicable. Thermo set, inert polymer bonding agent derived from plant starches. - Not applicable.
Acute toxicity (dermal) - LD50 dermal	No data were identified for the product as a whole. Data are for constituents: Biosoluble Fiberglass - Not applicable. Thermo set, inert polymer bonding agent derived from plant starches. - Not applicable.

Acute toxicity (inhalation) - LC50 Inhalation	No data were identified for the product as a whole. Data are for constituents: Biosoluble Fiberglass - Not applicable. Thermo set, inert polymer bonding agent derived from plant starches. - Not applicable.
Skin corrosion/irritation	May cause mechanical irritation to skin
Serious eye damage/irritation	May cause mechanical irritation to eyes.
Respiratory sensitization	No data were identified for this product or its constituents.
Skin sensitization	No data were identified for this product or its constituents.
Germ cell mutagenicity	No data were identified for this product or its constituents.
Carcinogenicity	SWA / WES requirements exempt biopersistent fibres as defined by notes. Results from a biopersistence test in line with the notes has shown that fibres in this product longer than 20 µm have a weighted half-life less than 40 days and meet the "Nota Q" requirements, thus this product is not classified as a carcinogen. None of the components of this product Reproductive toxicity are listed as a carcinogen.
Reproductive toxicity	
Reproductive toxicity - Fertility	No data were identified for this product or its constituents.
Developmental toxicity	No data were identified for this product or its constituents.
Specific target organ toxicity - single exposure	No data were identified for this product or its constituents.
Specific target organ toxicity - repeated exposure	No data were identified for this product or its constituents.
Aspiration hazard	Not relevant
Inhalation	Mechanical irritation to upper respiratory tract.
Ingestion	Non-hazardous when ingested.
Skin contact	Mechanical irritation to skin.
Eye contact	Mechanical irritation to eyes.
Most important symptoms/effects	Contact with skin, eyes and upper respiratory system may cause mechanical irritation. Biosoluble Fiberglass is classified as a nuisance dust by OSHA.

SECTION 12: Ecological information

General toxicity

This product is not ecotoxic to air, water or soil, by composition.

Persistence and degradability

Inert inorganic product with Thermo set, inert polymer bonding agent derived from plant starches; 0 - 18%

Bioaccumulative potential

Bioaccumulative potential No bioaccumulation potential

partition coefficient Not relevant

Mobility in soil Not considered mobile. Less than 1% leachable organic carbon if landfilled.

Results of PBT and vPvB assessment

Not relevant

Endocrine disrupting properties

Not relevant

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	Dispose of in accordance with regulations and procedures in force in country of use or disposal. Empty containers should be taken to an approved waste handling site for recycling or disposal.
Disposal methods	This product is not regulated under RCRA Hazardous Waste Regulations. May be disposed in landfill. If unsure, contact the local office of the USEPA, your local public health department or the local landfill regulators.

SECTION 14: Transport information

General information	The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, DOT).
UN number	Not applicable
UN proper shipping name	Not applicable
Transport hazard class(es)	No transport warning sign required.
Packing group	Not applicable
Environmental hazards	
Environmentally hazardous substance/marine pollutant	None.
Special precautions for user	Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

Regulatory status	This product is regulated as a nuisance dust under OSHA criteria. In accordance with industry practice and voluntary commitments, Knauf Insulation has decided to continue to provide its customers with the appropriate information for the purpose of assuring safe handling and use of mineral wool throughout the product life.
--------------------------	--

US Federal regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities : Not regulated.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA) : Not regulated.

SARA 313 Emission Reporting : Not listed.

SARA Section 311/312 Hazard Classes : Not regulated.

US State regulations

California Proposition 65 On-product Warning : This product is exempt from labeling requirements under this Act.

inventories

US - TSCA : All the ingredients are listed or exempt.

SECTION 16: Other information

General information	All products manufactured by Knauf Insulation are made of non-classified fibers and are certified by EUCEB.
----------------------------	---



Products meeting EUCEB certification requirements can be recognised by the EUCEB logo printed on the packaging.

Further information can be obtained from

www.euceb.org

www.knaufnorthamerica.com

**Revision comments**

§1

Revision date

07/04/2025

Supersedes version of

30/05/2024

Current revision

3.1

SDS number

KI_DP_101

Other information

In 2001, the International Agency for Research on Cancer (IARC) reclassified mineral wool fibres and fiberglass from Group 2B (possibly carcinogenic) to Group 3 «agent which cannot be classified as for their carcinogenicity to humans». (See Monograph Vol 81, <http://monographs.iarc.fr/>)

This Safety Data Sheet / Product Data Sheet does not constitute a workplace assessment.

Information contained in this document represents the state of our knowledge regarding this product as of the date of issue of the document. Attention of users is drawn to possible risks taken when the product is used for other applications than the ones it has been designed for.