


LaHabra®

EIFS Sheathing Adhesive



DESCRIPTION:

- Adhesive to laminate EPS to listed substrates
- 100% acrylic polymer base
- Ready to use, applied without the addition of cement
- Exceptional workability
- Color: Light gray

USES:

EPS adhesive for the following substrates:

- Wood
- Gypsum sheathing
- Glass mat gypsum sheathing
- Metal siding and painted surfaces in combination with mechanical fasteners

COMPOSITION:

- Binder base: 100% acrylic polymers
- Water-based: VOC-compliant

COVERAGE:

Depending on the condition of the substrate and method of application, approximate coverages are:

- Using 5/16-in. (8mm) notched trowel: 270-290 sq. ft. (25-27 sq. m.) per pail
- Using 3/16-in. (5mm) notched trowel: 320-350 sq. ft. (30-32 sq. m.) per pail

CONTAINER:

- 55 lb. (25kg) net weight in plastic pails.
- Storage: Protect from direct sunlight and freezing at all times
- Do not stack pails more than 3 pails high
- Shelf life: One year if properly stored in original unopened container.

WORKING TIME:

Set time depends upon temperature and humidity. High humidity and low temperatures extend working time.

DRYING TIME:

Full adhesive bond strength is reached after 1-2 days, depending upon humidity and temperature.

CLEAN-UP:

Water-soluble prior to drying. Clean tools and containers with water prior to drying.

SURFACE PREPARATION:

- Planar irregularities are limited to 1/4 in (6mm) or less in a 4 ft. (1.22 m) radius. Surface irregularities are limited to 1/8 in (3 mm) or less.
- Irregular and uneven surface should be filled with any LaHabra Insul-Bond Base Coat & Adhesive
- Remove surface contaminants such as dust or dirt without damaging the substrate.
- Painted substrates must have paint removed with methods that result in no more than 10% of the remaining surface having paint, or be evaluated for bond on a project by project basis.
- For additional options for surface preparation, contact Parex USA Technical Support.

MIXING:

- Use clean equipment for mixing and preparation.
- LaHabra EIFS Sheathing Adhesive is a factory pre-mixed product.
- No additives of any kind such as rapid binders, antifreeze, accelerators, fillers, portland cement, etc., should be added under any circumstances.
- Keep container closed when not in use.

APPLICATION:

- Read the entire label before using this product.
- Apply LaHabra Sheathing Adhesive to the entire surface on one face of the insulation board using a 5/16-in. (8mm) or 3/16-in. (5mm) notched trowel. The ribbons should be of uniform thickness, run vertically, and reach the perimeter of the insulation board. To ensure high initial grab and uniform adhesive contact, apply insulation board to the wall with firm pressure to entire surface. Apply sufficient pressure to flatten adhesive ridges.

LIMITATIONS:

- Ambient and surface temperatures must be 40°F (4.4°C) or higher during application and drying time. Provide supplemental heat and protection from precipitation as needed.
- Use only on surfaces that are sound, clean, dry, unpainted (except in combination with mechanical fasteners), and free from any residue that might affect the ability of the Sheathing Adhesive to bond to the surface.
- Avoid application in direct sunlight in hot weather.

WARNING:

- Read complete Warning information printed on product container prior to use. For medical emergency information, call 1-800-424-9300.
- For more information on handling this product refer to its Material Safety Data Sheet (MSDS). The most current MSDS and Product Data Sheet (PDS) can be found on our website.
- This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about the guidelines for the proper use and application of the covered product(s) under normal environmental and working conditions. Because each project is different, Parex USA, Inc. cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

LaHabra®
www.lahabrastucco.com

Corporate Office

Parex USA, Inc.
 4125 E. La Palma Ave., Suite 250
 Anaheim, CA 92807
 (866) 516-0061
 Tech Support: (800) 226-2424

Facilities

Riverside, CA
 French Camp, CA
 Albuquerque, NM
 Colorado Springs, CO
 Anaheim, CA

North Hollywood, CA
 San Antonio, TX
 Redan, GA
 Wilkes Barre, PA

