



Latex Bonding Agents

SEPTEMBER 2011

| SELECTION CRITERIA | | | | | |
|------------------------------|----------|-----------------------------|------------------------------|------------------|------------------------|
| USE | | APPLICABLE STANDARDS | STRENGTH REQUIREMENTS | | LAMBERT PRODUCT |
| | | | TENSILE | BOND | |
| Plaster Applications | Interior | ASTM C-631 | 20-lbs. Minimum | | Hibond |
| | Exterior | ASTM C-932 | 150-lbs. minimum | | Acrylbond |
| | Both | ASTM C-932 | 150-lbs. Minimum | | 932 LINK™ |
| | Interior | N/A | N/A | N/A | Lambco Bond |
| Concrete Applications | Both | ASTM C-1059 | | 1250-lb. minimum | 932 LINK™ |
| | Interior | ASTM C-1059, Type I | | 400-lb. minimum | Hibond or PVA-20 |
| | Exterior | ASTM C-1059, Type II | | 1250-lb. minimum | Acrylbond |
| | Interior | N/A | N/A | N/A | Lambco Bond |

| COMPARISON | | | | |
|-------------------|--------------|-------------------|--|-------------------------------|
| PRODUCT | RESIN | PROPERTIES | USES | LOCATIONS |
| 932 LINK™ | VAE | Non-rewettable | Concrete & plaster bonding agent & admix | Exterior & interior |
| Acrylbond | Acrylic | Non-rewettable | Concrete & plaster bonding agent & admix | Exterior & interior |
| Hibond | PVA | Rewettable | Portland cement plaster and some concrete work | Interior & protected exterior |
| PVA-20 | PVA | Rewettable | Portland cement plaster | Interior |
| Lambco Bond | PVA | Rewettable | Portland cement plaster | Interior |
| L-16 Primer | EVA | Rewettable 1-time | Only for L-16 Self-Level Underlayment | Exterior & interior |

20 North Coburn Avenue ~ Orlando, FL 32805-2198 ~ (407) 841-2940 ~ fax (407) 839-1890 ~ (800) 432-4746

LAMBERT CORPORATION