



L&M™ LUMISEAL PLUS™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations
Date of Issue: 03/17/2020

Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: L&M™ LUMISEAL PLUS™

1.2. Intended Use of the Product

Use of the Substance/Mixture: Sealer. For professional use only.

1.3. Name, Address, and Telephone of the Responsible Party

Company

LATICRETE International

1 Laticrete Park, N

Bethany, CT 06524

T (203)-393-0010

www.laticrete.com

1.4. Emergency Telephone Number

Emergency Number : For Chemical Emergency call ChemTel Inc. day or night:
(800)255-3924 (North America)
(800)-099-0731 (Mexico)
+1 (813)248-0585 (International - collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Muta. 1B	H340
Carc. 1B	H350
Repr. 2	H361
STOT SE 3	H336
Asp. Tox. 1	H304
Aquatic Acute 2	H401
Aquatic Chronic 2	H411

Full text of hazard classes and H-statements : see section 16

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H226 - Flammable liquid and vapor.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H340 - May cause genetic defects.
H350 - May cause cancer.
H361 - Suspected of damaging fertility or the unborn child.
H401 - Toxic to aquatic life.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary Statements (GHS-US)

: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.

L&M™ LUMISEAL PLUS™

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof electrical, ventilating, and lighting equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P261 - Avoid breathing vapors, mist, or spray.
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, and eye protection.
P301+P310 - If swallowed: Immediately call a poison center or doctor.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P312 - Call a poison center or doctor if you feel unwell.
P321 - Specific treatment (see section 4 on this SDS).
P331 - Do NOT induce vomiting.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use appropriate media (see section 5) to extinguish.
P391 - Collect spillage.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	%	GHS US classification
Solvent naphtha, petroleum, light aromatic	(CAS-No.) 64742-95-6	48 - 70	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Muta. 1B, H340 Carc. 1B, H350 Repr. 2, H361 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Mineral spirits	(CAS-No.) 64475-85-0	5 - 15	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Asp. Tox. 1, H304

L&M™ LUMISEAL PLUS™

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Benzene, 1,2,4-trimethyl-	(CAS-No.) 95-63-6	5 - 12	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapor), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Xylenes (o-, m-, p- isomers)	(CAS-No.) 1330-20-7	0.5 - 1.4	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapor), H332 Skin Irrit. 2, H315 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Acute 2, H401
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	(CAS-No.) 41556-26-7	0.4 - 0.5	Flam. Liq. 4, H227 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Isopropylbenzene	(CAS-No.) 98-82-8	0.1 - 0.5	Flam. Liq. 3, H226 Carc. 1B, H350 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]-	(CAS-No.) 104810-47-1	0.2 - 0.3	Skin Sens. 1, H317 Aquatic Chronic 2, H411
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy-	(CAS-No.) 104810-48-2	0.2 - 0.3	Skin Sens. 1, H317 Aquatic Chronic 2, H411
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidiny ester	(CAS-No.) 82919-37-7	0.1 - 0.2	Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

First-aid Measures After Skin Contact: Immediately remove contaminated clothing. Obtain medical attention if irritation/rash develops or persists. Immediately drench affected area with water for at least 15 minutes.

First-aid Measures After Eye Contact: Immediately rinse with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

First-aid Measures After Ingestion: Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

L&M™ LUMISEAL PLUS™

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Injuries: May cause drowsiness and dizziness. May cause cancer. Suspected of damaging fertility or the unborn child. Skin sensitization. Causes skin irritation. Causes serious eye irritation. May cause genetic defects. May be fatal if swallowed and enters airways.

Symptoms/Injuries After Inhalation: High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction. Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Symptoms/Injuries After Eye Contact: Contact causes severe irritation with redness and swelling of the conjunctiva.

Symptoms/Injuries After Ingestion: Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

Chronic Symptoms: May cause cancer. Suspected of damaging fertility or the unborn child. May cause genetic defects. Contains benzene, a regulated human carcinogen. Benzene has the potential to cause anemia and other blood diseases, including leukemia, after repeated and prolonged exposure.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂). Water may be ineffective but water should be used to keep fire-exposed container cool.

Unsuitable Extinguishing Media: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Flammable liquid and vapor.

Explosion Hazard: May form flammable or explosive vapor-air mixture.

Reactivity: Reacts violently with strong oxidizers. Increased risk of fire or explosion.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and oxides of sulfur. Hydrogen sulfide and other sulfur-containing gases can evolve from this product particularly at elevated temperatures.

Other Information: Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing. Do not breathe vapor, mist or spray. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area. Eliminate ignition sources.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment. Collect spillage.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

L&M™ LUMISEAL PLUS™

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable.

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not handle until all safety precautions have been read and understood. Do not breathe mist, spray, vapors. Obtain special instructions before use. Do not get in eyes, on skin, or on clothing. Take precautionary measures against static discharge. Use only non-sparking tools.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.

Storage Conditions: Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in a well-ventilated place. Keep container tightly closed. Keep in fireproof place.

Incompatible Materials: Oxidizers. Acids.

7.3. Specific End Use(s)

Sealer. For professional use only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

Benzene, 1,2,4-trimethyl- (95-63-6)		
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	125 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	25 ppm
Xylenes (o-, m-, p- isomers) (1330-20-7)		
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA ACGIH	ACGIH STEL (ppm)	150 ppm
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA ACGIH	Biological Exposure Indices (BEI)	1.5 g/g Kreatinin Parameter: Methylhippuric acids - Medium: urine - Sampling time: end of shift
USA OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm
Isopropylbenzene (98-82-8)		
USA ACGIH	ACGIH TWA (ppm)	50 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	245 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	50 ppm
USA IDLH	US IDLH (ppm)	900 ppm (10% LEL)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	245 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
USA OSHA	Limit value category (OSHA)	prevent or reduce skin absorption

8.2. Exposure Controls

Appropriate Engineering Controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment.

Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing

: Chemically resistant materials and fabrics. Wear fire/flame resistant/retardant clothing.

L&M™ LUMISEAL PLUS™

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hand Protection	: Wear protective gloves.
Eye and Face Protection	: Chemical safety goggles.
Skin and Body Protection	: Wear suitable protective clothing.
Respiratory Protection	: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.
Other Information	: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Clear
Odor	: Aromatic solvent
Odor Threshold	: No data available
pH	: No data available
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: No data available
Flash Point	: 44 °C (111.2 °F) (Closed Cup)
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapor Pressure	: No data available
Relative Vapor Density at 20°C	: No data available
Relative Density	: No data available
Specific Gravity	: 0.93
Solubility	: Water: Insoluble
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available

9.2. Other Information No additional information available

SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Reacts violently with strong oxidizers. Increased risk of fire or explosion.
- 10.2. Chemical Stability:** Flammable liquid and vapor. May form flammable or explosive vapor-air mixture.
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.
- 10.5. Incompatible Materials:** Oxidizers. Acids.
- 10.6. Hazardous Decomposition Products:** Not expected to decompose under ambient conditions. If stored under heat for extended periods or significantly agitated, this material might evolve or release hydrogen sulfide, a flammable gas, which can raise and widen this material's actual flammability limits and significantly lower its auto-ignition temperature. Hydrogen sulfide is a toxic gas that can be fatal. It also has a rotten egg smell that causes odor fatigue very quickly and shouldn't be used as an indicator for the presence of gas.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

Solvent naphtha, petroleum, light aromatic (64742-95-6)	
LD50 Oral Rat	8400 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	3400 ppm/4h
Mineral spirits (64475-85-0)	

L&M™ LUMISEAL PLUS™

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

LD50 Oral Rat	> 34600 mg/kg
LC50 Inhalation Rat	> 21400 mg/m ³ (Exposure time: 4 h)
Benzene, 1,2,4-trimethyl- (95-63-6)	
LD50 Oral Rat	6000 mg/kg
LD50 Dermal Rabbit	> 3160 mg/kg
LC50 Inhalation Rat	18 g/m ³ (Exposure time: 4 h)
LC50 Inhalation Rat	10.8 mg/l/4h
ATE (Dust/Mist)	18.00 mg/l/4h
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 Oral Rat	> 5000 mg/kg
ATE (Dermal)	1,100.00 mg/kg body weight
ATE (Vapors)	11.00 mg/l/4h
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)	
LD50 Oral Rat	2615 mg/kg
Isopropylbenzene (98-82-8)	
LD50 Oral Rat	2260 mg/kg
LD50 Dermal Rabbit	10000 mg/kg
LC50 Inhalation Rat	9.83 mg/l/4h
LC50 Inhalation Rat	> 3577 ppm (Exposure time: 6 h)

Skin Corrosion/Irritation: Causes skin irritation.

Serious Eye Damage/Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: May cause genetic defects.

Carcinogenicity: May cause cancer.

Xylenes (o-, m-, p- isomers) (1330-20-7)	
IARC group	3
Isopropylbenzene (98-82-8)	
IARC group	2B
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity, Reasonably anticipated to be Human Carcinogen.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

Reproductive Toxicity: Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity (Single Exposure): May cause drowsiness or dizziness.

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: May be fatal if swallowed and enters airways.

Symptoms/Injuries After Inhalation: High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction. Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Symptoms/Injuries After Eye Contact: Contact causes severe irritation with redness and swelling of the conjunctiva.

Symptoms/Injuries After Ingestion: Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

Chronic Symptoms: May cause cancer. Suspected of damaging fertility or the unborn child. May cause genetic defects. Contains benzene, a regulated human carcinogen. Benzene has the potential to cause anemia and other blood diseases, including leukemia, after repeated and prolonged exposure.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General : Toxic to aquatic life with long lasting effects.

Solvent naphtha, petroleum, light aromatic (64742-95-6)	
LC50 Fish 1	9.22 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Benzene, 1,2,4-trimethyl- (95-63-6)	
LC50 Fish 1	7.19 (7.19 - 8.28) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

L&M™ LUMISEAL PLUS™

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EC50 Daphnia 1	6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LC50 Fish 1	3.3 mg/l
EC50 Daphnia 1	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 Fish 2	2.661 (2.661 - 4.093) mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
NOEC Chronic Crustacea	1.17
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)	
LC50 Fish 1	0.97 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
Isopropylbenzene (98-82-8)	
LC50 Fish 1	6.04 - 6.61 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 Fish 2	4.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 Daphnia 2	7.9 - 14.1 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
NOEC Chronic Crustacea	0.35 mg/l
NOEC Chronic Algae	0.22 mg/l

12.2. Persistence and Degradability

L&M™ LUMISEAL PLUS™	
Persistence and Degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative Potential

L&M™ LUMISEAL PLUS™	
Bioaccumulative Potential	Not established.

Benzene, 1,2,4-trimethyl- (95-63-6)	
Log Pow	3.63

Xylenes (o-, m-, p- isomers) (1330-20-7)	
BCF Fish 1	0.6 (0.6 - 15)
Log Pow	2.77 - 3.15

Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)	
Log Pow	0.37 (at 25 °C)

Isopropylbenzene (98-82-8)	
BCF Fish 1	35.5
Log Pow	3.7

12.4. **Mobility in Soil** No additional information available

12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste Treatment Methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable.

Ecology - Waste Materials: Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

Proper Shipping Name	: FLAMMABLE LIQUIDS, N.O.S. (Solvent naphtha, petroleum, light aromatic; Mineral spirits)
Hazard Class	: 3
Identification Number	: UN1993
Label Codes	: 3
Packing Group	: III
Marine Pollutant	: Marine pollutant
ERG Number	: 128



L&M™ LUMISEAL PLUS™

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.2. In Accordance with IMDG

Proper Shipping Name : FLAMMABLE LIQUID, N.O.S. (Solvent naphtha, petroleum, light aromatic; Mineral spirits)
Hazard Class : 3
Identification Number : UN1993
Packing Group : III
Label Codes : 3
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Marine Pollutant : Marine pollutant



14.3. In Accordance with IATA

Proper Shipping Name : FLAMMABLE LIQUID, N.O.S. (Solvent naphtha, petroleum, light aromatic; Mineral spirits)
Packing Group : III
Identification Number : UN1993
Hazard Class : 3
Label Codes : 3
ERG Code (IATA) : 3L



SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

L&M™ LUMISEAL PLUS™	
SARA Section 311/312 Hazard Classes	Health hazard - Specific target organ toxicity (single or repeated exposure) Health hazard - Carcinogenicity Health hazard - Reproductive toxicity Health hazard - Respiratory or skin sensitization Health hazard - Skin corrosion or Irritation Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Serious eye damage or eye irritation Health hazard - Germ cell mutagenicity Health hazard - Aspiration hazard
Solvent naphtha, petroleum, light aromatic (64742-95-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Benzene, 1,2,4-trimethyl- (95-63-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
SARA Section 313 - Emission Reporting	1 %
Xylenes (o-, m-, p- isomers) (1330-20-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	100 lb
SARA Section 313 - Emission Reporting	1 %
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester (82919-37-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy- (104810-48-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	FRI - FRI - indicates a polymeric substance containing no free-radical initiator in its Inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used. PMN - PMN - indicates a commenced PMN substance. XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).

L&M™ LUMISEAL PLUS™

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]- (104810-47-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag

FRI - FRI - indicates a polymeric substance containing no free-radical initiator in its Inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

PMN - PMN - indicates a commenced PMN substance.

XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).

Isopropylbenzene (98-82-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Subject to reporting requirements of United States SARA Section 313

CERCLA RQ

5000 lb

SARA Section 313 - Emission Reporting

1 %

15.2. US State Regulations

Mineral spirits (64475-85-0)

U.S. - New Jersey - Right to Know Hazardous Substance List

Benzene, 1,2,4-trimethyl- (95-63-6)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

U.S. - Pennsylvania - RTK (Right to Know) List

Xylenes (o-, m-, p- isomers) (1330-20-7)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

U.S. - Pennsylvania - RTK (Right to Know) List

Isopropylbenzene (98-82-8)


U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

U.S. - Pennsylvania - RTK (Right to Know) List

California Proposition 65

 **WARNING:** This product can expose you to Isopropylbenzene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Chemical Name (CAS No.)	Carcinogenicity	Developmental Toxicity	Female Reproductive Toxicity	Male Reproductive Toxicity
Isopropylbenzene (98-82-8)	X			

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision : 03/17/2020

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

GHS Full Text Phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation:vapor)	Acute toxicity (inhalation:vapor) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration hazard Category 1

L&M™ LUMISEAL PLUS™

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carc. 1B	Carcinogenicity Category 1B
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Muta. 1B	Germ cell mutagenicity Category 1B
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)