

## LP<sup>®</sup> SOLIDSTART<sup>®</sup> **ENGINEERED WOOD LSL**

## **Surpasses traditional framing lumber** in length, strength and consistency.

- Straighter than traditional lumber
- Allows for taller walls and longer lengths
- Manufactured to a more consistent moisture content, which helps keep it from twisting, warping and shrinking
  - Helps windows and doors to function properly
  - Tile and drywall are less likely to crack
  - Cabinets and countertops are easier to install
  - Less prone to nail pops
- Straighter walls mean less need to scribe or shim cabinetry
- Edges and ends are sealed for additional moisture protection
- New zinc borate treated LP<sup>®</sup> SolidGuard<sup>®</sup> LSL now available for sill plates
- All of these advantages add up to fewer callbacks!



SFI-00003

## See complete warranty details at LPCorp.com or call 888.820.0325

PEFC/29-31-102



## **BEHIND EVERY GREAT ROOM ARE** LP SOLIDSTART LSL STUDS.

LP SolidStart LSL studs are available in:

- 1.35E and 1.55E grades for tall walls 1.5" thick and depths to match traditional 2x lumber sizes
- Standard precut lengths up to 10'
- Long lengths available



© 2019 Louisiana-Pacific Corporation. All rights reserved. Sustainable Forestry Initiative and SFI are registered trademarks of Sustainable Forestry Initiative, Inc. PEFC and the associated logo are trademarks of Programme for the Endorsement of Forest Certification. All other trademarks are owned by Louisiana-Pacific Corporation. Printed in USA. LPEW 0476