

CLOSED SOFFIT

Cedar Texture

Products:

- LP® SmartSide® 38 Series 4' x 8' Soffit
- LP® SmartSide® 38 Series No Groove Square Edge (NGSE) Dual Use Siding and Soffit Panel
- LP® SmartSide® 38 Series Cut-to-Width Soffit
- LP® SmartSide® ExpertFinish® 38 Series Cut-to-Width Soffit
- LP® SmartSide® ExpertFinish® 38 Series No Groove Square Edge (NGSE) Dual Use Siding and Soffit Panel (see p. 66 for details)

DESIGNED & RATED FOR EXTERIOR USE

Substrate:

- Features engineered wood strand technology with precisely-sized, shaped, and layered wood strands from responsibly sourced logs
- Made using LP's proprietary SmartGuard® process, which includes industrial-grade resins, water-resistant waxes, zinc borate, and a resin-saturated overlay



Sustainability Info:

- ASTM-Verified Carbon Negative
- Made with wood, a renewable resource, vetted through strict Sustainable Forestry Initiative® (SFI®) standards




Application Instructions:
LPCorp.com/Literature



38 Series Closed Soffit - Cedar Texture

3/8" Nominal Thickness
Primed:
 Soffit Panel: 4' x 8'
 NGSE Dual Use Siding and Soffit Panel: 4' x 8'
 Cut-to-Width: 12" | 16" | 24"
Prefinished:
 Varies by color

Primed Specifications and PIDs:



PRODUCT	LENGTH	ACTUAL WIDTH	THICKNESS	MAX SPAN RATING	PID
38 Series 4' x 8' Cedar Texture Soffit	8 ft. (96 in.) (2.4 m)	47.81 in. (1214 mm)	0.354 in. (9 mm)	24 in. o.c.	25813
38 Series Cedar Texture Panel No Groove Square Edge (NGSE) Dual Use Siding and Soffit ★	8 ft. (96 in.) (2.4 m)	47.81 in. (1214 mm)	0.354 in. (9 mm)	16 in. o.c. Siding 24 in. o.c. Soffit	41044
38 Series Cedar Texture Closed Soffit Cut-to-Width	16 ft. (192 in.) (4.9 m)	11.94 in. (303 mm)	0.354 in. (9 mm)	24 in. o.c.	25805
	16 ft. (192 in.) (4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	24 in. o.c.	25806
	16 ft. (192 in.) (4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	24 in. o.c.	25807

★ Can be used in siding or soffit applications

(See p. 66 for LP® SmartSide® ExpertFinish® Cedar Texture Dual Use Siding and Soffit Panels.)

ExpertFinish® Color Specifications and PIDs:



COLOR	LENGTH	ACTUAL WIDTH	THICKNESS	MAX SPAN RATING	PID	
Snowscape White Cut-to-Width	16 ft. (192 in.) (4.9 m)	11.94 in. (303 mm)	0.354 in. (9 mm)	24 in. o.c.	46434	
	16 ft. (192 in.) (4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	24 in. o.c.	46436	
	16 ft. (192 in.) (4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	24 in. o.c.	46536	
Sand Dunes	16 ft. (192 in.) (4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	24 in. o.c.	46535	
Quarry Gray	16 ft. (192 in.) (4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	24 in. o.c.	46534	
Abyss Black	16 ft. (192 in.) (4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	24 in. o.c.	46533	
NEW NATURALS COLLECTION™ CUT-TO-WIDTH SOFFIT	Washed White	16 ft. (192 in.) (4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	24 in. o.c.	47367
	Smoky Slate	16 ft. (192 in.) (4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	24 in. o.c.	47368
	Bonsai Black	16 ft. (192 in.) (4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	24 in. o.c.	47369
	Weathered Walnut	16 ft. (192 in.) (4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	24 in. o.c.	47370
	Aged Amber	16 ft. (192 in.) (4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	24 in. o.c.	47364
	Saffron Cedar	16 ft. (192 in.) (4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	24 in. o.c.	47363

38 SERIES 4' x 8' CEDAR TEXTURE SOFFIT



38 SERIES CEDAR TEXTURE SOFFIT - CUT-TO-WIDTH



All graphics are for illustrative purposes only. Metric units are rounded. Contact your LP Sales Rep for product availability. All colors shown are representative and may not be an exact match.

CLOSED SOFFIT

Brushed Smooth

Products:

LP® SmartSide® 38 Series No Groove Square Edge (NGSE) Dual Use Siding and Soffit Panel

LP® SmartSide® 38 Series Cut-to-Width Soffit

LP® SmartSide® ExpertFinish® 38 Series Cut-to-Width Soffit

LP® SmartSide® ExpertFinish® 38 Series No Groove Square Edge (NGSE) Dual Use Siding and Soffit Panel (see p. 69 for details)

DESIGNED & RATED FOR EXTERIOR USE

Substrate:

- Features engineered wood strand technology with precisely-sized, shaped, and layered wood strands from responsibly sourced logs
- Made using LP's proprietary SmartGuard® process, which includes industrial-grade resins, water-resistant waxes, zinc borate, and a resin-saturated overlay



Application Instructions:

LPCorp.com/Literature



Sustainability Info:

- ASTM-Verified Carbon Negative
- Made with wood, a renewable resource, vetted through strict Sustainable Forestry Initiative® (SFI®) standards



38 Series Closed Soffit - Brushed Smooth

3/8" Nominal Thickness

Primed:
NGSE Dual Use Siding and Soffit Panel: 8' | 10'
Cut-to-Width: 12" | 16" | 24"

Prefinished:
Varies by color

Primed Specifications and PIDs:



Brushed Smooth

Primed

PRODUCT	LENGTH	ACTUAL WIDTH	THICKNESS	MAX SPAN RATING	PID
38 Series Brushed Smooth Panel No Groove Square Edge (NGSE) Dual Use Siding and Soffit ★	8 ft. (96 in.) (2.4 m)	47.81 in. (1214 mm)	0.354 in. (9 mm)	16 in. o.c. Siding 24 in. o.c. Soffit	46008
	10 ft. (120 in.) (3.0 m)	47.81 in. (1214 mm)	0.354 in. (9 mm)	16 in. o.c. Siding 24 in. o.c. Soffit	46650
38 Series Brushed Smooth Closed Soffit Cut-to-Width	16 ft. (192 in.) (4.9 m)	11.94 in. (303 mm)	0.354 in. (9 mm)	24 in. o.c.	46005
	16 ft. (192 in.) (4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	24 in. o.c.	46006
	16 ft. (192 in.) (4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	24 in. o.c.	46009

★ Can be used in siding or soffit applications

(See p. 69 for LP® SmartSide® ExpertFinish® Brushed Smooth Dual Use Siding and Soffit Panels.)

ExpertFinish® Color Specifications and PIDs:




Brushed Smooth

Select ExpertFinish® Colors

COLOR	LENGTH	ACTUAL WIDTH	THICKNESS	MAX SPAN RATING	PID	
Snowscape White Cut-to-Width	16 ft. (192 in.) (4.9 m)	11.94 in. (303 mm)	0.354 in. (9 mm)	24 in. o.c.	46541	
	16 ft. (192 in.) (4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	24 in. o.c.	46542	
	16 ft. (192 in.) (4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	24 in. o.c.	46546	
Sand Dunes	16 ft. (192 in.) (4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	24 in. o.c.	46545	
Quarry Gray	16 ft. (192 in.) (4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	24 in. o.c.	46544	
Abyss Black	16 ft. (192 in.) (4.9 m)	23.94 in. (608 mm)	0.354 in. (9 mm)	24 in. o.c.	46543	
NEW NATURALS COLLECTION™ CUT-TO-WIDTH SOFFIT	Washed White	16 ft. (192 in.) (4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	24 in. o.c.	47366
	Smoky Slate	16 ft. (192 in.) (4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	24 in. o.c.	47365
	Bonsai Black	16 ft. (192 in.) (4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	24 in. o.c.	47362
	Weathered Walnut	16 ft. (192 in.) (4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	24 in. o.c.	47361
	Aged Amber	16 ft. (192 in.) (4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	24 in. o.c.	47360
	Saffron Cedar	16 ft. (192 in.) (4.9 m)	15.94 in. (405 mm)	0.354 in. (9 mm)	24 in. o.c.	47359

38 SERIES BRUSHED SMOOTH SOFFIT - CUT-TO-WIDTH



All graphics are for illustrative purposes only. Metric units are rounded. Contact your LP Sales Rep for product availability. All colors shown are representative and may not be an exact match.

CLOSED SOFFIT

Cedar Texture

Product:

LP® SmartSide® 76 Series Closed Soffit

DESIGNED & RATED FOR EXTERIOR USE

Substrate:

- Features engineered wood strand technology with precisely-sized, shaped, and layered wood strands from responsibly sourced logs
- Made using LP's proprietary SmartGuard® process, which includes industrial-grade resins, water-resistant waxes, zinc borate, and a resin-saturated overlay



Sustainability Info:

- ASTM-Verified Carbon Negative
- Made with wood, a renewable resource, vetted through strict Sustainable Forestry Initiative® (SFI®) standards



76 Series Closed Soffit - Cedar Texture

7/16" Nominal Thickness
Primed: 4' x 8' Soffit Panel




Application Instructions:

LPCorp.com/Literature



Primed Specifications and PIDs:

76 SERIES 4' x 8' CEDAR TEXTURE SOFFIT



PRODUCT	LENGTH	ACTUAL WIDTH	THICKNESS	MAX SPAN RATING	PID
76 Series 4' x 8' Cedar Texture Soffit	8 ft. (96 in.) (2.4 m)	47.81 in. (1214 mm)	0.418 in. (10.6 mm)	24 in. o.c.	25814

CLOSED SOFFIT

Cedar Texture

Product:

LP® SmartSide® 190 Series Closed Soffit

DESIGNED & RATED FOR EXTERIOR USE

Substrate:

- Features engineered wood strand technology with precisely-sized, shaped, and layered wood strands from responsibly sourced logs
- Made using LP's proprietary SmartGuard® process, which includes industrial-grade resins, water-resistant waxes, zinc borate, and a resin-saturated overlay



Sustainability Info:

- ASTM-Verified Carbon Negative
- Made with wood, a renewable resource, vetted through strict Sustainable Forestry Initiative® (SFI®) standards



190 Series Closed Soffit - Cedar Texture

19/32" Nominal Thickness
Primed: 4' x 8' Soffit Panel




Installation Instructions:

LPCorp.com/Literature



Primed Specifications and PIDs:

190 SERIES 4' x 8' CEDAR TEXTURE SOFFIT



PRODUCT	LENGTH	ACTUAL WIDTH	THICKNESS	MAX SPAN RATING	PID
190 Series 4' x 8' Cedar Texture Soffit	8 ft. (96 in.) (2.4 m)	47.81 in. (1214 mm)	0.578 in. (14.7 mm)	24 in. o.c.	25816*

*Special order item. Requires minimum quantity and extended lead times.