

LEED Credit Product Checklist for Lyons Manufacturing Products

SUPER FLOWCRETE®

Existing Building Restoration or Rehab

Mr Credit 1.1 and 1.2 – Maintain Existing Floor

SUPER FLOWCRETE can be used to repair an existing floor thereby reducing the waste and impacts of restoration.

MR Credit 5.1 and 5.2 – Regional Materials

For Projects within 500 miles of Dallas Texas, SUPER FLOWCRETE should be considered a 74% Regional Material.

IEQ Credit 4.1 and 4.2 – Indoor Low Emitting Materials

SUPER FLOWCRETE has 0 VOC emissions when used as an interior repair material. P-100 Primer used with SUPER FLOWCRETE has less than 2.34 g/l VOC emissions.

EA Prerequisite and Credit 1

SUPER FLOWCRETE will match the thermal mass of existing concrete floors when analyzing energy costs for design and optimization.

New Construction

MR Credit 5.1 and 5.2 – Regional Materials

For Projects within 500 miles of Dallas Texas, SUPER FLOWCRETE should be considered a 74% Regional Material.

IEQ Credit 4.1 and 4.2 – Indoor Low Emitting Materials

SUPER FLOWCRETE has 0 VOC emissions when used as an interior repair material. P-100 Primer used with SUPER FLOWCRETE has less than 2.34 g/l VOC emissions.

EA Prerequisite and Credit 1

SUPER FLOWCRETE will match the thermal mass of existing concrete floors when analyzing energy costs for design and optimization.