

Safety Data Sheet

KERAPOXY CQ PART A

Safety Data Sheet dated: 01/08/2025 - version 13

Date of first edition: 03/25/2015



1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: KERAPOXY CQ PART A

Trade code: 905UB9990

Recommended use of the chemical and restrictions on use

Recommended use: Epoxy grout

Restrictions on use: Not available

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: MAPEI CORP. (USA and Puerto Rico)

1144 East Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 954-246-8888

Responsible: RDProductSafety@mapei.com

Emergency 24 hour numbers:

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. HAZARD(S) IDENTIFICATION



Classification of the chemical

Skin irritation, Category 2

Causes skin irritation.

Eye irritation, Category 2A

Causes serious eye irritation.

Skin Sensitization, Category 1B

May cause an allergic skin reaction.

Reproductive toxicity, Category 1B

May damage fertility. May damage the unborn child.

Acute aquatic hazard, category 3

Harmful to aquatic life

Chronic (long term) aquatic hazard, category 3

Harmful to aquatic life with long lasting effects.

Label elements

Hazard pictograms and Signal Word



Danger

Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H360FD May damage fertility. May damage the unborn child.

H402 Harmful to aquatic life

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe mist/vapours/spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P314 Get medical advice/attention if you feel unwell.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P501 Dispose of contents/container in accordance with applicable regulations.

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

This product contains titanium dioxide which IARC has classified as a Group 2B carcinogen (possibly carcinogenic to humans). Evidence is based on sufficient animal testing as a result of long-term inhalation at high concentrations of respirable amounts of titanium dioxide. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a dust hazard)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Not Relevant

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

Qty	Name	Ident. Numb.	Classification
50-75 %	silica sand; quartz	CAS:14808-60-7 EC:238-878-4	STOT RE 1, H372; Carc. 1A, H350
10-20 %	bis-[4-(2,3-epoxipropoxy)phenyl]propane	CAS:1675-54-3, 25085-99-8 EC:216-823-5 Index:603-073-00-2	Skin Irrit. 2, H315; Skin Sens. 1, H317; Eye Irrit. 2A, H319; Aquatic Chronic 2, H411; Aquatic Acute 2, H401
5-10 %	titanium dioxide; Dioxotitanium	CAS:13463-67-7 EC:236-675-5 Index:022-006-00-2	Carc. 2, H351
5-10 %	alkyl epoxy resin; Oxirane, mono((C12-14-alkyloxy)methyl) derivatives	CAS:68609-97-2 EC:271-846-8 Index:603-103-00-4	Skin Irrit. 2, H315; Skin Sens. 1B, H317; Repr. 1B, H360F
2.5-5 %	formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol;	CAS:9003-36-5 EC:701-263-0	Skin Irrit. 2, H315; Aquatic Chronic 2, H411; Skin Sens. 1, H317

4. FIRST AID MEASURES

Description of first aid measures

- In case of skin contact:
- Immediately take off all contaminated clothing.
 - OBTAIN IMMEDIATE MEDICAL ATTENTION.
 - Obtain medical attention if skin related symptoms persist.
 - Remove contaminated clothing immediately and dispose of safely.
 - After contact with skin, wash immediately with soap and plenty of water.
- In case of eyes contact:
- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
 - Protect uninjured eye.
- In case of Ingestion:
- Do not induce vomiting, get medical attention showing the SDS and the hazard label.
- In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

Eye irritation
Eye damages
Skin Irritation
Erythema

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

Water.
Carbon dioxide (CO₂).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.
Burning produces heavy smoke.
Hazardous combustion products: Not available
Explosive properties: Not Relevant
Oxidizing properties: Not Relevant

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.
Remove persons to safety.
Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand
Retain contaminated washing water and dispose it.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.
Exercise the greatest care when handling or opening the container.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Storage temperature: Not available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Community Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
silica sand; quartz CAS: 14808-60-7	ACGIH		Long Term: 0.025 mg/m3 A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis
	MAK	AUSTRIA	Long Term: 0.15 mg/m3
	ACGIH		Long Term: 0.025 mg/m3 (R), A2 - Pulm fibrosis, lung cancer
	MAK	SWITZERLAND	Long Term: 0.15 mg/m3
titanium dioxide; Dioxotitanium CAS: 13463-67-7	EU		Long Term: 0.1 mg/m3 Behaviour Binding
	ACGIH		Long Term: 10 mg/m3 A4 - LRT irr
	MAK	GERMANY	Long Term: 0.3 mg/m3
	OSHA		Long Term: 15 mg/m3
	ACGIH		Long Term: 10 mg/m3 A4 - Not Classifiable as a Human Carcinogen;lower respiratory tract irritation
	MAK	AUSTRIA	Long Term: 5 mg/m3; Short Term: 10 mg/m3
	MAK	SWITZERLAND	Long Term: 3 mg/m3

Predicted No Effect Concentration (PNEC) values

titanium dioxide; Dioxotitanium CAS: 13463-67-7	Exposure Route: Fresh Water; PNEC Limit: 0.184 mg/l
	Exposure Route: Soil; PNEC Limit: 100 mg/kg
	Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 100 mg/l
	Exposure Route: Marine water; PNEC Limit: 0.0184 mg/l
	Exposure Route: Marine water sediments; PNEC Limit: 100 mg/kg
	Exposure Route: Freshwater sediments; PNEC Limit: 1000 mg/kg
	Exposure Route: Intermittent release; PNEC Limit: 0.193 mg/l
alkyl epoxy resin; Oxirane, mono((C12-14-alkyloxy)methyl) derivatives CAS: 68609-97-2	Exposure Route: Marine water; PNEC Limit: 0.00072 mg/l
	Exposure Route: Fresh Water; PNEC Limit: 0.0072 mg/l
	Exposure Route: Freshwater sediments; PNEC Limit: 66.77 mg/kg
	Exposure Route: Marine water sediments; PNEC Limit: 6.677 mg/kg
	Exposure Route: Soil; PNEC Limit: 80.12 mg/kg
	Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 10 mg/l
	Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 10 mg/l
formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol; CAS: 9003-36-5	Exposure Route: Fresh Water; PNEC Limit: 0.003 mg/l
	Exposure Route: Freshwater sediments; PNEC Limit: 0.294 mg/kg
	Exposure Route: Marine water; PNEC Limit: 0.0003 mg/l
	Exposure Route: Marine water sediments; PNEC Limit: 0.0294 mg/kg
	Exposure Route: Soil; PNEC Limit: 0.237 mg/kg

Derived No Effect Level (DNEL) values

titanium dioxide; Dioxotitanium CAS: 13463-67-7	Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects Worker Industry: 0.17 mg/m3
	Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects

Consumer: 0.028 mg/m3

Appropriate engineering controls: Not available

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: paste various

Odour: characteristic

Odour threshold: Not Relevant

pH: Not Relevant

Melting point / freezing point: Not Relevant

Initial boiling point and boiling range: Not Relevant

Flash point: 94 °C (201 °F)

Evaporation rate: Not Relevant

Upper/lower flammability or explosive limits: Not Relevant

Vapour density: Not Relevant

Vapour pressure: Not Relevant

Relative density: 1.77 g/cm³

Solubility in water: insoluble

Solubility in oil: partly soluble

Partition coefficient (n-octanol/water): Not Relevant

Auto-ignition temperature: Not Relevant

Decomposition temperature: Not Relevant

Viscosity: 4,000,000.00 mPA-s

Kinematic viscosity: > 20,5 mm²/sec (40 °C) mm²/s

Explosive properties: Not Relevant

Oxidizing properties: Not Relevant

Solid/gas flammability: Not Relevant

Other information

Substance Groups relevant properties Not Relevant

Miscibility: Not Relevant

Fat Solubility: Not Relevant

Conductivity: Not Relevant

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Data not available.

Possibility of hazardous reactions

None.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological Information of the Preparation

a) acute toxicity	Not classified Based on available data, the classification criteria are not met
b) skin corrosion/irritation	The product is classified: Skin irritation, Category 2(H315)
c) serious eye damage/irritation	The product is classified: Eye irritation, Category 2A(H319)
d) respiratory or skin sensitisation	The product is classified: Skin Sensitization, Category 1B(H317)
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified Based on available data, the classification criteria are not met
g) reproductive toxicity	The product is classified: Reproductive toxicity, Category 1B(H360)
h) STOT-single exposure	Not classified Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

silica sand; quartz	a) acute toxicity	LD50 Oral > 2000 mg/kg LD50 Skin > 2000 mg/kg
bis-[4-(2,3-epoxipropoxy)phenyl]propane	a) acute toxicity	LD50 Skin Rabbit = 20 mg/kg LD50 Oral Rat = 11300 µL/kg
titanium dioxide; Dioxotitanium	a) acute toxicity	LD50 Oral Rat > 5000 mg/kg LD50 Skin Rat > 2000 mg/m3 LC50 Inhalation Dust Rat > 6.82 mg/l 4h LD50 Skin Rabbit > 10000 mg/kg
alkyl epoxy resin; Oxirane, mono((C12-14-alkyloxy)methyl) derivatives	a) acute toxicity	LD50 Oral Rat = 19200 mg/kg LD50 Skin Rabbit = 4000 mg/kg
formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol;	a) acute toxicity	LD50 Oral Rat > 5000 mg/kg LD50 Skin Rat > 2000 mg/kg
	i) STOT-repeated exposure	NOAEL Oral = 250 mg/kg

Substance(s) listed on the IARC Monographs:

silica sand; quartz	Group 1
---------------------	---------

bis-[4-(2,3-epoxipropoxy)phenyl]propane Group 3

titanium dioxide; Dioxotitanium Group 2B

Substance(s) listed as OSHA Carcinogen(s):

silica sand; quartz

titanium dioxide; Dioxotitanium

Substance(s) listed as NIOSH Carcinogen(s):

silica sand; quartz

titanium dioxide; Dioxotitanium

Substance(s) listed on the NTP report on Carcinogens:

silica sand; quartz

12. ECOLOGICAL INFORMATION

Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

The product is classified: Acute aquatic hazard, category 3(H402), Chronic (long term) aquatic hazard, category 3(H412)

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
bis-[4-(2,3-epoxipropoxy)phenyl]propane	CAS: 1675-54-3, a) 25085-99-8 - EINECS: 216- 823-5 - INDEX: 603-073-00-2	a) Aquatic acute toxicity : LC50 Fish = 2 mg/L 96h
titanium dioxide; Dioxotitanium	CAS: 13463-67- 7 - EINECS: 236-675-5 - INDEX: 022- 006-00-2	a) Aquatic acute toxicity : EC50 Daphnia = 1.8 mg/L 48h a) Aquatic acute toxicity : LC50 Fish > 100 mg/L 96
alkyl epoxy resin; Oxirane, mono((C12-14-alkyloxy)methyl) derivatives	CAS: 68609-97- 2 - EINECS: 271-846-8 - INDEX: 603- 103-00-4	a) Aquatic acute toxicity : EC50 Algae = 16 mg/L 72 a) Aquatic acute toxicity : NOEC Algae = 5600 mg/L 72 a) Aquatic acute toxicity : EC50 Daphnia > 100 mg/L 48 a) Aquatic acute toxicity : LC50 Fish > 100 mg/L 96h
formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol;	CAS: 9003-36-5 - EINECS: 701- 263-0	a) Aquatic acute toxicity : EL50 Daphnia = 7.2 mg/L 48h a) Aquatic acute toxicity : EC50 Algae = 843 mg/L 72h b) Aquatic chronic toxicity : NOEC Algae = 500 mg/L 72h a) Aquatic acute toxicity : LC50 Fish = 5.7 mg/L 96h
		a) Aquatic acute toxicity : EC50 Daphnia = 2.55 mg/L 48h a) Aquatic acute toxicity : EC50 Algae = 1.8 mg/L 72h

Persistence and degradability

Component	Persistence/Degradability:
alkyl epoxy resin; Oxirane, mono((C12-14-alkyloxy)methyl) derivatives	Readily biodegradable

Bioaccumulative potential

Component	Bioaccumulation
-----------	-----------------

alkyl epoxy resin; Oxirane, Not bioaccumulative
mono((C12-14-alkyloxy)methyl)
derivatives

Mobility in soil

N.A.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations.

UN number

DOT-UN Number: Not Applicable

ADR-UN number: Not Applicable

IATA-Un number: Not Applicable

IMDG-Un number: Not Applicable

UN proper shipping name

DOT-Proper Shipping Name: Not Applicable

ADR-Shipping Name: Not Applicable

IATA-Technical name: Not Applicable

IMDG-Technical name: Not Applicable

Transport hazard class(es)

DOT-Hazard Class: Not Applicable

ADR-Class: Not Applicable

IATA-Class: Not Applicable

IMDG-Class: Not Applicable

Packing group

DOT Packing Group: Not Applicable

ADR-Packing Group: Not Applicable

IATA-Packing group: Not Applicable

IMDG-Packing group: Not Applicable

Environmental hazards

Marine pollutant: No

Environmental Pollutant: Not Applicable

DOT-RQ: No

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

Special precautions

Department of Transportation (DOT):

Not Applicable

Road and Rail (ADR-RID) :

Not Applicable

Air (IATA) :
Not Applicable
Sea (IMDG) :
Not Applicable

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

All the components are listed on the TSCA inventory

TSCA listed substances:

silica sand; quartz	is listed in TSCA	Section 8b
bis-[4-(2,3-epoxipropoxy)phenyl]propane	is listed in TSCA	Section 8b
titanium dioxide; Dioxotitanium	is listed in TSCA	Section 8b
alkyl epoxy resin; Oxirane, mono((C12-14-alkyloxy)methyl) derivatives	is listed in TSCA	Section 8b
formaldehyde, polymer with 2-(chloromethyl)oxirane and phenol;	is listed in TSCA	Section 8b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

No substances listed

Section 313 - Toxic chemical list:

No substances listed

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

No substances listed

CAA - Clean Air Act

CAA listed substances:

No substances listed

CWA - Clean Water Act

CWA listed substances:

No substances listed

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

silica sand; quartz	Listed as carcinogen
titanium dioxide; Dioxotitanium	Listed as carcinogen

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

silica sand; quartz
titanium dioxide; Dioxotitanium

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

silica sand; quartz
titanium dioxide; Dioxotitanium

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

silica sand; quartz
titanium dioxide; Dioxotitanium

Canada - Federal regulations

DSL - Domestic Substances List

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

This product complies with NDSL inventory

NPRI - National Pollutant Release Inventory

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

16. OTHER INFORMATION

Safety Data Sheet dated: 1/8/2025 - version 13

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H350	May cause cancer.
H351	Suspected of causing cancer.
H360F	May damage fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
A.2/2	Skin Irrit. 2	Skin irritation, Category 2
A.3/2A	Eye Irrit. 2A	Eye irritation, Category 2A
A.4.2/1	Skin Sens. 1	Skin Sensitization, Category 1
A.4.2/1B	Skin Sens. 1B	Skin Sensitization, Category 1B
A.6/1A	Carc. 1A	Carcinogenicity, Category 1A
A.6/2	Carc. 2	Carcinogenicity, Category 2
A.7/1B	Repr. 1B	Reproductive toxicity, Category 1B
A.9/1	STOT RE 1	Specific target organ toxicity following repeated exposure, Category 1
US-HAE/A2	Aquatic Acute 2	Acute aquatic hazard, category 2
US-HAE/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2

Legend to abbreviations and acronyms used in the safety data sheet:

- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
- RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
- IMDG: International Maritime Code for Dangerous Goods.
- IATA: International Air Transport Association.
- IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
- ICAO: International Civil Aviation Organization.
- ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
- GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
- CLP: Classification, Labeling, Packaging.
- EINECS: European Inventory of Existing Commercial Chemical Substances.
- INCI: International Nomenclature of Cosmetic Ingredients.
- CAS: Chemical Abstracts Service (division of the American Chemical Society).
- GefStoffVO: Ordinance on Hazardous Substances, Germany.
- LC50: Lethal concentration, for 50 percent of test population.
- LD50: Lethal dose, for 50 percent of test population.
- DNEL: Derived No Effect Level.
- PNEC: Predicted No Effect Concentration.
- TLV: Threshold Limiting Value.
- TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
WGK: German Water Hazard Class.
KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 15. REGULATORY INFORMATION
- 16. OTHER INFORMATION