

Safety Data Sheet

PLANICRETE W PART A

Safety Data Sheet dated: 06/24/2021 - version 10

Date of first edition: 05/26/2015



1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: PLANICRETE W PART A

Trade code: 9003790

Recommended use of the chemical and restrictions on use

Recommended use: Epoxy-polyurethane adhesive

Restrictions on use: N.A.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: MAPEI CORP. (USA and Puerto Rico)

1144 East Newport Center Drive - 33442 - Deerfield Beach - FL - USA


Responsible: RDProductSafety@mapei.com

Emergency 24 hour numbers:

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. HAZARD(S) IDENTIFICATION



Classification of the chemical

Flam. Liq. 4	Combustible liquid
Skin Sens. 1B	May cause an allergic skin reaction.
Repr. 2	Suspected of damaging fertility. Suspected of damaging the unborn child.
Aquatic Acute 3	Harmful to aquatic life
Aquatic Chronic 3	Harmful to aquatic life with long lasting effects.

Label elements

Pictograms and Signal Words



Warning

Hazard statements:

H227	Combustible liquid
H317	May cause an allergic skin reaction.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements:

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P261	Avoid breathing mist/vapours/spray.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P321	Specific treatment (see supplementary instructions on this label)
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.

P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire, use a dry powder fire extinguisher to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with applicable regulations.

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

This product contains titanium dioxide which IARC has classified as a Group 2B carcinogen (possibly carcinogenic to humans). Evidence is based on sufficient animal testing as a result of long-term inhalation at high concentrations of respirable amounts of titanium dioxide. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a dust hazard)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

Concentration (% w/w)	Name	Ident. Numb.	Classification	Registration Number
5-10 %	Bisphenol A epoxy resin	CAS:25085-99-8	Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Aquatic Chronic 2, H411; Skin Sens. 1B, H317	
1-2.5 %	TITANIUM DIOXIDE	CAS:13463-67-7	Carc. 2, H351	
1-2.5 %	ETHYLACETATE	CAS:141-78-6	Flam. Liq. 2, H225; STOT SE 3, H336	
0.49-1 %	4-NONYLPHENOL, BRANCHED	CAS:84852-15-3	Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Corr. 1B, H314; Eye Dam. 1, H318; Repr. 2, H361	

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- OBTAIN IMMEDIATE MEDICAL ATTENTION.
- Obtain medical attention if skin related symptoms persist.
- Remove contaminated clothing immediately and dispose of safely.

In case of eyes contact:

- Wash immediately with water.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

N.A.

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

- (see paragraph 4.1)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: N.A.

Explosive properties: N.A.

Oxidizing properties: N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Storage temperature: N.A.

Always keep in a well ventilated place.

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

List of components with OEL value

Component	OEL Type	Country	Ceiling	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Behaviour	Note
TITANIUM DIOXIDE	OSHA			15					
	ACGIH			10					A4 - Not Classifiable as a Human Carcinogen; lower respiratory tract irritation;
	MAK	GERMANY		0.3					
	ACGIH			10					A4 - Not Classifiable as a Human Carcinogen; lower respiratory tract irritation
ETHYLACETATE	OSHA			1400	400				
	ACGIH				400				eye and upper respiratory tract irritation;
	MAK	AUSTRIA		5		10			
	MAK	SWITZERLAND		3					

MAK	GERMANY	750	200		
ACGIH			400		
MAK	AUSTRIA	734	200	1468	400
MAK	SWITZERLAND	730	200		

eye and upper respiratory tract irritation

Appropriate engineering controls: N.A.

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

N.A.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: paste white

Odour: No data available

Odour threshold: No data available

pH: No data available

Melting point / freezing point: No data available

Initial boiling point and boiling range: 100 °C (212 °F)

Flash point: 83 °C (181 °F)

Evaporation rate: < 1.0

Upper/lower flammability or explosive limits: No data available

Vapour density: > 1.0

Vapour pressure: No data available

Relative density: No data available

Solubility in water: Insoluble

Solubility in oil: No data available

Partition coefficient (n-octanol/water): No data available

Auto-ignition temperature: No data available

Decomposition temperature: No data available

Viscosity: No data available

Explosive properties: No data available

Oxidizing properties: No data available

Solid/gas flammability: No data available

Other information

Substance Groups relevant properties No data available

Miscibility: No data available

Fat Solubility: No data available

Conductivity: No data available

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Data not available.

Possibility of hazardous reactions

None.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION**Information on toxicological effects****Toxicological information of the mixture:**

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information on main components of the mixture:

TITANIUM DIOXIDE	a) acute toxicity	LD50 Oral Rat > 10000 mg/kg
ETHYLACETATE	a) acute toxicity	LD50 Skin Rabbit > 20 ml/kg LC50 Inhalation Mouse = 1500 ppm 4h LD50 Oral Rat = 5620 mg/kg LD50 Skin Rabbit > 18000.00000 mg/kg LD50 Skin Rabbit > 18000 mg/kg LC50 Inhalation Rat = 4000 ppm 4h LD50 Oral Rat = 5620 mg/kg LC50 Inhalation Rat = 4000 ppm 4h
4-NONYLPHENOL, BRANCHED	a) acute toxicity	LD50 Oral Rat 1300 mg/kg LD50 Skin Rabbit > 2000 mg/kg LD50 Skin Rabbit = 2000 mg/kg LD50 Oral Rat = 1300 mg/kg

If not differently specified, the information required in the regulation and listed below must be considered as N.A.

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure
Toxicological kinetics, metabolism
and distribution information
- i) STOT-repeated exposure
- j) aspiration hazard

Substance(s) listed on the IARC Monographs:

TITANIUM DIOXIDE Group 2B

Substance(s) listed as OSHA Carcinogen(s):

TITANIUM DIOXIDE

Substance(s) listed as NIOSH Carcinogen(s):

TITANIUM DIOXIDE

Substance(s) listed on the NTP report on Carcinogens:

None

12. ECOLOGICAL INFORMATION

Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of components with eco-toxicological properties

Component	Ident. Numb.	Ecotox Infos
ETHYLACETATE	CAS: 141-78-6	a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 220 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 484 mg/L 96h IUCLID a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 560 mg/L 48h EPA a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss 352 mg/L 96h EPA
4-NONYLPHENOL, BRANCHED	CAS: 84852-15-3	LC50 Fish Pimephales promelas 0.135 mg/L 96h „Holcombe, G.W., Phipps, G.L., Knuth, M.L. and Felhaber, T. (1984) Environ. Pollut. (Series A) 35, 367-381 LC100 Fish Leuciscus idus 1.1 mg/L 48h „Huels study, 1988 (unpublished) LC50 Fish Leuciscus idus 0.95 mg/L 48h „Huels study, 1988 (unpublished) LOEC Fish Pimephales promelas 14 µg/L 33d „Chemical Manufacturers Association (1991) Two environmental effects 4-Nonylphenol final reports 1. Chronic toxicity of Nonylphenol to the Mysid, Mysidopsis bahia: EnviroSystems Study Number 8977-CMA 2. Early life stage toxicity of Nonylphenol to the fath NOEC Fish Pimephales promelas 7.4 µg/L 33d „Chemical Manufacturers Association (1991) Two environmental effects 4-Nonylphenol final reports 1. Chronic toxicity of Nonylphenol to the Mysid, Mysidopsis bahia: EnviroSystems Study Number 8977-CMA 2. Early life stage toxicity of Nonylphenol to the fath EC100 Daphnia Daphnia magna > 400 µg/L 48h „Huels report No. DK-522, 1992 (unpublished) EC0 Daphnia Daphnia magna < 100 µg/L 48h „Huels report No. DK-522, 1992 (unpublished) EC50 Daphnia Daphnia magna 140 µg/L 48h „Huels report No. DK-522, 1992 (unpublished) LOEC Daphnia Daphnia magna > 100 µg/L 21d „Huels report No. DL-143, 1992 (unpublished) NOEC Daphnia Daphnia magna 0.024 mg/L 21d ICI PLC (1991) Nonyl Phenol: Chronic Toxicity to Daphnia Magna Report No: BLS1319/B (Interim) BL4176/B (Final) EC90 Algae Scenedesmus subspicatus (Desmodesmus subspicatus) 3.2 mg/L 72h Huels study (unpublished) EC10 Algae Scenedesmus subspicatus (Desmodesmus subspicatus) 0.5 mg/L 72h Huels study (unpublished) EC50 Algae Scenedesmus subspicatus (Desmodesmus subspicatus) 1.3 mg/L 72h Huels study (unpublished) a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 0.135 mg/L 96h IUCLID a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 0.1351 mg/L 96h EPA a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 0.14 mg/L 48h IUCLID a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata 0.36 mg/L 96h EPA a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata 0.16 mg/L 72h EPA a) Aquatic acute toxicity : EC50 Algae Desmodesmus subspicatus = 1.3 mg/L 72h IUCLID

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS**Waste treatment methods**

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations.

UN number

ADR-UN number: N.A.

DOT-UN Number: NA1993

IATA-Un number: N.A.

IMDG-Un number: N.A.

UN proper shipping name

ADR-Shipping Name: N.A.

DOT-Proper Shipping Name: Combustible Liquid, n.o.s. (Ethylacetate)

IATA-Technical name: N.A.

IMDG-Technical name: N.A.

Transport hazard class(es)

ADR-Class: N.A.

DOT-Hazard Class: COMBUSTIBLE

IATA-Class: N.A.

IMDG-Class: N.A.

Packing group

ADR-Packing Group: N.A.

DOT-Packing group: III

IATA-Packing group: N.A.

IMDG-Packing group: N.A.

Environmental hazards

Marine pollutant: No

Environmental Pollutant: N.A.

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

N.A.

Special precautions

Department of Transportation (DOT):

N.A. DOT-Special Provision(s): 148, IB3, T1, TP1

DOT-Label(s): None

DOT-Symbol: D G

DOT-Cargo Aircraft: 220 L

DOT-Passenger Aircraft: 60 L
DOT-Bulk: 241
DOT-Non-Bulk: 203
Road and Rail (ADR-RID) :
N.A.
Air (IATA) :
N.A.
Sea (IMDG) :
N.A.

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory:

All the components are listed on the TSCA inventory

TSCA listed substances:

Bisphenol A epoxy resin	is listed in TSCA	Section 8b
TITANIUM DIOXIDE	is listed in TSCA	Section 8b
ETHYLACETATE	is listed in TSCA	Section 8b
4-NONYLPHENOL, BRANCHED	is listed in TSCA	Section 8b Section 8a - PAIR Section 5a - SNUR Section 12b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

ETHYLACETATE

Section 313 - Toxic chemical list:

4-NONYLPHENOL, BRANCHED

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

ETHYLACETATE	Reportable quantity:	5000	pounds
--------------	----------------------	------	--------

CAA - Clean Air Act

CAA listed substances:

No substances listed

CWA - Clean Water Act

CWA listed substances:

No substances listed

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

TITANIUM DIOXIDE	Listed as carcinogen
------------------	----------------------

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

TITANIUM DIOXIDE

ETHYLACETATE

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

TITANIUM DIOXIDE

ETHYLACETATE

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

TITANIUM DIOXIDE

ETHYLACETATE

Canada - Federal regulations

DSL - Domestic Substances List

DSL Inventory:

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List**NDSL Inventory:**

No substances listed

NPRI - National Pollutant Release Inventory**Substances listed in NPRI:**

No substances listed

16. OTHER INFORMATION

Safety Data Sheet dated: 6/24/2021 - version 10

Additional classification information

NFPA Health: 1 = Slight

NFPA Flammability: 2 = Combustible liquid

NFPA Reactivity: 0 = Minimal

NFPA Special Risk: N.A.



Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description
H225	Highly flammable liquid and vapour.
H227	Combustible liquid
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H400	Very toxic to aquatic life.
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 2. HAZARDS IDENTIFICATION
- 4. FIRST AID MEASURES
- 5. FIRE-FIGHTING MEASURES
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 14. TRANSPORT INFORMATION
- 16. OTHER INFORMATION