

# Ultrabond ECO 360

Premium, High-Performance Adhesive for Solid Vinyl Sheet, Tile and Plank



## DESCRIPTION

*Ultrabond ECO*<sup>®</sup> 360 is a proprietary, high-performance, wet-lay and pressure-sensitive adhesive designed specifically for installing homogeneous and heterogeneous solid vinyl flooring. With its strong, durable, moisture-resistant and alkali-resistant bond, it is ideal for commercial and institutional applications. *Ultrabond ECO* 360 has an excellent open time, develops strength quickly, performs well under rolling loads and resists indentation. Its low volatile organic content makes it ideal for use in occupied buildings such as hospitals and medical centers.

## FEATURES AND BENEFITS

- Excellent indentation and shrinkage resistance
- Resistant against plasticizer migration for use with all solid vinyl flooring
- Easy trowelability for quick installation

## INDUSTRY STANDARDS AND APPROVALS

- Living Building Challenge (LBC) Red List Free: This product has been verified per the most current Red List on the LBC's Website.
- RFCI IP #1, Recommended Installation Practice for Homogeneous Sheet Flooring

## WHERE TO USE

- For the installation of sheet vinyl, luxury vinyl tile and vinyl plank

## LIMITATIONS

- Do not install over any substrates containing asbestos.
- For interior installations only
- Do not use to install nonporous floor coverings over nonporous surfaces.
- Do not apply over any adhesive residues including cutback adhesive.
- Do not install when the moisture vapor emission rate (MVER) exceeds 5 lbs. per 1,000 sq. ft. (2.27 kg per 92.9 m<sup>2</sup>) per 24 hours, when using the anhydrous calcium chloride test (ASTM F1869).
- Do not install when relative humidity of concrete slabs exceeds 80% (ASTM F2170).
- Do not install unless the temperature of the prepared concrete slab is at least 5 degrees Fahrenheit (2.8 degrees Celsius) above the dew point to avoid condensation.

## SUITABLE SUBSTRATES

- Exterior-grade plywood, Group 1, CC type
- Other approved wood underlayments (per manufacturer recommendations)
- Concrete and cement terrazzo
- Cement-based self-leveling underlayments and patching compounds
- Embossing levelers applied over existing and fully bonded ceramic tile and fully bonded vinyl composition tile (VCT) – one layer only
- Properly primed gypsum underlayments that meet the ASTM F2419 requirements for compressive strength
- Radiant-heat systems that have been properly installed

Consult MAPEI's Technical Services Department for installation recommendations regarding substrates and conditions not listed.

## SURFACE PREPARATION

- All substrates must be structurally sound, dry, solid and stable.
- The substrate should be clean and free of dust, dirt, oil, grease, paint, curing agents, concrete sealers, loosely bonded toppings, loose particles, old adhesive residues, and any other substance or condition that may prevent or reduce adhesion. All surfaces must be level, even, flat and smooth.

See the "Surface preparation requirements: Resilient/carpet adhesives" reference guide in the Floor Covering Installation Systems section of MAPEI's Website.

## MIXING

Before product use, take appropriate safety precautions. Refer to the Safety Data Sheet for details.

- Ready to use; no mixing necessary

## PRODUCT APPLICATION

Read all installation instructions thoroughly before installation.

1. Select the appropriately notched trowel (see the “Approximate Coverage” chart below).
2. Spread adhesive evenly over the subfloor, keeping the trowel at a 45-degree angle to the subfloor.
3. For working time and flash time, refer to the “Application Properties” chart below.
4. Install flooring per the flooring manufacturer’s instructions.
5. Roll the flooring with the recommended-weight roller across the width and length of the flooring surface.

## CLEANUP

1. Promptly clean any adhesive smudges from the flooring material’s surface with water while the adhesive is still fresh/wet.
2. Clean tools with water while the adhesive is still fresh/wet. Clean with mineral spirits once dried. Use caution with mineral spirits, which may be harmful to some materials.

### Product Performance Properties

Laboratory Tests	Results
Solids content	55% to 65%
VOCs (Rule #1168 of California’s SCAQMD)	Less than 34 g per L
pH	7 to 9
Density	8.3 lbs. per U.S. gal. (3.77 kg per 3.79 L), +/- 0.8 1.0 g/mL (+/- 0.1)
Flash point (ASTM D56)	> 212°F (100°C)

### Shelf Life and Product Characteristics

Shelf life	2 years when stored in original, unopened packaging at 73°F (23°C)
Storage conditions	40°F to 100°F (4°C to 38°C)
Polymer type	Vinyl acrylic
Color	Off-white
Consistency	Creamy
Trowelability	Light
Protect from traffic	24 hours for light traffic, 72 hours for heavy traffic

Protect containers from freezing in transit and storage. Provide for heated storage on site and deliver all materials at least 24 hours before work begins.

## Application Properties

	Flash time*	Working time**
Solid vinyl sheet	0 to 15 minutes	30 to 60 minutes
Vinyl tile	15 to 30 minutes or until dry to touch	2 hours
Vinyl plank	15 to 30 minutes or until dry to touch	2 hours

\* Flash time is the waiting time required before installing flooring.

\*\* Working time is the window of time for the adhesive to accept flooring.

Flash time and working time may vary based on temperature, humidity, substrate porosity, trowel size and jobsite conditions.

## Packaging

### Size

Pail: 1 U.S. gal. (3.79 L)

Pail: 4 U.S. gals. (15.1 L)

## Approximate Coverage\*\*\*

Flooring Type	Typical Trowel	Coverage
Vinyl sheet, tile and plank	1/32" x 1/16" x 1/32" (1 x 1.5 x 1 mm), U-notch	185 to 245 sq. ft. per U.S. gal. (4.53 to 6.0 m <sup>2</sup> per L)

\*\*\* Trowel dimensions are depth/width/space. Coverage shown is for estimating purposes only. Actual jobsite coverage may vary according to substrate conditions, type of trowel used and setting practices.

## RELATED DOCUMENTS

- Reference guide: "Surface preparation requirements: Resilient/carpet adhesives"<sup>†</sup>

<sup>†</sup>At [www.mapei.com](http://www.mapei.com)

## ADDITIONAL INFORMATION

Refer to the SDS for specific data related to health and safety as well as product handling.

For information on MAPEI's commitment to sustainability and transparency, as well as how MAPEI products may contribute to green building standards and certification systems, contact [sustainability\\_USA@mapei.com](mailto:sustainability_USA@mapei.com) (USA) or [sustainability-durabilite@mapei.com](mailto:sustainability-durabilite@mapei.com) (Canada).

**LEGAL NOTICE**

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement nor replace requirements per the TDS in effect at the time of the MAPEI product installation. For the most up-to-date TDS and warranty information, please visit our website at [www.mapei.com](http://www.mapei.com). **ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED MAPEI WARRANTIES.**

Before using, the user must determine the suitability of our products for the intended use, and the user alone assumes all risks and liability. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

**CONTACT INFORMATION**

**MAPEI Headquarters of North America**

1144 East Newport Center Drive  
 Deerfield Beach, Florida 33442  
 1-888-US-MAPEI (1-888-876-2734) / (954) 246-8888

**Technical Services**

U.S. and Puerto Rico:  
 Flooring: 1-800-992-6273  
 Concrete and heavy construction: 1-888-365-0614  
Canada:  
 1-800-361-9309

**Customer Service**

1-800-42-MAPEI (1-800-426-2734)

**Edition Date: June 16, 2023 MK 3000237 (22-3355)**

For the most current product data and BEST-BACKED<sup>SM</sup> warranty information,  
 visit [www.mapei.com](http://www.mapei.com).  
 All Rights Reserved. © 2023 MAPEI Corporation.

