



INNOVATIVE Fire-Stopping Solutions for Building Joints

MarinoWARE FIRE GASKET is a fire rated composite vinyl intumescent accessory that provides fire-ratings for both dynamic and static joints with both concrete and fluted deck assemblies according to UL-2079 5th Edition. Fire Gasket also provides 1 and 2 hour fire-ratings, an L-Rating of less than 1 CFM and is sound tested according to ASTM E90.



U.S. Patent No. 10,246,871

UL listings/approvals - HW-D-0515; HW-D-0514;
HW-D-0551; HW-D-0550; HW-D-0554; HW-D-0600;
HW-D-0620; HW-D-0652; HW-D-0518; HW-D-0553;
HW-D-0573.

- Fast and easy to install fire-stopping at head-of-wall building joints that does not require a fire spray over compressed mineral wool when used perpendicular to fluted decks.
- Manufactured as a pink color vinyl that is easily identified by the inspector.
- Features an intumescent strip along the inside leg of the profile where it is protected from any potential trade damages.
- Installs fully cured and has no installation temperature or humidity restrictions.
- Installs on both sides of the wall and comes in 10' lengths.
- Can be installed in the field or pre-installed to the track prior to installing track in place.
- Provides up to 1-1/2" overall unencumbered movement. L-Rated less than 1 cfm.
- Durable and is not easily damaged, once installed it will not delaminate, it will not take in water, and it will not shrink or harden over time.
- Provides premium STC ratings.
 - STC 51 on 3-5/8" 20 EQ studs unbalanced walls
 - STC 55 on 3-5/8" 20 EQ studs balanced walls



800.627.4661 | www.marinoware.com



NJ | IN | GA ©WARE Industries, Inc. 2020