

## DIAMOND MESH LATH



**USE:** Manufactured by slitting and stretching galvanized steel to form small openings to allow the keying of plaster so it will bond to the lath. Diamond Mesh Lath can be bent easily to create curved surfaces.

**SIZE:**

27" x 97" (686 mm x 2440 mm)


**MATERIAL:**

G-60

| Approx. Lath Weight |                      | Finish | Bundle |        |        |                                   |
|---------------------|----------------------|--------|--------|--------|--------|-----------------------------------|
|                     |                      |        | No.    | Weight |        | Area                              |
| lbs/yd <sup>2</sup> | (kg/m <sup>2</sup> ) | Galv.  | Pcs.   | lbs.   | (kg)   | yd <sup>2</sup> (m <sup>2</sup> ) |
| 1.75                | (0.9)                | ✓      | 10     | 35     | (15.9) | 20 (16.7)                         |
| 2.50                | (1.4)                | ✓      | 10     | 50     | (22.7) | 20 (16.7)                         |
| 3.40                | (1.8)                | ✓      | 10     | 68     | (30.8) | 20 (16.7)                         |

\*1.75 does not meet ASTM C847

## SELF-FURRING DIAMOND MESH LATH



**USE:** Uses the same mesh configuration as Diamond Mesh Lath but made with 1/4" dimple indentations spaced 1-1/2" o.c. each way. Used as exterior stucco base, column fireproofing and re-plastering over old surfaces. Available in galvanized only.

**SIZE:**

27" x 97" (686 mm x 2440 mm)

**MATERIAL:**

G-60

| Approx. Lath Weight |                      | Finish | Bundle |        |        |                                   |
|---------------------|----------------------|--------|--------|--------|--------|-----------------------------------|
|                     |                      |        | No.    | Weight |        | Area                              |
| lbs/yd <sup>2</sup> | (kg/m <sup>2</sup> ) | Galv.  | Pcs.   | lbs.   | (kg)   | yd <sup>2</sup> (m <sup>2</sup> ) |
| 1.75                | (0.9)                | ✓      | 10     | 35     | (15.9) | 20 (16.7)                         |
| 2.50                | (1.4)                | ✓      | 10     | 50     | (22.7) | 20 (16.7)                         |
| 3.40                | (1.8)                | ✓      | 10     | 68     | (30.8) | 20 (16.7)                         |

\*1.75 does not meet ASTM C847

## 3/8" HIGH RIB LATH



**USE:** Superior spanning characteristics over common expanded metal laths, suited for horizontal applications such as ceilings and soffits. Its 3/8" deep ribbed configuration is a self-furring feature. Designed for application on 24" on center.

**SIZE:**

27" x 97" (686 mm x 2440 mm)

**MATERIAL:**

G-60

| Approx. Lath Weight |                      | Finish | Bundle Quantity |        |        |                                   |
|---------------------|----------------------|--------|-----------------|--------|--------|-----------------------------------|
|                     |                      |        | No.             | Weight |        | Area                              |
| lbs/yd <sup>2</sup> | (kg/m <sup>2</sup> ) | Galv.  | Pcs.            | lbs.   | (kg)   | yd <sup>2</sup> (m <sup>2</sup> ) |
| 3.40                | (1.8)                | ✓      | 10              | 68     | (30.8) | 20 (16.7)                         |

## V-GROOVE MESH LATH



**USE:** For exterior stucco work over sheathing and as a plaster base over masonry walls. Self-furring embossed "V" groove holds the lath away from the surface to aid in the keying of stucco to the lath.

**SIZE:**

27" x 97" (686 mm x 2440 mm)

**MATERIAL:**

G-60

| Approx. Lath Weight |                      | Finish | Bundle Quantity |        |        |                                   |
|---------------------|----------------------|--------|-----------------|--------|--------|-----------------------------------|
|                     |                      |        | No.             | Weight |        | Area                              |
| lbs/yd <sup>2</sup> | (kg/m <sup>2</sup> ) | Galv.  | Pcs.            | lbs.   | (kg)   | yd <sup>2</sup> (m <sup>2</sup> ) |
| 1.75                | (0.9)                | ✓      | 10              | 35     | (15.9) | 20 (16.7)                         |
| 2.50                | (1.4)                | ✓      | 10              | 50     | (22.7) | 20 (16.7)                         |
| 3.40                | (1.8)                | ✓      | 10              | 68     | (30.8) | 20 (16.7)                         |

\*1.75 does not meet ASTM C847

For more information, please contact Marino|WARE® Technical Services at 866.545.1545

This technical information reflects the most current information available and supersedes any and all previous publications effective June 24, 2025 | MW-Accessory Catalog | © WARE Industries, Inc. 2025

**PAPERBACKED DIAMOND MESH LATH**



**USE:** Asphalt paper is factory bonded to the back. The paper conforms to Federal Specification UU-B-790A, type 1, grade D, style 2.

**SIZE:**

27" x 97" (686 mm x 2440 mm)


**MATERIAL:**

G-60

| Approx. Lath Weight |                      | Finish | Bundle |        |        |                                   |
|---------------------|----------------------|--------|--------|--------|--------|-----------------------------------|
|                     |                      |        | No.    | Weight |        | Area                              |
| lbs/yd <sup>2</sup> | (kg/m <sup>2</sup> ) | Galv.  | Pcs.   | lbs.   | (kg)   | yd <sup>2</sup> (m <sup>2</sup> ) |
| 1.75                | (0.9)                | ✓      | 10     | 40     | (18.2) | 20 (16.7)                         |
| 2.50                | (1.4)                | ✓      | 10     | 55     | (25.0) | 20 (16.7)                         |
| 3.40                | (1.8)                | ✓      | 10     | 73     | (33.2) | 20 (16.7)                         |

*\*1.75 does not meet ASTM C847*

**PAPERBACKED SELF-FURRING DIAMOND MESH LATH**



**USE:** Uses same mesh configuration as Diamond Mesh Lath but made with 1/4" dimple indentations spaced 1-1/2" o.c. each way. Used as exterior stucco base, column fireproofing and re-plastering over old surfaces. Available in galvanized only. Paper conforms to Federal Specification UU-B-790A, type 1, grade D, style 2.

**SIZE:**

27" x 97" (686 mm x 2440 mm)

**MATERIAL:**

G-60

| Approx. Lath Weight |                      | Finish | Bundle |        |        |                                   |
|---------------------|----------------------|--------|--------|--------|--------|-----------------------------------|
|                     |                      |        | No.    | Weight |        | Area                              |
| lbs/yd <sup>2</sup> | (kg/m <sup>2</sup> ) | Galv.  | Pcs.   | lbs.   | (kg)   | yd <sup>2</sup> (m <sup>2</sup> ) |
| 1.75                | (0.9)                | ✓      | 10     | 40     | (18.2) | 20 (16.7)                         |
| 2.50                | (1.4)                | ✓      | 10     | 55     | (25.0) | 20 (16.7)                         |
| 3.40                | (1.8)                | ✓      | 10     | 73     | (33.2) | 20 (16.7)                         |

*\*1.75 does not meet ASTM C847*

**PAPERBACKED V-GROOVE MESH LATH**



**USE:** Same as V-Groove with asphalt paper factory bonded to the back. Paper conforms to Federal Specification UU-B-790A, type 1, grade D, style 2.

**SIZE:**

27" x 97" (686 mm x 2440 mm)


**MATERIAL:**

G-60


| Approx. Lath Weight |                      | Finish | Bundle |        |        |                                   |
|---------------------|----------------------|--------|--------|--------|--------|-----------------------------------|
|                     |                      |        | No.    | Weight |        | Area                              |
| lbs/yd <sup>2</sup> | (kg/m <sup>2</sup> ) | Galv.  | Pcs.   | lbs.   | (kg)   | yd <sup>2</sup> (m <sup>2</sup> ) |
| 1.75                | (0.9)                | ✓      | 10     | 40     | (18.2) | 20 (16.7)                         |
| 2.50                | (1.4)                | ✓      | 10     | 55     | (25.0) | 20 (16.7)                         |
| 3.40                | (1.8)                | ✓      | 10     | 73     | (33.2) | 20 (16.7)                         |

*\*1.75 does not meet ASTM C847*

## 1-A EXPANDED CORNER BEAD



**USE:** Available in zinc or galvanized steel. Wide expanded flanges are easily flexed. Preferred for irregular corners. It provides increased reinforcement close to the nose of the bead. Zinc should be used for exterior applications.




| Product                              | Size  |        | Length |        | Carton Quantity |        |        |        |        |
|--------------------------------------|-------|--------|--------|--------|-----------------|--------|--------|--------|--------|
|                                      |       |        |        |        | No. Pcs.        | Weight |        | Length |        |
|                                      | in.   | (mm)   | ft.    | (m)    |                 | lbs.   | (kg)   | ft.    | (m)    |
| 1-A Expanded Corner Bead, Galvanized | 2-5/8 | (66.7) | 8      | (2.44) | 30              | 52     | (23.6) | 240    | (73.2) |
|                                      |       |        | 10     | (3.05) | 30              | 56     | (25.5) | 300    | (91.4) |
| 1-A Expanded Corner Bead, Zinc       | 2-5/8 | (66.7) | 10     | (3.05) | 30              | 48     | (21.8) | 300    | (91.4) |
| 1-A Expanded Corner Bead, Galvanized | 3     | (76.2) | 8      | (2.44) | 30              | 58     | (26)   | 240    | (73.2) |
|                                      |       |        | 10     | (3.05) | 30              | 63     | (29)   | 300    | (91.4) |
| 1-A Expanded Corner Bead, Zinc       | 3     | (76.2) | 10     | (3.05) | 30              | 58     | (26)   | 300    | (73.2) |

## CORNERITE




**USE:** Expanded mesh component that is used as corner reinforcement on interior angles where lath is not carried around and over non-ferrous bases such as masonry and wood lath.




| Size | Box Qty. | Length |
|------|----------|--------|
| 2"   | 75       | 8'     |
| 3"   | 75       | 8'     |

## DOUBLE X CORNER BEAD




**USE:** It is galvanized steel and has full 3-1/8" flanges. It is easily adjusted for plaster depth on columns and is ideal for structural tile corners with rough masonry. Double X Corner Bead has perforated stiffening ribs along the expanded flanges.



| Product              | Size  |        | Length |        | Carton Quantity |        |        |        |         |
|----------------------|-------|--------|--------|--------|-----------------|--------|--------|--------|---------|
|                      |       |        |        |        | No. Pcs.        | Weight |        | Length |         |
|                      | in.   | (mm)   | ft.    | (m)    |                 | lbs.   | (kg)   | ft.    | (m)     |
| Double X Corner Bead | 3-1/8 | (82.6) | 8      | (2.44) | 30              | 61     | (27.7) | 240    | (73.2)  |
|                      |       |        | 9      | (2.74) | 30              | 69     | (31.4) | 270    | (82.3)  |
|                      |       |        | 10     | (3.05) | 30              | 76     | (34.5) | 300    | (91.4)  |
|                      |       |        | 12     | (3.66) | 30              | 91     | (41.4) | 360    | (109.7) |

## STRIP LATH



**USE:** An expanded mesh product used to fill voids in wire lath construction and as a base for wire lath patches.

| Size | Box Qty. | Length |
|------|----------|--------|
| 4"   | 75       | 8'     |
| 6"   | 75       | 8'     |