

Marino\WARE® Product Submittal Data

PRODUCT NAME: 362QFH350-68

MARINO\WARE PART # 358QFH35068



PROPERTIES:

A. Web (in)	3-5/8	Yield Strength Fy (KSI)	50
B. Flange (in)	3-1/2	Tensile Strength Fu (KSI)	65
C. Lip (in)	1	Design Thickness (in)	0.0713
Mils	68	Minimum Thickness (in)	0.0677
Available Finish	G60, G90	Gauge	14

SECTION PROPERTIES

GROSS SECTION PROPERTIES

Cross Sectional Area: A (in ²)	0.862
Weight of Member: (lb/ft)	2.93
Moment of Inertia: Ix (in ⁴)	2.00
Section Modulus: Sx (in ³)	1.10
Radius of Gyration: Rx (in)	1.52
Moment of Inertia: Iy (in ⁴)	1.53
Section Modulus: Sy (in ³)	0.772
Radius of Gyration: Ry (in)	1.33

EFFECTIVE SECTION PROPERTIES - Unpunched


Moment of Inertia-Deflection: Ixe (in ⁴)	1.94
Section Modulus: Sxe (in ³)	0.922
Allowable Bending Moment: Max (in-k)	27.6
Allowable Bending Moment: Madx (in-k)	28.6
Moment of Inertia: Iye (in ⁴)	1.53
Section Modulus: Sye (in ³)	0.751
Allowable Bending Moment: Maly (in-k)	22.5
Allowable Bending Moment: Mady (in-k)	20.2
Allowable shear: Vag (k)	4,370

TORSIONAL SECTION PROPERTIES

St. Venant Torsional Constant: Jx1000 (in ⁴)	1.46
Torsional Warping Constant: Cw (in ⁶)	6.67
Shear Center to Centroid on Principal X-axis: Xo (in)	-3.43
Radius of Gyration on the Centroid Principal axis: Ro (in)	3.98
Torsional Flexural Constant: β = [1-(xo/Ro) ²]	0.258

* 33 mil and 43 mil calculated with the Direct strength Method

05.40.00 Cold-Formed Metal Framing



CODES & STANDARDS

- AISI S100-2016
- Meets IBC 2015 & 2012
- ASTM C 955 compliant
- Galvanized steel sheet meets ASTM A 1003 & A 653

GREEN INFO

- LEED v3 & LEED v4 credits available
- Contact Technical Services for more information



www.marinoware.com

For more information, please contact Marino\WARE Technical Services at 866-545-1545.

This technical information reflects the most current information available and supersedes any and all publications, effective 01/27/2017
©Copyright 2016 by Ware Industries, Inc. All rights reserved