

# Marino\WARE® Product Submittal Data

**PRODUCT NAME:** 362QFJ300-54

**MARINO\WARE PART #** 358QFJ30054



## PROPERTIES:

<b>A. Web (in)</b>	3-5/8	<b>Yield Strength Fy (KSI)</b>	50
<b>B. Flange (in)</b>	3	<b>Tensile Strength Fu (KSI)</b>	65
<b>C. Lip (in)</b>	1	<b>Design Thickness (in)</b>	0.0566
<b>Mils</b>	54	<b>Minimum Thickness (in)</b>	0.0538
<b>Available Finish</b>	G60 & G90	<b>Gauge</b>	16

## SECTION PROPERTIES

### GROSS SECTION PROPERTIES

Cross Sectional Area: <b>A</b> (in <sup>2</sup> )	0.634
Weight of Member: <b>(lb/ft)</b>	2.16
Moment of Inertia: <b>Ix</b> (in <sup>4</sup> )	1.43
Section Modulus: <b>Sx</b> (in <sup>3</sup> )	0.791
Radius of Gyration: <b>Rx</b> (in)	1.50
Moment of Inertia: <b>Iy</b> (in <sup>4</sup> )	0.863
Section Modulus: <b>Sy</b> (in <sup>3</sup> )	0.504
Radius of Gyration: <b>Ry</b> (in)	1.17

### EFFECTIVE SECTION PROPERTIES - Punched

Moment of Inertia-Deflection: <b>Ixe</b> (in <sup>4</sup> )	1.36
Section Modulus: <b>Sxe</b> (in <sup>3</sup> )	0.624
Allowable Bending Moment: <b>Malx</b> (in-k)	18.7
Allowable Bending Moment: <b>Madx</b> (in-k)	20.2
Allowable shear: <b>Van</b> (k)	1.016

### TORSIONAL SECTION PROPERTIES

St. Venant Torsional Constant: <b>Jx1000</b> (in <sup>4</sup> )	0.677
Torsional Warping Constant: <b>Cw</b> (in <sup>6</sup> )	3.83
Shear Center to Centroid on Principal X-axis: <b>Xo</b> (in)	-2.95
Radius of Gyration on the Centroid Principal axis: <b>Ro</b> (in)	3.51
Torsional Flexural Constant: <b>β</b> = [1-(xo/Ro) <sup>2</sup> ]	0.293


## CODES & STANDARDS

- AISI S100 & S240
- ASTM A 1003, A 653, & C 955
- IBC 2012, 2015, 2018, 2021

## GREEN INFO

- LEED credits available
- Contact Technical Services for more information

## 05.40.00 Cold-Formed Metal Framing



For more information, please contact Marino\WARE Technical Services at 866-545-1545.

This technical information reflects the most current information available and supersedes any and all publications, effective 8/02/2024  
©Copyright 2024 by Ware Industries, Inc. All rights reserved