


Marino\WARE® Product Submittal Data

PRODUCT NAME: RC-Max

PROPERTIES:

Width (in)	2-7/16	Yield Strength Fy (KSI)	50
Length (ft)	12	Mils	19
Available Finish	G40, G60	Design Thickness (in)	0.0190
		Minimum Thickness (in)	0.0181



USE:

For furring over wood or steel framed walls and ceilings. Reduces contact with supporting members and offers an economical means for reducing sound transmission. Refer to ASTM C754 for complete installation instructions. See RC-Max flyer for STC test information.

INSTALLATION:

WALLS: Fasten RC-Max channels to steel studs at right angles with 3/8" Type S screws and with 1-1/4" Type W screws to wood studs. Locate the RC-Max channel 2" maximum up from the floor, and within 6" of the ceiling, and at no more than 24" o.c. (16" o.c. max may be required depending on wall assembly type). Extend RC channels into all corners and attach to corner framing. Splice channels directly over studs by nesting (not butting). Mounting flange must be facing down, except for the starter row.

CEILINGS: Attach RC-Max channels at right angles to the joists. Fasten the RC-Max channel to steel joists with 1-1/4" Type S screws, and to wood joists with 1-1/4" Type W screws. Install the channels 24" o.c. when joist spacing is 16" o.c. and 16" o.c. when joists are spaced 24" o.c. One or two layers of gypsum board may be used.

CODES & STANDARDS

- ASTM C 645, E 119
- UL 263 (see specific assemblies for requirements)
- Galvanized steel sheet meets ASTM A 1003 & A 653
- Installation and storage requirements are per ASTM C 754

GREEN INFO

- LEED v4 credits available
- Contact Technical Services for more information



For more information, please contact Marino\WARE Technical Services at 866-545-1545.

This technical information reflects the most current information available and supersedes any and all publications, effective 6/5/2024
©Copyright 2024 by Ware Industries, Inc. All rights reserved