PRODUCT NAME: 400SLT250-54

1-1/2

PROPERTIES:

Slot (in)

A. Web (in)	4	Yield Strength Fy (KSI)	50
B. Flange (in)	2-1/2	Design Thickness (in)	0.0566
Mils	54	Minimum Thickness (in)	0.0538
Available Finish	G60, G90	Gauge	16

SECTION PROPERTIES

GROSS SECTION PROPERTIES

Cross Sectional Area: A (in ²)	0.5087
Weight of Member: (lb/ft)	1.7310
Section Modulus: Sx (in ³)	0.7198
Moment of Inertia: Ix (in ⁴)	1.5108
Radius of Gyration: Rx (in)	1.7233
Gross Moment of Inertia: ly (in ⁴)	0.3346
Gross Radius of Gyration: Ry (in)	1.7233

TORSIONAL SECTION PROPERTIES

St. Venant Torsional Constant: Jx1000 (in ⁴)	0.5432
Torsional Warping Constant: Cw (in ⁶)	1.0108
Shear Center to Centroid on Principal X-axis: Xo (in)	-1.646
Shear Center to Mid-Plane of the Web: m (in)	0.966
Radius of Gyration on the Centroid Principal axis: Ro (in)	2.517
Torsional Flexural Constant: $\beta \left[1-(xo/Ro)^2\right]$	0.572

CODES & STANDARDS

- AISI North American Specification 2007
- Framing meets ASTM A 1003, A 653, & C 955
- Galvanized steel sheet meets ASTM A 924

GREEN INFO LEED® v3

Available LEED® points in the following categories:

- •MR Credit 2 Construction Waste Management (1-2 points)
- •MR Credit 4 Recycled Content (1-2 points)
- •MR Credit 5 Regional Materials (1-2 points)
- Total Recycled Content: 34.9%
- Post Consumer Content: 24.3%
- Pre Consumer (Post Industrial) Content: 9.4%

FIRE RATINGS

•Approved for these UL Head Of Wall Assemblies

```
HW-D-0003, HW-D-0020, HW-D-0021, HW-D-0024, HW-D-0025, HW-D-0029, HW-D-0031, HW-D-0032, HW-D-0033, HW-D-0034, HW-D-0036, HW-D-0042, HW-D-0043, HW-D-0044, HW-D-0044, HW-D-0044, HW-D-0044, HW-D-0044, HW-D-0044, HW-D-0044, HW-D-0084, HW-D-0084, HW-D-0054, HW-D-0054, HW-D-0073, HW-D-0073, HW-D-0073, HW-D-0073, HW-D-0073, HW-D-0074, HW-D-0074, HW-D-0074, HW-D-0074, HW-D-0074, HW-D-0074, HW-D-0074, HW-D-0074, HW-D-0104, HW-D-0104, HW-D-0104, HW-D-0104, HW-D-0104, HW-D-0104, HW-D-0104, HW-D-0104, HW-D-0105, HW-D-0107, HW-D-0108, HW-D-0117, HW-D-0127, HW-D-0128, HW-D-0130, HW-D-0134, HW-D-0227, HW-D-0227, HW-D-0227, HW-D-0227, HW-D-0227, HW-D-0228, HW-D-0238, HW-D-0239, HW-D-0241, HW-D-0242, HW-D-0244, HW-D-0244, HW-D-0244, HW-D-0244, HW-D-0244, HW-D-0254, HW-D-0254, HW-D-0254, HW-D-0254, HW-D-0254, HW-D-0305, HW-D-0314, HW-D-0314, HW-D-0314, HW-D-0315, HW-D-0317, HW-D-0314, HW-D-0314, HW-D-0314, HW-D-0314, HW-D-0314, HW-D-0314, HW-D-0388, HW-D-0393, HW-D-0324, HW-D-0324, HW-D-0342, HW-D-0344, HW-D-0365, HW-D-0371, HW-D-0377, HW-D-0377, HW-D-0380, HW-D-0388, HW-D-0383, HW-D-0393, HW-D-0354, HW-D-0354, HW-D-0354, HW-D-0544, HW-D-0542, HW-D-0544, HW-D-0545, HW-D-0545, HW-D-0546, HW-D-0557, HW-D-0552
```



05.40.00 Cold-Formed Metal Framing

