#### PRODUCT NAME: 400SLT300-33

### **PROPERTIES:**

A. Web (in)	4	Yield Strength Fy (KSI)	40
B. Flange (in)	3	Design Thickness (in)	0.0346
Mils	33	Minimum Thickness (in)	0.0329
<b>Available Finish</b>	G60, G90	Gauge	20
Slot (in)	2		

#### **SECTION PROPERTIES**

# **GROSS SECTION PROPERTIES**

Cross Sectional Area: <b>A</b> (in <sup>2</sup> )	0.3459
Weight of Member: (lb/ft)	1.1769
Section Modulus: <b>Sx</b> (in <sup>3</sup> )	0.5116
Moment of Inertia: <b>Ix</b> (in <sup>4</sup> )	1.0605
Radius of Gyration: <b>Rx</b> (in)	1.7510
Gross Moment of Inertia: <b>Iy</b> (in <sup>4</sup> )	0.3380
Gross Radius of Gyration: Ry (in)	

#### **TORSIONAL SECTION PROPERTIES**

St. Venant Torsional Constant: <b>Jx1000</b> (in <sup>4</sup> )	0.1380
Torsional Warping Constant: <b>Cw</b> (in <sup>6</sup> )	1.0089
Shear Center to Centroid on Principal X-axis: Xo (in)	-2.103
Shear Center to Mid-Plane of the Web: <b>m</b> (in)	1.213
Radius of Gyration on the Centroid Principal axis: Ro (in)	2.910
Torsional Flexural Constant: <b>β</b> [1-(xo/Ro) <sup>2</sup> ]	0.478

# **CODES & STANDARDS**

- AISI North American Specification 2007
- Framing meets ASTM A 1003, A 653, & C 955
- Galvanized steel sheet meets ASTM A 924

# **GREEN INFO** LEED® v3

Available LEED® points in the following categories:

- •MR Credit 2 Construction Waste Management (1-2 points)
- •MR Credit 4 Recycled Content (1-2 points)
- •MR Credit 5 Regional Materials (1-2 points)
- •Total Recycled Content: 34.9%
- Post Consumer Content: 24.3%
- Pre Consumer (Post Industrial) Content: 9.4%

#### **FIRE RATINGS**

•Approved for these UL Head Of Wall Assemblies

```
HW-D-0003, HW-D-0020, HW-D-0021, HW-D-0024, HW-D-0025, HW-D-0029, HW-D-0031, HW-D-0032, HW-D-0033, HW-D-0034, HW-D-0036, HW-D-0042, HW-D-0043, HW-D-0044, HW-D-0045, HW-D-0045, HW-D-0045, HW-D-0054, HW-D-0054, HW-D-0058, HW-D-0059, HW-D-0062, HW-D-0063, HW-D-0071, HW-D-0072, HW-D-0073, HW-D-0076, HW-D-0079, HW-D-0083, HW-D-0083, HW-D-0085, HW-D-0085, HW-D-0088, HW-D-0088, HW-D-0089, HW-D-0101, HW-D-0102, HW-D-0103, HW-D-0105, HW-D-0106, HW-D-0106, HW-D-0107, HW-D-0113, HW-D-0129, HW-D-0129, HW-D-0130, HW-D-0134, HW-D-0134, HW-D-0154, HW-D-0154, HW-D-0154, HW-D-0154, HW-D-0152, HW-D-0152, HW-D-0173, HW-D-0173, HW-D-0173, HW-D-0184, HW-D-0185, HW-D-0185, HW-D-0191, HW-D-0194, HW-D-0205, HW-D-0209, HW-D-0210, HW-D-0217, HW-D-0218, HW-D-0221, HW-D-0222, HW-D-0223, HW-D-0227, HW-D-0227, HW-D-0228, HW-D-0238, HW-D-0239, HW-D-0241, HW-D-0244, HW-D-0243, HW-D-0244, HW-D-0244, HW-D-0255, HW-D-0257, HW-D-0263, HW-D-0263, HW-D-0265, HW-D-0310, HW-D-0313, HW-D-0315, HW-D-0316, HW-D-0316, HW-D-0316, HW-D-0311, HW-D-0317, HW-D-0317, HW-D-0316, HW-D-0318, HW-D-0388, HW-D-0389, HW-D-0371, HW-D-0377, HW-D-0371, HW-D-0380, HW-D-0388, HW-D-0388, HW-D-0396, HW-D-0371, HW-D-0377, HW-D-0354, HW-D-0345, HW-D-0364, HW-D-0366, HW-D-0364, HW-D-0366, HW-D-0366,
```



# 05.40.00 Cold-Formed Metal Framing

