Marino\WARE® Product Submittal Data

800SLT250-33

PRODUCT NAME:

PROPERTIES:


A. Web (in)	8	Yield Strength Fy (KSI)	40
B. Flange (in)	2-1/2	Design Thickness (in)	0.0346
Mils	33	Minimum Thickness (in)	0.0329
Available Finish	G60, G90	Gauge	20
Slot (in)	1-1/2		

SECTION PROPERTIES

GROSS SECTION PROPERTIES

Cross Sectional Area: A (in ²)	0.4497
Weight of Member: (lb/ft)	1.5301
Section Modulus: Sx (in ³)	1.0602
Moment of Inertia: Ix (in ⁴)	4.3181
Radius of Gyration: Rx (in)	3.0989
Gross Moment of Inertia: Iy (in ⁴)	0.2518
Gross Radius of Gyration: Ry (in)	3.0989
TORSIONAL SECTION PROPERTIES	

05.40.00 Cold-Formed Metal Framing



CODES & STANDARDS

AISI North American Specification 2007

Torsional Flexural Constant: β [1-(xo/Ro)²]

St. Venant Torsional Constant: Jx1000 (in⁴)

Shear Center to Mid-Plane of the Web: m (in)

Shear Center to Centroid on Principal X-axis: Xo (in)

Radius of Gyration on the Centroid Principal axis: Ro (in)

Torsional Warping Constant: **Cw** (in⁶)

- Framing meets ASTM A 1003, A 653, & C 955
- Galvanized steel sheet meets ASTM A 924

GREEN INFO LEED® v3

Available LEED[®] points in the following categories:

- •MR Credit 2 Construction Waste Management (1-2 points)
- MR Credit 4 Recycled Content (1-2 points)
- MR Credit 5 Regional Materials (1-2 points)
- •Total Recycled Content: 34.9%
- Post Consumer Content: 24.3%

•Pre Consumer (Post Industrial) Content: 9.4%

FIRE RATINGS

Approved for these UL Head Of Wall Assemblies

HW-D-0003, HW-D-0020, HW-D-0021, HW-D-0024, HW-D-0025, HW-D-0029, HW-D-0031, HW-D-0033, HW-D-0034, HW-D-0036, HW-D-0042, HW-D-0043, HW-D-0044, HW-D-0046, HW-D-0049, HW-D-0054, HW-D-0058, HW-D-0059, HW-D-0062, HW-D-0063, HW-D-0071, HW-D-0072, HW-D-0073, HW-D-0076, HW-D-0079, HW-D-0083, HW-D-0083, HW-D-0088, HW-D-0088, HW-D-0088, HW-D-0089, HW-D-0089, HW-D-0011, HW-D-0072, HW-D-0073, HW-D-0076, HW-D-00104, HW-D-0105, HW-D-0106, HW-D-0106, HW-D-0107, HW-D-00111, HW-D-0112, HW-D-0122, HW-D-0120, HW-D-0106, HW-D-0105, HW-D-0106, HW-D-0107, HW-D-0111, HW-D-0117, HW-D-0128, HW-D-0129, HW-D-0130, HW-D-0136, HW-D-0139, HW-D-0144, HW-D-0146, HW-D-0152, HW-D-0154, HW-D-0170, HW-D-0173, HW-D-0173, HW-D-0180, HW-D-0184, HW-D-0184, HW-D-0185, HW-D-0190, HW-D-0219, HW-D-0219, HW-D-0205, HW-D-0227, HW-D-0228, HW-D-0238, HW-D-0221, HW-D-0222, HW-D-0222, HW-D-0227, HW-D-0227, HW-D-0228, HW-D-0238, HW-D-0239, HW-D-0227, HW-D-0227, HW-D-0228, HW-D-0238, HW-D-0239, HW-D-0227, HW-D-0228, HW-D-0238, HW-D-0238, HW-D-0239, HW-D-0227, HW-D-0228, HW-D-0238, HW-D-0239, HW-D-0227, HW-D-0228, HW-D-0238, HW-D-0239, HW-D-0231, HW-D-0272, HW-D-0278, HW-D-0238, HW-D-0238, HW-D-0239, HW-D-0232, HW-D-0230, HW-D-0236, HW-D-0335, HW-D-0355, HW-D-0310, HW-D-0313, HW-D-0314, HW-D-0315, HW-D-0317, HW-D-0320, HW-D-0321, HW-D-0322, HW-D-0324, HW-D-0344, HW-D-0365, HW-D-0337, HW-D-0337, HW-D-0337, HW-D-0339, HW-D-0339, HW-D-0339, HW-D-0332, HW-D-0344, HW-D-0342, HW-D-0365, HW-D-0371, HW-D-0377, HW-D-0330, HW-D-0380, HW-D-0388, HW-D-3393, HW-D-0396, HW-D-0453, HW-D-0457, HW-D-0457, HW-D-0564, HW-D-0569, HW-D-0570, HW-D-0572, HW-D-0554, HW-D-0554, HW-D-0554, HW-D-0554, HW-D-0554, HW-D-0557, HW-D-0554, HW-D-0554, HW-D-0554, HW-D-0557, HW-D-0554, HW-D-05572, HW-D-0554, HW-D-0554, HW-D-0554, HW-D-0557, HW-D-05572

0.1794

2.9864

-1.278

0.804

3.435

0.862



www.marinoware.com

For more information, please contact Marino\WARE Technical Services at 866-545-1545.

This technical information reflects the most current information available and supersedes any and all publications, effective 12/1/2010 ©Copyright 2010 by Ware Industries, Inc. All rights reserved