

# Marino\WARE® Product Submittal Data

**PRODUCT NAME:** 362T200-68

**05.40.00 Cold-Formed Metal Framing**

**MARINO\WARE PART #** 358T214

## PROPERTIES:

<b>A. Web (in)</b>	3-5/8"	<b>Yield Strength Fy (KSI)</b>	50
<b>B. Flange (in)</b>	2"	<b>Tensile Strength Fu (KSI)</b>	65
<b>Mils</b>	68	<b>Design Thickness (in)</b>	0.0713
<b>Available Finish</b>	G60	<b>Minimum Thickness (in)</b>	0.0677
		<b>Gauge</b>	14

## SECTION PROPERTIES

### GROSS SECTION PROPERTIES

Cross Sectional Area: <b>A</b> (in <sup>2</sup> )	0.543
Weight of Member: (lb/ft)	1.85
Moment of Inertia: <b>I<sub>x</sub></b> (in <sup>4</sup> )	1.307
Section Modulus: <b>S<sub>x</sub></b> (in <sup>3</sup> )	0.675
Radius of Gyration: <b>R<sub>x</sub></b> (in)	1.552
Gross Moment of Inertia: <b>I<sub>y</sub></b> (in <sup>4</sup> )	0.221
Gross Radius of Gyration: <b>R<sub>y</sub></b> (in)	0.638

### EFFECTIVE SECTION PROPERTIES

Moment of Inertia-Deflection: <b>I<sub>x</sub></b> (in <sup>4</sup> )	1.138
Section Modulus: <b>S<sub>x</sub></b> (in <sup>3</sup> )	0.480
Allowable Bending Moment: <b>Ma</b> (in-k)	14.370
Allowable strong axis shear away from punch: <b>V<sub>ag</sub></b> (lb)	4703

### TORSIONAL SECTION PROPERTIES

St. Venant Torsional Constant: <b>J<sub>x1000</sub></b> (in <sup>4</sup> )	0.919
Torsional Warping Constant: <b>C<sub>w</sub></b> (in <sup>6</sup> )	0.564
Shear Center to Centroid on Principal X-axis: <b>X<sub>o</sub></b> (in)	-1.250
Shear Center to Mid-Plane of the Web: <b>m</b> (in)	0.743
Radius of Gyration on the Centroid Principal axis: <b>R<sub>o</sub></b> (in)	2.093
Torsional Flexural Constant: <b>β</b> [1-(x <sub>o</sub> /R <sub>o</sub> ) <sup>2</sup> ]	0.643

## CODES & STANDARDS

- AISI S100-12 & ICC ES ESR-4062
- Meets IBC 2012, 2015 & FBC 2014
- Framing meets ASTM A 1003, A 653, C 645 & C 955

## GREEN INFO

- LEED v3 & LEED v4 credits available
- Contact Technical Services for more information.

