

Marino\WARE® Product Submittal Data

PRODUCT NAME: 1400S300-54

05.40.00 Cold-Formed Metal Framing

MARINO\WARE PART # 140SX16

PROPERTIES:

A. Web (in)	14"	Yield Strength Fy (KSI)	50
B. Flange (in)	3"	Tensile Strength Fu (KSI)	65
C. Lip (in)	5/8"	Design Thickness (in)	0.0566
Mils	54	Minimum Thickness (in)	0.0538
Available Finish	G90	Gauge	16

SECTION PROPERTIES

GROSS SECTION PROPERTIES

Cross Sectional Area: A (in ²)	1.18
Weight of Member: (lb/ft)	4.012
Moment of Inertia: Ix (in ⁴)	31.462
Section Modulus: Sx (in ³)	4.495
Radius of Gyration: Rx (in)	5.166
Gross Moment of Inertia: Iy (in ⁴)	1.115
Gross Radius of Gyration: Ry (in)	0.972

EFFECTIVE SECTION PROPERTIES

Moment of Inertia-Deflection: Ixe (in ⁴)	25.548
Section Modulus: Sxe (in ³)	2.580
Allowable Local Bending Moment: Mal (in-k)	77.25
Allowable Distortional Bending Moment: Mad (in-k)	67.60
Allowable strong axis shear away from punch: Vag (lb)	1176
Allowable strong axis shear at punch: Vanet (lb)	1176

TORSIONAL SECTION PROPERTIES

St. Venant Torsional Constant: Jx1000 (in ⁴)	1.259
Torsional Warping Constant: Cw (in ⁶)	42.691
Shear Center to Centroid on Principal X-axis: Xo (in)	-1.617
Shear Center to Mid-Plane of the Web: m (in)	1.046
Radius of Gyration on the Centroid Principal axis: Ro (in)	5.500
Torsional Flexural Constant: β 1-(xo/Ro) ²	0.914



CODES & STANDARDS

- AISI S100, S240 & ICC ES ESR-4062
- ASTM A 1003, A 653, & C 955
- IBC 2012, 2015, 2018, 2021 & FBC 2020, 2023

GREEN INFO

- LEED credits available
- Contact Technical Services for more information.

Note: Web depth to thickness ratio (h/t) exceeds 200. Web stiffeners required at all support points and concentrated loads.



For more information, please contact Marino\WARE Technical Services at 866-545-1545.

This technical information reflects the most current information available and supersedes any and all publications, effective 11/5/2023
©Copyright 2023 by Ware Industries, Inc. All rights reserved